



DTH2 - Dual Tech Hybrid Exit

Photoluminescent/LED Thin Die-Cast Exit Sign

DATE:

PROJECT

COMMENTS:



FEATURES

- Thin architectural profile constructed from die cast aluminum alloy.
- Internal LEDs are used to charge the photoluminescence material internally for an eco-friendly solution.
- Maintenance-free LED light source illuminates the letters in normal AC power.
- Non-electrical photoluminescence illuminates the letters when AC power fails.
- Requires only 2 watts of power to operate.
- Eliminates the need for any auxiliary power, batteries, or external charging light sources.
- Optional vandal resistant and tamper proof polycarbonate shield available, makes the sign suitable for floor proximity applications.
- Zero current, low-voltage disconnect used to prevent battery from being overly discharged.
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life.
- 120/277 VAC with field selectable inputs.
- 100' viewing distance in both the photoluminescence and LED operation modes.

ORDERING INFORMATION *DTH2-1-BA-MB*

1. SERIES	2. FACE COUNT	3. FRAME COLOR	4. MOUNTING	5. OPTIONS
DTH2	-	-	-	-
	1 Single 2 Double U Universal	BA Brushed Aluminum BK Black WH White	MB Back Mount MPA 12" Swivel Pendant Kit MPB 24" Swivel Pendant Kit MPC 36" Swivel Pendant Kit MPD 48" Swivel Pendant Kit MTEB Top/End/Back Mount	BLANK = NO OPTION VR 1/8" Vandal Resistant Lens

ACCESSORIES; ORDER SEPARATELY

- WG-16.0LX11.0WX3.0D** = Wireguard, Length: 16", Width: 11", Depth: 3"

NOTE: Wireguards only available with Back Mount.

SPECIFICATIONS

CONSTRUCTION

- Injection molded internal cavity reflector provides easy installation and maintenance with perfectly even legend illumination.
- Two piece, heavy-duty walls are constructed from die cast aluminum alloy.
- Front stencil face has an overlapping light seal for no light leakage.
- Hidden knock out access points with a universal pattern.

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA type, universal field selectable chevrons.

TEMPERATURE RATING

- 50°F to 104°F



APPROVALS

- UL 924
- UL 924 Damp Location Approved
- UL 924 Floor Proximity (with VR option)
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- NAFTA
- BAA Compliant

WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS



0.625" Single or
Double face