

---

# Product datasheet

## DULUX F 36 W/830 106 V 2G10

OSRAM DULUX F | Flat CFLni, 2 tubes, with 4-pin base for ECG/CCG operation



## Product datasheet

### Technical data


#### Electrical data

Nominal current	0.44 A A
-----------------	----------

#### Photometrical data

Light color (designation)	LUMILUX Warm White
Rated LLMF at 4,000 h	0.86
Rated LLMF at 6,000 h	0.83
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.77
Luminous flux	2800 lm
Color rendering index Ra	≥80

#### Dimensions & weight



Overall length	221.00 mm
Tube diameter	17,5 mm
Length with base excl. base pins/connection	215,0 mm
Product weight	99.87 g

#### Temperatures & operating conditions

Ambient temperature range	-5...+40 °C
---------------------------	-------------

#### Lifespan

Service life	9000 h
Nominal lamp life time	13000 h

#### Additional product data

Mercury content	2.5 mg
-----------------	--------

## Product datasheet

Appropriate disposal acc. to WEEE	Yes
-----------------------------------	-----

### Certificates & standards

Energy efficiency class	G
Energy consumption	38.00 kWh/1000h

### Country specific categorizations

ILCOS	FSD-36/830-E-2G10-90/217
-------	--------------------------

### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300299051
Declaration No. in SCIP database	In work

### Equipment / Accessories

– Suitable for operation on electronic and conventional control gear

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300299051	DULUX F 36 W/830 106 V 2G10	Shipping carton box 10 Pieces Folding carton box	275 mm x 105 mm x 245 mm	7.07 dm <sup>3</sup>	1631.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

For more information on QUICKTRONIC electronic control gear go to

▶ [www.osram.com/QUICKTRONIC](http://www.osram.com/QUICKTRONIC)