

**LED ENCLOSED RATED OMNIDIRECTIONAL A-LAMP**  
**A19 GEN 6 SERIES**



6W, 9W & 11W



15W



GU24 Base



**PRODUCT DESCRIPTION:**

MaxLite's LED enclosed rated Omnidirectional A-Line lamp replicate true A19 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces and table and floor lamps.

**FEATURES:**

- 6W, 480lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 11W, 1100lm, 75W Inc. replacement
- 15W, 1600lm, 100W Inc. replacement
- Dimmable down to 10%
- Power factor: ≥ 0.90
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- Volts: 120V
- ENERGY STAR pending - ETA: End of May
- Available in E26 and GU24 base
- Suitable for dry and damp locations
- Suitable for use in fully enclosed luminaires
- Five year limited warranty

**APPLICATIONS**

- Pendants
- Table and floor lamps
- Sconces

**ORDERING:**

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: E9A19DLED27/G6		
		DLED	/G6	
FAMILY	BASE	DIMMABILITY	CCT	GENERATION
<b>E6A19=</b> 6 watts, A19 <b>E9A19=</b> 9 watts, A19 <b>E11A19=</b> 11 watts, A19 <b>E15A19=</b> 15 watts, A19	<b>(OMIT)=</b> E26 <b>GU=</b> GU24	<b>DLED=</b> Dimmable	<b>27=</b> 2700K <b>30=</b> 3000K <b>40=</b> 4000K	<b>/G6=</b> Generation 6

**NOTES:**

1. E6A19DLED27/G6 is available in bulk pack (50pcs)
2. E9A19DLED27/G6 is available in 4-Packs and bulk pack (50pcs)

Specifications are subject to change without notice.

**SPECIFICATIONS:**

ITEM	SPECIFICATION	DETAILS			
		E6A19DLEDxx/G6	E9A19DLEDxx/G6	E11A19DLEDxx/G6	E15A19DLEDxx/G6
GENERAL PERFORMANCE	Power Consumption	6W	9W	11W	15W
	Lumens Delivered	480	800	1100	1600
	Efficacy (lm/w)	80	88	100	106
	CRI	≥80			
	Color Temperature (CCT)	2700K, 3000K, 4000K			
	Lumen Maintenance (L70)	25,000 Hours			
ELECTRICAL	Power Factor	≥0.9			
	Input Voltage	120V			
PHYSICAL	Base Type	E26			
	Operating Temperature	-4°F - 104°F			
CERTIFICATION	Certification	UL Listed, FCC, RoHS Compliant			
	Environment	Dry, Damp			
	Warranty	5 Year Limited			

Lighting layouts and spacing criteria available upon request

**ORDERING:**

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
<b>E26 Base</b>									
14099390	E6A19DLED27/G6	☆	6	40W Inc.	480	80	80	2700K	2.36" x 4.25"
14099391	E6A19DLED27/G6/BP	☆	6	40W Inc.	480	80	80	2700K	
14099392	E6A19DLED30/G6	☆	6	40W Inc.	480	80	80	3000K	
14099393	E6A19DLED40/G6	☆	6	40W Inc.	480	80	80	4000K	
14099394	E9A19DLED27/G6	☆	9	60W Inc.	800	88	80	2700K	
14099395	E9A19DLED27/G6/4P	☆	9	60W Inc.	800	88	80	2700K	
14099396	E9A19DLED27/G6/BP	☆	9	60W Inc.	800	88	80	2700K	
14099397	E9A19DLED30/G6	☆	9	60W Inc.	800	88	80	3000K	
14099398	E9A19DLED40/G6	☆	9	60W Inc.	800	88	80	4000K	
14099399	E11A19DLED27/G6	☆	11	75W Inc.	1100	100	80	2700K	
14099400	E11A19DLED30/G6	☆	11	75W Inc.	1100	100	80	3000K	
14099401	E11A19DLED40/G6	☆	11	75W Inc.	1100	100	80	4000K	
14099402	E15A19DLED27/G6	☆	15	100W Inc.	1600	106	80	2700K	
14099403	E15A19DLED30/G6	☆	15	100W Inc.	1600	106	80	3000K	
14099404	E15A19DLED40/G6	☆	15	100W Inc.	1600	106	80	4000K	

☆ ENERGY STAR pending

Specifications are subject to change without notice.

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
<b>GU24 Base</b>									
14099405	E6A19GUDLED27/G6	☆	6	40W Inc.	480	80	80	2700K	2.36" x 4.21"
14099406	E6A19GUDLED30/G6	☆	6	40W Inc.	480	80	80	3000K	
14099407	E6A19GUDLED40/G6	☆	6	40W Inc.	480	80	80	4000K	
14099408	E9A19GUDLED27/G6	☆	9	60W Inc.	800	89	80	2700K	
14099409	E9A19GUDLED30/G6	☆	9	60W Inc.	800	89	80	3000K	
14099410	E9A19GUDLED40/G6	☆	9	60W Inc.	800	89	80	4000K	
14099411	E11A19GUDLED27/G6	☆	11	75W Inc.	1100	100	80	2700K	
14099412	E11A19GUDLED30/G6	☆	11	75W Inc.	1100	100	80	3000K	
14099413	E11A19GUDLED40/G6	☆	11	75W Inc.	1100	100	80	4000K	
14099414	E15A19GUDLED27/G6	☆	15	100W Inc.	1600	106	83	2700K	2.36" x 4.61"
14099415	E15A19GUDLED30/G6	☆	15	100W Inc.	1600	106	83	3000K	
14099416	E15A19GUDLED40/G6	☆	15	100W Inc.	1600	106	83	4000K	

☆ ENERGY STAR pending

**Compatible dimmer list coming soon**