

**LED OMNIDIRECTIONAL A-LAMP**  
**A19 NON-DIM SERIES GEN 3**



9W & 11W



15W



**PRODUCT DESCRIPTION:**

MaxLite's LED Omnidirectional A-Line lamp replicate true A19 incandescents that produces even light in all directions. They are suited to a wide variety of residential and commercial applications, pendants, wall sconces and table and floor lamps.

**FEATURES:**

- 9 Watts (60W Equivalent, 800 Lumens)
- 11 Watts (75W Equivalent, 1100 Lumens)
- 15 Watts (100W Equivalent, 1600 Lumens)
- 15,000 hour life (L70 standards)
- CCT: 2700K & 3000K Standard (4000K & 5000K, special order only. Please call MaxLite for more information.)
- CRI:  $\geq 80$
- Non-Dimmable
- Saves more than 84 percent on energy
- Power factor:  $\geq 0.6$
- Standard E26 base
- ENERGY STAR certified
- Mercury-free
- RoHS Compliant
- Three year limited warranty

**APPLICATIONS**

- Table and floor lamps
- Sconces
- Approved for use in totally enclosed fixtures or recessed lighting
- Suitable for use in damp locations

**ORDERING:**

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: E9A19ND30/G3

FAMILY	BASE	DIMMABILITY	CCT
<b>E9A19=</b> Enclosed 9 watts, A19 <b>E11A19=</b> Enclosed 11 watts, A19 <b>E15A19=</b> Enclosed 15 watts, A19	<b>(OMIT)=</b> E26	<b>ND=</b> Non-Dimmable	<b>27/G3=</b> 2700K Gen 3 <b>30/G3=</b> 3000K Gen #

**NOTES:**

1. 3000K models are available in 9W & 15W only

**SPECIFICATIONS:**

		9A19NDxx/G3	11A19NDxx/G3	15A19NDxx/G3
ITEM	SPECIFICATION	DETAILS		
GENERAL PERFORMANCE	Power Consumption	9W	11W	15W
	Lumens Delivered	800	1,100	1,600
	Efficacy (lm/w)	89	100	106
	CRI	≥ 82		
	Color Temperature (CCT)	2700K, 3000K	2700K	2700K, 3000K
	Lumen Maintenance (L70)	15,000 Hours		
	Dimmable	No		
ELECTRICAL	Power Factor	≥0.6		
	Input Voltage	120V		
PHYSICAL	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
CERTIFICATION	Environment	Dry, Damp		
	Warranty	3 Year Limited		

Lighting layouts and spacing criteria available upon request

**ORDERING:**

ORDER CODE	MODEL NUMBER	ENERGY STAR	INPUT WATTAGE	EQUIVALENT WATTAGE	DELIVERED LUMENS	EFFICACY (lm/W)	CRI	CCT (K)	DIMENSIONS (D" x MOL")
<b>E26 Base</b>		★							
14099661	E9A19ND27/G3	★	9	60W Inc.	800	89	82	2700K	2.36" x 4.25"
14099663	E9A19ND30/G3	★	9	60W Inc.	800	89	83	3000K	
14099662	E9A19ND27/G3/4P	★	9	60W Inc.	800	89	82	2700k	
14099664	E11A19ND27/G3	★	11	75W Inc.	1100	100	84	2700K	
14099666	E15A19ND27/G3	★	15	100W Inc.	1600	106	84	2700K	2.36" x 4.55"
14099668	E15A19ND30/G3	★	15	100W Inc.	1600	106	84	3000K	

★ ENERGY STAR certified