



# Bottom Turn Knob Lampholders

660W 250V




## Bottom Turn Knob Lampholders

### FEATURES

- Molded of high-temperature thermoset plastic.
- Screw terminals are backed out – ready for wiring.

### Medium Base Lampholders – Phenolic Body

Rating W	V	Description	Nipple Length	Bracket Length	Finish – Nipple & Nuts	Catalog No.
660	250	0.375" (9.53mm) 1/8-27 Nipple with Removable Knob	0.375" (9.53mm)	0.69" (17.46mm)	Nickel	1198



# Incandescent Lampholders

250W 250V  
660W 250V

## Incandescent Lampholders

### FEATURES

- Screw terminals are backed out – ready for wiring.
- Interiors have removable turn knobs.
- Hickeys and nipples are threaded for mounting on standard fixture, lamp stems or brackets.

### Incandescent Medium Base Fixture Sockets

Rating W	V	Description	Switch	Bracket Height	Overall Height	Catalog No.
660	250	Porcelain – Screw Terminals	Keyless	0.44" (11.11mm)	1.88" (47.8mm)	969*†
660	250	Phenolic – Screw Terminals	Keyless	0.44" (11.11mm)	1.88" (47.8mm)	968*



### Electrolier Medium Base Sockets 0.13" (3.18mm) – IPS Bracket – Screw Terminals

Rating W	V	Description	Switch	Bracket Height	Overall Height	Catalog No.
250	250	One Circuit	Turn Knob	0.50" (12.7mm)	2.062" (52.4mm)	918*
250	250	Two Circuit (3-Way)	Turn Knob	0.50" (12.7mm)	2.25" (57.2mm)	926



\*Not NOM certified

†Not UL