



# Halogen reflector

## EKE 150W 21V 24PK

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

### Product data

<b>General Information</b>		<b>Voltage (Nom)</b> 21 V	
Base	GX5.3 [ GX5.3]	<b>Controls and Dimming</b>	
Philips Code	13629	Dimmable	Yes
ANSI Code	EKE-ENA	<b>Mechanical and Housing</b>	
LIF Code	-	Bulb Material	Quartz-UV Open
Operating Position	Base Down +/- 90 D [ Base Down +/- 90 D]	Reflector Finish	Smooth
Main Application	Projection	Filament Dimensions WxH	-
Life to 50% Failures (Nom)	200 h	<b>Luminaire Design Requirements</b>	
<b>Light Technical</b>		Bulb Temperature (Max)	900 °C
Luminous Flux (Rated) (Nom)	900 lm	Pinch Temperature (Max)	400 °C
Color Rendering Index (Nom)	100	Working Distance WD	45 mm
<b>Operating and Electrical</b>			
Power (Rated) (Nom)	150 W		


## Halogen reflector

### Product Data

Order product name	13629 150W GX5.3 21V 1CT/24
EAN/UPC - Product	8711500410733
Order code	315929
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	24
Material Nr. (12NC)	924010319894
Net Weight (Piece)	0.025 kg

### Dimensional drawing



13629 150W GX5.3 21V

### Product

13629 150W GX5.3 21V 1CT/24

