

COMPATIBLE CLASS 2 POWER SUPPLY (REQUIRED)

	Model		Input	Output	Dimming	Description
	EN-2460-RB2-T EN-24100-RB2-T	Remote	120VAC 120VAC	24VAC / 60W 24VAC / 96W	100%-5% ELV	Includes a 6' lead wire. UL Class 2 output.
	PS-24DC-U60R-T PS-24DC-U96R-T	Remote	120-277VAC	24VDC / 60W 24VDC / 96W	100%-5% ELV, TRIAC	Includes a 6' lead wire. UL Class 2 output.
	EN-24100-277-RB2-T	Remote	277VAC	24VDC / 96W	100%-5% 0-10V	Includes a 6' lead wire. UL Class 2 output.
	EN-2460-P-AR-T EN-24100-P-AR-T	Plug-in	120VAC 120VAC	24VAC / 60W 24VAC / 96W	Non Dimmable	Includes a 6' lead wire. UL Class 2 output.
	EN-D24100-120-R	Wall Dimmer & Driver	120VAC	24VDC / 96W	Integral	Includes a 6' lead wire. UL Class 2 output.

SMART CONTROL

	Model	Description
	CT-96-SM	Includes a 96W 24VDC Power Supply (EN-24DC096-UNV-RB2), wireless controller (CTR-WDMX-24VDC) and a ready-to-connect lead wire with an InvisiLED Connector (LED-TC-B-2-WT) <i>See page 251 for optional WallStation.</i>

Transform your interiors with the InvisiLED® Smart Home Kit, designed exclusively for InvisiLED Lite, Pro, Pro 2 and Pro 3 Tape. Crafted to simplify your life and elevate your everyday lighting experience, control your LED tape seamlessly via Wi-Fi using the MyWAC app with devices you already own, including Amazon Alexa and Google Home. Offers on/off activation and up/down dimming capability for 24VDC systems and high-output tape lighting applications. Or use DMX to control your popular control platforms.

EXAMPLE INSTALLATION FOR WIRELESS AND DMX CONTROL

