



HALOGEN LAMPS



Bulb	Base	Product Number	Footnotes	Product Code	ANSI	Description	Pkg. Qty.	Volts	Lumens	Color Temp	Avg. Life	Design Filament	MOL	Beam Spread
 J Type Double Ended continued														
500 WATT														
T3	R7s	107196	3,8,9	Q500T3C	DVS	Clear 118mm	10/500	130	9500	3000	2000	C-8	4.65"	-
		127196	3,8,9	Q500T3C/120	FCL	Clear 118mm	10/500	120	9500	3000	2000	C-8	4.65"	-
1000 WATT														
T3	R7s	107198	3,8,9	Q1000T3C	-	Clear 254mm	10/500	240	22000	3050	2000	C-8	10.00"	-
1500 WATT														
T3	R7s	107200	3,8,9	Q1500T3C	-	Clear 254mm	10/500	240	33000	3050	2000	C-8	10.00"	-
		107202	3,8,9	Q1500T3C/277	-	Clear 254mm	10/500	277	33000	3050	2000	C-8	10.00"	-
 JD Type Single Ended														
35 WATT														
T4	BA15d	107035	3	Q35CL/DC	-	Clear	10/400	130	380	2700	2000	CC-2V	1.97"	-
	E11	107034	3	Q35CL/MC	-	Clear	10/400	130	380	2700	2000	CC-2V	1.97"	-
50 WATT														
T4	BA15d	107018	3	Q50CL/DC	-	Clear	10/400	130	750	2800	2000	CC-2V	1.97"	-
	E11	107019	3	Q50CL/MC	-	Clear	10/400	130	750	2800	2000	CC-2V	1.97"	-
75 WATT														
T4	BA15d	107021	3	Q75CL/DC	-	Clear	10/400	130	1250	2850	2000	CC-8	2.40"	-
	E11	107020	3	Q75CL/MC	-	Clear	10/400	130	1250	2850	2000	CC-8	2.68"	-
		127020	3	Q75CL/MC/120	-	Clear	10/400	120	1250	2850	2000	CC-8	2.68"	-
100 WATT														
T4	BA15d	107025	3	Q100CL/DC	-	Clear	10/400	130	1700	2950	2000	CC-8	2.40"	-
		127025	3	Q100CL/DC/120	ESR	Clear	10/400	120	1700	2950	2000	CC-8	2.40"	-
	E11	107024	3	Q100CL/MC	-	Clear	10/400	130	1700	2950	2000	CC-8	2.68"	-
		127024	3	Q100CL/MC/120	ESN	Clear	10/400	120	1700	2950	2000	CC-8	2.68"	-
150 WATT														
T4	BA15d	107029	3	Q150CL/DC	-	Clear	10/400	130	2400	2950	2000	CC-8	2.40"	-
		71102	3	Q150CL/DC/120	ETC	Clear	10/200	120	2400	2950	2000	CC-8	2.40"	-
		107027	X 3	Q150DC	-	Frost	10/400	130	2280	2950	2000	CC-8	2.40"	-
	E11	107028	3	Q150CL/MC	-	Clear	10/400	130	2400	2950	2000	CC-8	2.72"	-
		127028	X	Q150CL/MC/120	-	Clear	10/400	120	2400	2950	2000	CC-8	2.72"	-
		107026	3	Q150MC	-	Frost	10/400	130	2280	2950	2000	CC-8	2.72"	-
		71100	3	Q150MC/120	ETH	Frost	10/200	120	2280	2950	2000	CC-8	2.72"	-

Ⓔ Means this lamp meets Federal Minimum Efficiency standards.
Halogen lamp symbols, footnotes and abbreviations are located on pages 131-133.