

## TRIPHOSPOR T10

Ø 32mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
20	T-10	Bi-Pin	2050L	F20T10/850	30	85	1100	20,000	5000°	24"
20	T-10	Bi-Pin	2033L	F20T10/841	30	85	1100	20,000	4100°	24"
20	T-10	Bi-Pin	2035L	F20T10/835	30	85	1100	20,000	3500°	24"
20	T-10	Bi-Pin	2029L	F20T10/830	30	85	1100	20,000	3000°	24"
40	T-10	Bi-Pin	4050L	F40T10/850	30	85	2600	20,000	5000°	48"
40	T-10	Bi-Pin	4033L	F40T10/841	30	85	2600	20,000	4100°	48"
40	T-10	Bi-Pin	4035L	F40T10/835	30	85	2600	20,000	3500°	48"
40	T-10	Bi-Pin	4029L	F40T10/830	30	85	2600	20,000	3000°	48"

## STANDARD T12

Ø 38mm. - G13 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
20	T-12	Bi-Pin	2054L2	F20T12/764	30	70	1100	20,000	6400°	24"
20	T-12	Bi-Pin	2050L2	F20T12/750	30	70	1100	20,000	5000°	24"
20	T-12	Bi-Pin	2033L2	F20T12/741	30	70	1100	20,000	4100°	24"
20	T-12	Bi-Pin	2035L2	F20T12/735	30	70	1100	20,000	3500°	24"
20	T-12	Bi-Pin	2029L2	F20T12/730	30	70	1100	20,000	3000°	24"
34	T-12	Bi-Pin	3454L2	F34T12/764	30	70	2450	20,000	6400°	48"
34	T-12	Bi-Pin	3450L2	F34T12/750	30	70	2450	20,000	5000°	48"
34	T-12	Bi-Pin	3433L2	F34T12/741	30	70	2450	20,000	4100°	48"
34	T-12	Bi-Pin	3435L2	F34T12/735	30	70	2450	20,000	3500°	48"
34	T-12	Bi-Pin	3429L2	F34T12/730	30	70	2450	20,000	3000°	48"
40	T-12	Bi-Pin	4054L2	F40T12/764	30	70	2600	20,000	6400°	48"
40	T-12	Bi-Pin	4050L2	F40T12/750	30	70	2600	20,000	5000°	48"
40	T-12	Bi-Pin	4033L2	F40T12/741	30	70	2600	20,000	4100°	48"
40	T-12	Bi-Pin	4035L2	F40T12/735	30	70	2600	20,000	3500°	48"
40	T-12	Bi-Pin	4029L2	F40T12/730	30	70	2600	20,000	3000°	48"

## MINI T5

Ø 16mm. - G5 cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
6	T-5	Bi-Pin	0654M	F6T5/Daylight	10	75	240	20,000	6100°	9"
6	T-5	Bi-Pin	0633M	F6T5/Cool Light	10	65	270	20,000	4300°	9"
8	T-5	Bi-Pin	0854M	F8T5/Daylight	10	75	330	20,000	6100°	12"
8	T-5	Bi-Pin	0833M	F8T5/Cool Light	10	65	385	20,000	4300°	12"
13	T-5	Bi-Pin	1354M	F13T5/Daylight	10	75	720	20,000	6100°	21"
13	T-5	Bi-Pin	1333M	F13T5/Cool Light	10	65	830	20,000	4300°	21"

## CIRCULAR

Ø 29mm. - 4 pins G10q cap

Watts	Bulb	Base	Product Code	Order Code	Pkg	CRI	Lumens	Life (HRS)	Kelvin	MOL
22	FC	Bi-Pin	2254C	FC22T9/Daylight	12	75	900	20,000	6100°	8 1/4"
22	FC	Bi-Pin	2233C	FC22T9/Cool Light	12	65	1000	20,000	4300°	8 1/4"
32	FC	Bi-Pin	3254C	FC32T9/Daylight	12	75	1700	20,000	6100°	12"
32	FC	Bi-Pin	3233C	FC32T9/Cool Light	12	65	1700	20,000	4300°	12"
40	FC	Bi-Pin	4054C	FC40T9/Daylight	12	75	2200	20,000	6100°	16"
40	FC	Bi-Pin	4033C	FC40T9/Cool Light	12	65	2300	20,000	4300°	16"



- Life 20,000 h
- Up to 80% power saving.