



ProLume.
◀ Programmed Start T5

FLUORESCENT

ProLume® Programmed Start T5



Energy Efficient

- Delivers up to 104 LPW with a compact design
- Improved tri-phosphor coating provides superior color rendering - up to 86 CRI
- Excellent lumen maintenance - up to 94%

Technical Data

- Low profile
- Minimum starting temperature -15°F
- Peak operating temperature 95°F
- Uniform surface brightness regardless of length
- Special coating on glass wall prevents glass and phosphor mercury absorption
- 3000, 3500, 4100, and 5000K

Benefits Over Standard T8 or T12 Lamps

- Delivers superior optical control
- All T5 lamps have the same surface brightness for uniform lighting
- Higher peak operating temperatures, 95°F vs. 77°F for T8 and T12 lamps
- 2-Year Guarantee

Applications

- Cove lighting
- Display lighting
- Indirect fixtures
- High-bay fixtures

The Eco-Shield® mark indicates this product is TCLP compliant.



ISO 9001 Certified



where there's light,
there's halco®

Bulb Type	Watts	Base	Product #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Mean Lumens	Avg Rated Life	Commercial Life**	Nom Length (in)	
PROGRAMMED START ECO-SHIELD®														
T5	14	G5	30117	F14T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	1350	1270	24000	30000	22"	
T5	14	G5	30118	F14T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	1350	1270	24000	30000	22"	
T5	14	G5	30119	F14T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	1350	1270	24000	30000	22"	
T5	21	G5	30125	F21T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	2100	1990	24000	30000	34"	
T5	21	G5	30126	F21T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	2100	1990	24000	30000	34"	
T5	21	G5	30127	F21T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	2100	1990	24000	30000	34"	
T5	24	G5	30134	F24T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	2000	1900	24000	30000	22"	
T5	24	G5	30135	F24T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	2000	1900	24000	30000	22"	
T5	35	G5	35049	F35T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	3650	3450	24000	30000	58"	
T5	35	G5	35050	F35T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	3650	3450	24000	30000	58"	
T5	37	G5	35060	F39T5/830/HO/ECO/IC	830 Phosphor High Output Eco-Shield®	25	3000	86	3500	3320	24000	30000	34"	
T5	37	G5	35061	F39T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	3500	3320	24000	30000	34"	
T5	37	G5	35062	F39T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	3500	3320	24000	30000	34"	
T5	28	G5	35041	F28T5/830/ECO/IC	830 Phosphor Eco-Shield®	25	3000	86	2900	2750	24000	30000	46"	
T5	28	G5	35042	F28T5/835/ECO/IC	835 Phosphor Eco-Shield®	25	3500	86	2900	2750	24000	30000	46"	
T5	28	G5	35043	F28T5/841/ECO/IC	841 Phosphor Eco-Shield®	25	4100	86	2900	2750	24000	30000	46"	
T5	28	G5	35044	F28T5/850/ECO/IC	850 Phosphor Eco-Shield®	25	5000	86	2900	2750	24000	30000	46"	
☼	T5	49	G5	35085	F49T5/835/HO/ECO	835 Phosphor High Output Eco-Shield®	25	3500	86	4900	4700	24000	30000	46"
☼	T5	49	G5	35088	F49T5/841/HO/ECO	841 Phosphor High Output Eco-Shield®	25	4100	86	4900	4700	24000	30000	46"
☼	T5	49	G5	35089	F49T5/850/HO/ECO	850 Phosphor High Output Eco-Shield®	25	5000	86	4900	4700	24000	30000	46"
T5	54	G5	35081	F54T5/830/HO/ECO/IC	830 Phosphor High Output Eco-Shield®	25	3000	86	5000	4850	24000	30000	46"	
T5	54	G5	35082	F54T5/835/HO/ECO/IC	835 Phosphor High Output Eco-Shield®	25	3500	86	5000	4850	24000	30000	46"	
T5	54	G5	35083	F54T5/841/HO/ECO/IC	841 Phosphor High Output Eco-Shield®	25	4100	86	5000	4850	24000	30000	46"	
T5	54	G5	35084	F54T5/850/HO/ECO/IC	850 Phosphor High Output Eco-Shield®	25	5000	86	5000	4850	24000	30000	46"	
☼	T5	54	G5	35086	F54T5/865/HO/ECO/IC	865 Phosphor High Output Eco-Shield®	25	6500	86	5000	4850	24000	30000	46"
☼	T5	80	G5	35087	F80T5/835/HO/ECO	835 Phosphor High Output Eco-Shield®	25	3500	86	7000	6650	24000	30000	57.1"
☼	T5	80	G5	35090	F80T5/841/HO/ECO	841 Phosphor High Output Eco-Shield®	25	4100	86	7000	6650	24000	30000	57.1"
ULTRA EFFICIENT T5 EXTENDED LIFE														
T5	28	G5	35046	F28T5/835/ECO/XL	835 Phosphor Eco-Shield®	25	3500	86	2800	2660	40000	46000	46"	
T5	28	G5	35047	F28T5/841/ECO/XL	841 Phosphor Eco-Shield®	25	4100	86	2800	2660	40000	46000	46"	
T5 HIGH OUTPUT EXTENDED LIFE														
T5	54	G5	35070	F54T5/835/HO/ECO/XL	835 Phosphor Eco-Shield®	25	3500	86	5000	4790	40000	46000	46"	
T5	54	G5	35071	F54T5/841/HO/ECO/XL	841 Phosphor Eco-Shield®	25	4100	86	5000	4790	40000	46000	46"	
T5	54	G5	35072	F54T5/850/HO/ECO/XL	850 Phosphor Eco-Shield®	25	5000	86	5000	4790	40000	46000	46"	
CIRCLINE PROGRAMMED START 2GX13														
T5	22	2GX13	109080	FC22T5/835	835 Phosphor	20	3500	82	1900	1800	10000	12500	9"	
T5	22	2GX13	109082	FC22T5/841	841 Phosphor	20	4100	82	1900	1800	10000	12500	9"	
T5	40	2GX13	109084	FC40T5/835	835 Phosphor	20	3500	82	3350	3150	10000	12500	12"	
T5	40	2GX13	109086	FC40T5/841	841 Phosphor	20	4100	82	3350	3150	10000	12500	12"	

☼ NEW ITEM!

** Based on commercial standards of 12 hours per start.

☼ Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.

Visit www.lamprecycle.org for disposal information for your state or local government.