Presented By: **Candela Corporation** Contact Phone: (800) 922-9226 Contact E-mail: sales@candelacorp.com

**Customer Name:** Project Name: Fixture Type:



# Lighting

# 72864 - F28T8/XLSPX35ECO

GE Ecolux® UltraMax™ Starcoat® T8


• Passes TCLP, which can lower disposal costs.











# **CAUTIONS & WARNINGS**

- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.
- Lamp may shatter and cause injury if broken
- Wear safety glasses and gloves when handling lamp.
- Do not use excessive force when installing lamp.

#### Warning

- · Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- · Risk of Electric Shock
- Turn power off before inspection, installation or removal.

# **GRAPHS & CHARTS**

**Lamp Mortality** 



#### **GENERAL CHARACTERISTICS**

Lamp Type Linear Fluorescent - Straight

Linear

Bulb T8 Medium Bi-Pin (G13) Base

Wattage 28 Voltage 115 Rated Life 36000 hrs Rated Life (instant start) @ 24000 h @ 3 h 30000 h @ 12 h Time

Rated Life (rapid start) @ Time 36000.0 @ 3.0/42000.0 @

12.0 h **Bulb Material** Soda lime Starting Temperature 15 K (59 °F)

LEED-EB MR Credit 43 picograms Hg per mean

lumen hour

Additional Info TCLP compliant

#### PHOTOMETRIC CHARACTERISTICS

**Initial Lumens** 2725 Mean Lumens 2562 Nominal Initial Lumens per Watt 97 Color Temperature 3500 K Color Rendering Index (CRI) 85 S/P Ratio (Scotopic/Photopic 1.5 Ratio)

#### **ELECTRICAL CHARACTERISTICS**

Open Circuit Voltage (instant 550 V @ 15 °C

start ) Min @ Temperature

Cathode Resistance Ratio - Rh/ 4.25

Rc (MIN)

Cathode Resistance Ratio - Rh/ 6.5 Rc (MAX)

Lamp Current 0.275 A **Current Crest Factor** 1.7

#### **DIMENSIONS**

Maximum Overall Length 47.78 cm

(MOL)

Minimum Overall Length 47.78 cm Nominal Length 48 cm Bulb Diameter (DIA) 1 cm Bulb Diameter (DIA) (MIN) 0.94 cm Bulb Diameter (DIA) (MAX) 1 cm Max Base Face to Base Face 47.22 cm

(A)

Face to End of Opposing Pin 47.4 cm

(B) (MIN) Face to End of Opposing Pin

47.5 cm (B) (MAX)

End of Base Pin to End of

47.67 cm

Opposite Pin End (C)

#### **PRODUCT INFORMATION**

**Product Code** 72864

Description F28T8/XLSPX35ECO Standard Package Case

Standard Package GTIN


10043168728642 Standard Package Quantity 36

Sales Unit Unit No Of Items Per Sales Unit No Of Items Per Standard 36

Package

UPC 043168728645

# **Lumen Maintenance**



# **Spectral Power Distribution**

