

Rapid Start Fluorescent Lamps

Feature: T12 Medium Bipin

Watts: 34 Bulb: T12 Base: Med. Bipin

Product Number: 046677–25686–7 Ordering Code: F34/WW/RS/EW/ALTO

Package Quantity: 30

Description: Warm White, 3000K

CRI: 53

Average Life Hours: 20,000 Design Lumens: 2350 Nominal Length: 48

Approximate Initial Lumens: 2700 This Bulb Meets US Federal Minimum Efficiency Standard



Footnotes

- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions.
- For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate Ballast Factor for each of their ballasts when they are informed of the designated lamp. The Ballast Factor is a multiplier applied to the designated lamp lumen output.
- Approximate hours of life for F40 lamps operated by standard Rapid Start ballasts at three hours per start. When
 these lamps are operated on modified Rapid Start or Preheat circuits the operating life will be reduced by
 approximately 25 percent. When employing dimming systems, or energy saving device systems the device
 manufacturer can advise of the effect of their system upon lamp life.
- Design Lumens are the approximate lamp lumen output at 40% of the lamps Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions.
- Features **ALTO**® Lamp Technology