

Activa T8 F36W/T8/ACTIVA 0002219



Range Features

- Features
- Full-spectrum high colour rendering T8 fluorescent lamp
- Colour rendering: Ra98/Class 1A
- Colour temperature of 6500K (daylight characteristic)
- Applications
- For all applications where natural colour rendering is required
- Supports the treatment of Seasonal Affective Disorder (Winter Depression) SAD
- Applications
- For all applications where natural colour rendering is required
- Supports the treatment of Seasonal Affective Disorder (Winter Depression) SAD



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Colour temperature (K)	6500
CRI (Ra)	98
Dimmable	Yes
EAN code	5410288022192
Energy class	B
Cap/Base	G13
Type	Activa
Watt (Nominal) (W)	36
Ordering number	0002219
Efficacy (Rated) (lm/w)	66
Luminous flux (Rated) (lm)	2350
Technology	Fluorescent
Voltage (V)	103

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	6500
CRI (Ra)	98
Luminous flux (Nominal) (lm)	2300
Rated lumen maint. factor at 12000 h 50Hz	0.9

Activa T8 F36W/T8/ACTIVA 0002219

Rated lumen maint. factor at 16000 h 50Hz	0.89
Rated lumen maint. factor at 20000 h 50Hz	0.87
Rated lumen maint. factor at 2000 h 50Hz	0.96
Rated lumen maint. factor at 4000 h 50Hz	0.94
Rated lumen maint. factor at 6000 h 50Hz	0.92
Luminous flux (Rated) (lm)	2350

General data

Average life (Nominal) (h)	14000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288022192
Energy class	B
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	Special lighting
Cap/Base	G13
Lamp mercury content (mg)	2.8
Type	Activa
Ordering number	0002219
Range features	<p>Features</p> <p>Full-spectrum high colour rendering T8 fluorescent lamp Colour rendering: Ra98/Class 1A Colour temperature of 6500K (daylight characteristic)</p> <p>Applications</p> <p>For all applications where natural colour rendering is required Supports the treatment of Seasonal Affective Disorder (Winter Depression) SAD</p> <p>Applications</p> <p>For all applications where natural colour rendering is required Supports the treatment of Seasonal Affective Disorder (Winter Depression) SAD</p>
Product name	F36W/T8/ACTIVA
Rated survival factor at 12000 h 50Hz	0.92
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 4000 h 50Hz	0.98

Activa T8 F36W/T8/ACTIVA 0002219

Rated survival factor at 6000 h 50Hz	0.96
Rated survival factor at 8000 h 50Hz	0.94
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356641
E-number FI	4943038


Electrical data

Current (A)	0.43
kWh per 1000 hours burning time	43
Watt (Nominal) (W)	36
Efficacy (Rated) (lm/w)	66
Watt (Rated) (W)	36
Watt (Rated) - High frequency (W)	32
Voltage (V)	103

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	1200
Length base to base (mm) - A	1199.4
Length base to pin Min-Max - B	1204.1-1206.5
Single packaging type	Box/Sleeve
Weight (kg)	0.16

TECHNICAL DRAWINGS



Activa T8
F36W/T8/ACTIVA
0002219

