


# GE Lighting

## 97634 - F42TBX/830/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse







### **CAUTIONS & WARNINGS**

#### Caution

- · Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp

# **GENERAL CHARACTERISTICS**

**Customer Name:** 

Project Name: Fixture Type:

Lamp Type	Compact Fluorescent - Plug-
	In
Bulb	T4
Base	GX24-q4
Equivalent Wattage (NOM)	190.0 W
Rated Life (NOM)	17000.0 h
Starting Temperature (MIN)	-18.0 °C
Cathode Resistance (NOM)	2.7 Ohm
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	65.6 pg
Rated Life (rapid start) @ Time	17000.0 @ 3.0/20000.0 @
	12.0 h
Additional Info	Dimmable with appropriate
	dimming ballast./End of
	Life Protection (EOL)/TCLP
	compliant
Primary Application	Facilities;Retail
	Display;Hospitality;Office;Restaurant;Wa

### **PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM) 3200.0 Mean Lumens (NOM) 2690.0 Nominal Initial Lumens per Watt 76.19048 (NOM) Color Temperature (NOM) 3000.0 K Color Rendering Index (CRI) 82.0 (NOM)

#### **ELECTRICAL CHARACTERISTICS**

Wattage (NOM) 42.0 Voltage (NOM) 120.0 Current (max) (NOM) 5.25 A Open Circuit Voltage (after 265.0 V preheating) (MAX) Open Circuit Voltage (MIN) 515.0 V Lamp Current (NOM) 0.32 A 4.25 V Preheat Voltage (MIN) Current Crest Factor (MAX) 1.7 Supply Current Frequency 20.0 Hz (NOM)

#### DIMENSIONS

Maximum Overall Length	6.400 in(162.6 mm)
(MOL) (NOM)	
Nominal Length (NOM)	6.400 in(162.6 mm)
Base Face to Top of Lamp	5.770 in(146.6 mm)
(NOM)	

## **PRODUCT INFORMATION**

Product Code 97634 Description ANSI Code Standard Package Case Standard Package GTIN Standard Package Quantity 10 Sales Unit Unit No Of Items Per Sales Unit 1 No Of Items Per Standard 10 Package UPC

F42TBX/830/A/ECO 60901-IEC-7442-2 10043168976340

043168976343

#### NOTES

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

Amalgam product experience stable brightness over a wider temperature range and in various operating positions.

• Based on 60Hz reference circuit.

· Fluorescent lamp lumens decline during life