



Voltarc **TriLightmax** Thermal T8

Long Life Lamps - 60,000 Hours

Catalog #	Description	Max Overall		Color	CRI	Qty/Box	Avg. Rated Life (hrs)
		Length	Watts†				
MM-84H-18TC	F18T8/CW/841/HO/RDC/CC	15.91"	15	Cool White	85	12	60,000
MM-84H-24TC	F24T8/CW/841/HO/RDC/CC	21.91"	17	Cool White	85	12	60,000
MM-84H-30TC	F30T8/CW/841/HO/RDC/CC	27.91"	21	Cool White	85	12	60,000
MM-84H-36TC	F36T8/CW/841/HO/RDC/CC	33.91"	25	Cool White	85	12	60,000
MM-84H-42TC	F42T8/CW/841/HO/RDC/CC	39.91"	30	Cool White	85	12	60,000
MM-84H-48TC	F48T8/CW/841/HO/RDC/CC	45.91"	35	Cool White	85	12	60,000
MM-84H-58TC	F58T8/CW/841/HO/RDC/CC	59.00"	58	Cool White	85	12	60,000
MM-84H-60TC	F60T8/CW/841/HO/RDC/CC	57.91"	44	Cool White	85	12	60,000
MM-84H-64TC	F64T8/CW/841/HO/RDC/CC	61.91"	48	Cool White	85	12	60,000
MM-84H-72TC	F72T8/CW/841/HO/RDC/CC	69.91"	53	Cool White	85	12	60,000
MM-84H-84TC	F84T8/CW/841/HO/RDC/CC	81.91"	62	Cool White	85	12	60,000
MM-84H-96TC	F96T8/CW/841/HO/RDC/CC	93.91"	73	Cool White	85	12	60,000
MM-85H-18TC	F18T8/5000/950/HO/RDC/CC	15.91"	15	Max 5000	90	12	60,000
MM-85H-24TC	F24T8/5000/950/HO/RDC/CC	21.91"	17	Max 5000	90	12	60,000
MM-85H-30TC	F30T8/5000/950/HO/RDC/CC	27.91"	21	Max 5000	90	12	60,000
MM-85H-36TC	F36T8/5000/950/HO/RDC/CC	33.91"	25	Max 5000	90	12	60,000
MM-85H-42TC	F42T8/5000/950/HO/RDC/CC	39.91"	30	Max 5000	90	12	60,000
MM-85H-48TC	F48T8/5000/950/HO/RDC/CC	45.91"	35	Max 5000	90	12	60,000
MM-85H-58TC	F58T8/5000/950/HO/RDC/CC	59.00"	58	Max 5000	90	12	60,000
MM-85H-60TC	F60T8/5000/950/HO/RDC/CC	57.91"	44	Max 5000	90	12	60,000
MM-85H-64TC	F64T8/5000/950/HO/RDC/CC	61.91"	48	Max 5000	90	12	60,000
MM-85H-72TC	F72T8/5000/950/HO/RDC/CC	69.91"	53	Max 5000	90	12	60,000
MM-85H-84TC	F84T8/5000/950/HO/RDC/CC	81.91"	62	Max 5000	90	12	60,000
MM-85H-96TC	F96T8/5000/950/HO/RDC/CC	93.91"	73	Max 5000	90	12	60,000
MM-86H-18TC	F18T8/DL/865/HO/RDC/CC	15.91"	15	Day Light	85	12	60,000
MM-86H-24TC	F24T8/DL/865/HO/RDC/CC	21.91"	17	Day Light	85	12	60,000
MM-86H-30TC	F30T8/DL/865/HO/RDC/CC	27.91"	21	Day Light	85	12	60,000
MM-86H-36TC	F36T8/DL/865/HO/RDC/CC	33.91"	25	Day Light	85	12	60,000
MM-86H-42TC	F42T8/DL/865/HO/RDC/CC	39.91"	30	Day Light	85	12	60,000
MM-86H-48TC	F48T8/DL/865/HO/RDC/CC	45.91"	35	Day Light	85	12	60,000
MM-86H-58TC	F58T8/DL/865/HO/RDC/CC	59.00"	58	Day Light	85	12	60,000
MM-86H-60TC	F60T8/DL/865/HO/RDC/CC	57.91"	44	Day Light	85	12	60,000
MM-86H-64TC	F64T8/DL/865/HO/RDC/CC	61.91"	48	Day Light	85	12	60,000
MM-86H-72TC	F72T8/DL/865/HO/RDC/CC	69.91"	53	Day Light	85	12	60,000
MM-86H-84TC	F84T8/DL/865/HO/RDC/CC	81.91"	62	Day Light	85	12	60,000
MM-86H-96TC	F96T8/DL/865/HO/RDC/CC	93.91"	73	Day Light	85	12	60,000

All lamps are made to standard T12 HO lengths with Recessed Double Contacts (RDC) end caps.

Lamp life is based on 12 hour switching cycle using electronic warm start ballast.

Lamps are available with Medium Bi-Pin caps as a special order.

† Lamp wattage is based on nominal 315 mA +/- 5% operating current. Lamp operating current range 265 - 465 mA