



Voltarc *TriLightmax*™ T8

High Output **Long Life** Lamps

Catalog #	Description	Max Overall		Color	CRI	Qty/Box	Avg. Rated Life (hrs)
		Length	Watts†				
MM-84H-18	F18T8/CW/841/HO/RDC	15.91"	15	Cool White	85	18	60,000
MM-84H-24	F24T8/CW/841/HO/RDC	21.91"	17	Cool White	85	18	60,000
MM-84H-30	F30T8/CW/841/HO/RDC	27.91"	21	Cool White	85	18	60,000
MM-84H-36	F36T8/CW/841/HO/RDC	33.91"	25	Cool White	85	18	60,000
MM-84H-42	F42T8/CW/841/HO/RDC	39.91"	30	Cool White	85	18	60,000
MM-84H-48	F48T8/CW/841/HO/RDC	45.91"	35	Cool White	85	18	60,000
MM-84H-58	F58T8/CW/841/HO/RDC	59.00"	58	Cool White	85	18	60,000
MM-84H-60	F60T8/CW/841/HO/RDC	57.91"	44	Cool White	85	18	60,000
MM-84H-64	F64T8/CW/841/HO/RDC	61.91"	48	Cool White	85	18	60,000
MM-84H-72	F72T8/CW/841/HO/RDC	69.91"	53	Cool White	85	18	60,000
MM-84H-84	F84T8/CW/841/HO/RDC	81.91"	62	Cool White	85	18	60,000
MM-84H-96	F96T8/CW/841/HO/RDC	93.91"	73	Cool White	85	18	60,000
MM-85H-18	F18T8/5000/950/HO/RDC	15.91"	15	Max 5000	90	18	60,000
MM-85H-24	F24T8/5000/950/HO/RDC	21.91"	17	Max 5000	90	18	60,000
MM-85H-30	F30T8/5000/950/HO/RDC	27.91"	21	Max 5000	90	18	60,000
MM-85H-36	F36T8/5000/950/HO/RDC	33.91"	25	Max 5000	90	18	60,000
MM-85H-42	F42T8/5000/950/HO/RDC	39.91"	30	Max 5000	90	18	60,000
MM-85H-48	F48T8/5000/950/HO/RDC	45.91"	35	Max 5000	90	18	60,000
MM-85H-58	F58T8/5000/950/HO/RDC	59.00"	58	Max 5000	90	18	60,000
MM-85H-60	F60T8/5000/950/HO/RDC	57.91"	44	Max 5000	90	18	60,000
MM-85H-64	F64T8/5000/950/HO/RDC	61.91"	48	Max 5000	90	18	60,000
MM-85H-72	F72T8/5000/950/HO/RDC	69.91"	53	Max 5000	90	18	60,000
MM-85H-84	F84T8/5000/950/HO/RDC	81.91"	62	Max 5000	90	18	60,000
MM-85H-96	F96T8/5000/950/HO/RDC	93.91"	73	Max 5000	90	18	60,000
MM-86H-18	F18T8/DL/865/HO/RDC	15.91"	15	Day Light	85	18	60,000
MM-86H-24	F24T8/DL/865/HO/RDC	21.91"	17	Day Light	85	18	60,000
MM-86H-30	F30T8/DL/865/HO/RDC	27.91"	21	Day Light	85	18	60,000
MM-86H-36	F36T8/DL/865/HO/RDC	33.91"	25	Day Light	85	18	60,000
MM-86H-42	F42T8/DL/865/HO/RDC	39.91"	30	Day Light	85	18	60,000
MM-86H-48	F48T8/DL/865/HO/RDC	45.91"	35	Day Light	85	18	60,000
MM-86H-58	F58T8/DL/865/HO/RDC	59.00"	58	Day Light	85	18	60,000
MM-86H-60	F60T8/DL/865/HO/RDC	57.91"	44	Day Light	85	18	60,000
MM-86H-64	F64T8/DL/865/HO/RDC	61.91"	48	Day Light	85	18	60,000
MM-86H-72	F72T8/DL/865/HO/RDC	69.91"	53	Day Light	85	18	60,000
MM-86H-84	F84T8/DL/865/HO/RDC	81.91"	62	Day Light	85	18	60,000
MM-86H-96	F96T8/DL/865/HO/RDC	93.91"	73	Day Light	85	18	60,000

All lamps are made to standard T12 HO lengths with Recessed Double Contacts (RDC) end caps.

Lamp life is based on 12 hour switching cycle using electronic warm start ballast.

Lamps are available with Medium Bi-Pin caps as a special order.

† Lamp wattage is based on nominal 315 mA +/- 5% operating current. Lamp operating current range 265 - 465 mA