

**Product Number:** 21366

**Order Abbreviation:** F8T5/CW 25/CS

**General Description:** 8W, T5 preheat fluorescent lamp, Cool White phosphor, 4200K color temperature, 60 CRI. 7500 Avg rated life at 3 hrs/start



**\* Full Case Required**

#### Product Information

Abbrev. With Packaging Info.	F8T5CW 25/CS 1/SKU
Actual Length (in)	11.909
Actual Length (mm)	302.49
Average Rated Life (hr)	7500
Base	Miniature Bipin
Bulb	T5
Color Temperature/CCT (K)	4000
Diameter (in)	0.630
Diameter (mm)	16.00
Initial Lumens at 25C	385
Nominal Length (in)	12.000
Nominal Length (mm)	304.80
Nominal Wattage (W)	8.00

#### Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Preheat lamp, starter required.
- Mean lumens are measured at 40% of average rated lamp life.
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).