


- Available in LED & GU24
- Fade & Rust Resistant Composite Construction with Powder Coated Aluminum Base
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

COMMERCIAL CENTURY - 8.25"



FC321



RoHS
compliant



EXAMPLE # FC321-LE800C-BFP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC321	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W -White B - Black	POLYPROPYLENE F -Frosted GLASS G -Clear	P -Photocell
	LE800 - 13W, 80 CRI >88 Lumens Per Watt** W -1140lm 3000K C -1280lm 4000K			
	LE1200 - 14W, 80 CRI >102 Lumens Per Watt** W -1430lm 3000K C -1500lm 4000K			
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W -White B - Black	POLYPROPYLENE F -Frosted GLASS G -Clear	N/A
	L900 - 11.3W Power Input CRI 74 (TYP) >80 Lumens Per Watt** C -912lm 4000K			
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G26 -1 X 27W	W -White B -Black	POLYPROPYLENE F -Frosted GLASS G -Clear	P - Photocell L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.