

Project Name

Location

Prepared By



SATCO S16510

FC8T9/LED/CIR/CCT/DM/A-B

Notes

(www) 02-19-2023 09:59:23

General

| | |
|------------------------|------------------------|
| Status | Active |
| Watts | 11W |
| Fluorescent Equivalent | 22W |
| Volts | 120V-277V |
| Ballast Type | Type A/B |
| Shape | T9 |
| Base | G10q (4-Pin) |
| ANSI Base | G10q |
| Finish | Frost |
| CCT (Kelvin) | 3000K/4000K/6500K |
| Temperature | Soft White to Daylight |
| CRI | 80+ |
| Lumens | 1300L/1400L/1350L |
| Beam Spread | 180 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Product Category | Circline |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast required (Type A, Electronic only) or Ballast Bypass (Type B) |
| Operating Frequency | 50/60Hz |
| THD | 25% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 8.08 |
| MOD | 1.2 |
| Housing Color | Frost |
| Weight (lb.) | 0.37 |

Additional Information

| | |
|----------------------------|---|
| Specification Note | Only compatible with Electronic ballasts when installed in Type A mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 5.71 in. |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5 Year Limited - 10 hr per day |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Classified |
| Location Rating | Damp |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |