







FE351



FE352



FE353



## FE351 | FE352 | FE353 RESIDENTIAL EUROSTYLE


- ◊ Fade & Rust Resistant Composite Construction
- ◊ UL Listed for Wet Locations
- ◊ Polycarbonate Lens & Base
- ◊ Ceiling or Wall Mount
- ◊ Mounting Hardware Included

### EXAMPLE # FE351-I75-BF-LWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FE351	INCANDESCENT 120V	B-Black	POLYCARBONATE	<b>S</b> -Security Motion Sensor & Photocell Combo. 120V only. See page 16.  LED LAMP, 3 YEAR WARRANTY DIMMABLE <b>LWE</b> -A19/E26, 80CRI, 3000K <b>LCE</b> -A19/E26, 80CRI, 4000K
FE352	INCANDESCENT, MEDIUM BASE, 120V	W-White	F-Frost	
FE353	I75-1 X 75W Max			

See page 122 for dimmer compatibility. Data per LM79/LM80/TM21 available upon request. Fixtures available with custom packaging options, assembled or knocked down. MOQS apply. Specification subject to change without notice.





## FE361 COMMERCIAL EUROSTYLE

- ◊ Fade & Rust Resistant Composite Construction
- ◊ UL Listed for Wet Locations
- ◊ Polycarbonate Lens & Aluminum Base
- ◊ Ceiling or Wall Mount
- ◊ Mounting Hardware Included



### EXAMPLE # FE361-LE800C-BFP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
<b>FE361</b>	<b>DEDICATED 120V LED</b>	<b>B-Black</b> <b>W-White</b>	<b>POLYCARBONATE</b> <b>F-Frost</b>	<b>P-Photocell</b> 120V only. See page 18 for details. <b>S-Security</b> Motion Sensor & Photocell Combo. 120V only. See page 14.	
	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE				
	<b>LE800</b> - 13W, 80 CRI >88 Lumens Per Watt**				<b>W-1140lm</b> 3000K <b>C-1280lm</b> 4000K
	<b>LE1200</b> - 14W, 80 CRI >102 Lumens Per Watt**				<b>W-1430lm</b> 3000K <b>C-1500lm</b> 4000K
<b>LE1800</b>	- 22W, 80 CRI >88 Lumens Per Watt**	<b>W-1950lm</b> 3000K <b>C-2130lm</b> 4000K			
	<b>MULTI-VOLT 120-277V LED</b>	<b>B-Black</b> <b>W-White</b>	<b>POLYCARBONATE</b> <b>F-Frost</b>	<b>S-Security</b> Motion Sensor & Photocell Combo. See page 16.	
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY				
<b>L1800</b> - 22W, 80 CRI CRI 74 (TYP) >88 Lumens Per Watt**	<b>W-1704lm</b> 3000K <b>C-1824lm</b> 4000K				

See page 122 for dimmer compatibility. Data per LM79/LM80/TM21 available upon request. \*\*Estimated from LED source. Fixtures available with custom packaging options, assembled or knocked down. MOQS apply. Specification subject to change without notice.

