



VFLOOD - 212W LED Flood Light

Order Code: FL00502



Description

VFLOOD is a low profile, lightweight LED Flood Light fixture, designed for long life and low maintenance. The fixtures are designed to quickly and easily upgrade existing flood fixtures. Twist lock photocell receptacle and shorting cap included with the fixture.

Construction

The housing unit is constructed from heavy-duty, die cast aluminum. Fixtures are finished with a durable bronze polyester powder coating. To ensure weather-tight protection and to keep out contaminants, each optical assembly is sealed with a silicone gasket. Each unit is rated for wet locations.

Electrical

The Class II power supply has a range of 120-277V, 50/60 Hz. 0-10V dimming capability is standard.

Mounting

Fixtures can be mounted by a 6" straight arm extension, a slipfitter mount that fits onto a 2-3/8" tenon, or a yoke mount. Not included with fixture. Order separately.

NOTE:

*Lumen maintenance data is based on LED testing per IESNA LM-80-08 and projected per IESNA TM-21-11

DLC Model# FA-212C5A

Product Performance

Wattage	212W
Lumen Output	25343
Correlated Color Temperature (CCT)	5000K
Color Rendering Index (CRI)	80+
Lumen Maintenance @50,000 hours*	93%
Calculated L70 @ 25°C Ambient in Hours*	258,000
Replaces HID Wattage	1000W
Operating Temperature Range	-40°F to 104°F (-40°C to 40°C)

Physical Characteristics

Fixture Color	Bronze
EPA	2.24
Weight	21.8 lbs
Width	13.25"
Length	19.25"
Height	6.25"

Electrical Characteristics

Amperage Draw (Input Volts/Amps)	120/1.78 208/1.10 240/0.90 277/0.78
Surge Protection	10kA

Regulatory Qualifications

- cULus Listed
- DLC Qualified - Model# FA-212C5A
- Rated for wet locations

Accessories

- FL99436 U-Bracket for 212W LED VFlood
- FL22402 6" Straight Arm, Square Pole - Brz
- FL25107 Adjustable Slipfitter for LED VFloods
- PH12415 Twist lock photocell
- PH81975 Twist lock shorting cap
- FL26815 6" STRAIGHT ARM, 4" DIA ROUND POLE, BRZ
- SP12714 - 120-277V Surge Protector



Venture VFLOOD - 212W LED Flood Light

