Lamp Specification Sheet: T5, HE Lamps

Description:

Fluorescent T5 High Effciency Linear Mini Bipin Lamps.

Lamp Data:

| Nominal | CCFL | MOL | MOL | Item Number | NEMA Generic | Pkg | Rated | Rated | CCT | CRI | Approx. | Approx. |
|---------|------|--------|--------|-------------|--------------|-----|-------|--------|------|------|---------|---------|
| Wattage | Bulb | | | | Description | Qty | Life | Life* | (K) | | Lumens | Lumens |
| 4.4 | 70 | (in) | (mm) | | | 05 | 3 hrs | 12 hrs | 0700 | > 00 | Initial | Mean |
| 14 | | 22.173 | 563.2 | FLFT514W827 | F14T5 | 25 | 20000 | 35000 | 2700 | ≥ 82 | 1350 | 1230 |
| 14 | T5 | 22.173 | 563.2 | FLFT514W830 | F14T5 | 25 | 20000 | 35000 | 3000 | ≥ 82 | 1350 | 1230 |
| 14 | T5 | 22.173 | 563.2 | FLFT514W835 | F14T5 | 25 | 20000 | 35000 | 3500 | ≥ 82 | 1350 | 1230 |
| 14 | T5 | 22.173 | 563.2 | FLFT514W841 | F14T5 | 25 | 20000 | 35000 | 4100 | ≥ 82 | 1350 | 1230 |
| 14 | T5 | 22.173 | 563.2 | FLFT514W850 | F14T5 | 25 | 20000 | 35000 | 5000 | ≥ 82 | 1350 | 1230 |
| 14 | T5 | 22.173 | 563.2 | FLFT514W865 | F14T5 | 25 | 20000 | 35000 | 6500 | ≥ 82 | 1350 | 1230 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W827 | F21T5 | 25 | 20000 | 35000 | 2700 | ≥ 82 | 2100 | 1910 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W830 | F21T5 | 25 | 20000 | 35000 | 3000 | ≥ 82 | 2100 | 1910 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W835 | F21T5 | 25 | 20000 | 35000 | 3500 | ≥ 82 | 2100 | 1910 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W841 | F21T5 | 25 | 20000 | 35000 | 4100 | ≥ 82 | 2100 | 1910 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W850 | F21T5 | 25 | 20000 | 35000 | 5000 | ≥ 82 | 2100 | 1910 |
| 21 | T5 | 33.984 | 863.2 | FLFT521W865 | F21T5 | 25 | 20000 | 35000 | 6500 | ≥ 82 | 2100 | 1910 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W827 | F28T5 | 25 | 20000 | 35000 | 2700 | ≥ 82 | 2900 | 2640 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W830 | F28T5 | 25 | 20000 | 35000 | 3000 | ≥ 82 | 2900 | 2640 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W835 | F28T5 | 25 | 20000 | 35000 | 3500 | ≥ 82 | 2900 | 2640 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W841 | F28T5 | 25 | 20000 | 35000 | 4100 | ≥ 82 | 2900 | 2640 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W850 | F28T5 | 25 | 20000 | 35000 | 5000 | ≥ 82 | 2900 | 2640 |
| 28 | T5 | 45.795 | 1163.2 | FLFT528W865 | F28T5 | 25 | 20000 | 35000 | 6500 | ≥ 82 | 2900 | 2640 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W827 | F35T5 | 25 | 20000 | 35000 | 2700 | ≥ 82 | 3650 | 3300 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W830 | F35T5 | 25 | 20000 | 35000 | 3000 | ≥ 82 | 3650 | 3300 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W835 | F35T5 | 25 | 20000 | 35000 | 3500 | ≥ 82 | 3650 | 3300 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W841 | F35T5 | 25 | 20000 | 35000 | 4100 | ≥ 82 | 3650 | 3300 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W850 | F35T5 | 25 | 20000 | 35000 | 5000 | ≥ 82 | 3650 | 3300 |
| 35 | T5 | 57.6 | 1463.0 | FLFT535W865 | F35T5 | 25 | 20000 | 35000 | 6500 | ≥ 82 | 3650 | 3300 |

Model: T5 High Effciency

Lamp Specifcations:

- Variety of Application Including:

2. POP Applications

1. Direct and Indirect Offce Lighting

Custom colors (CCT) are available, 27K thru' 65K

*Rated lamp life based on 3 hours per start (min.).

Lamp Features:

3

- High Effciency T5 Lamp
- Full Range of Color Temperatures (CCT)
- High Color Rendering Index (CRI) ≥82
- Longer Rated Life 35,000 Hours
- TCLP Compliant, Lowering Disposal Costs Where
- Applicable (State Regulations Vary, Consult Your State EPA).

| Measurements: | | | | |
|---------------|-----|---|---------------|----------------|
| 0.18" | | 0 | .283 <u> </u> | _ |
| + = | | | | \oplus |
| | MOL | | | /" 5/8" DIA |

Notes:

LAMP CONTAINS MERCURY Each of these lamps contain 4.25 milligrams of mercury.

