
FRANCE

PKA2N

**Self-Enclosed
Outdoor Non-weatherproof**

***MOST MODELS
UL 506 LISTED***



***MODELS:
6030 PKA2N, 5030 PKA2N & 4030 PKA2N
120 & 277 V
UL 2161 LISTED***

- ◆ No Additional Enclosure Needed When Installed in a Protective Environment
- ◆ Complete with an On-Off Switch
- ◆ Easy Access to Secondary Wiring Compartments via “Easy-Off” Top Cover
- ◆ Easy Carry Handle
- ◆ Multiple Knockouts for a Variety of Connection Choices
- ◆ Pre-wired Primary Connections Save Installation Time
- ◆ Power Corrected Units Available as Special Build for models 7500 V and up
- ◆ 6030 PKA2N, 5030 PKA2N & 4030 PKA2N -120 and 277 V are UL 2161 Listed

PKA2N

NORMAL POWER FACTOR

Catalog Number	Secondary Volts	mA	Primary VA	Input Amp	Wt lbs	Dimensions in Inches					
						L	W	H	A	B	C
◆ 15030 PKA2N	15000	30	450	3.75	24	13.375	4.5	7.5	10.875	12.25	2
◆ 12030 PKA2N	12000	30	360	3.00	23	13.375	4.5	7.5	10.875	12.25	2
◆ 10530 PKA2N	10500	30	315	2.63	22	13.375	4.5	7.5	10.875	12.25	2
◆ 9030 PKA2N	9000	30	270	2.25	16	13.375	4	5.75	10.875	12.25	2
◆ 7530 PKA2N	7500	30	225	1.88	16	13.375	4	5.75	10.875	12.25	2
◆ 6030 PKA2N	6000	30	200	1.65	14	13.375	4	5.75	10.875	12.25	2
◆ 5030 PKA2N	5000	30	170	1.40	14	13.375	4	5.75	10.875	12.25	2
◆ 4030 PKA2N	4000	30	140	1.15	14	13.375	4	5.75	10.875	12.25	2
15060 PKA2N	15000	60	890	7.42	39	14.875	5.375	8.5	12.375	13.75	2
12060 PKA2N	12000	60	720	6.00	38	14.875	5.375	8.5	12.375	13.75	2
9060 PKA2N	9000	60	540	4.50	26	13.375	4.5	7.5	10.875	12.25	2
7560 PKA2N	7500	60	450	3.75	24	13.375	4.5	7.5	10.875	12.25	2

◆ Model available in 277 VAC/60 Hz. To determine Input Amps multiply by 0.433.

