
FRANCE

P2G Series 7530 P2 & 9030 P4

**Low Profile
Outdoor Non-weatherproof**



P2G Models - UL 2161 Listed 

P2 & P4 Models - UL 506 Listed  

- ◆ Low Profile Design Allows for Increased Mounting Flexibility
- ◆ Use in Virtual Series, Mid-point Return or Series Wiring Methods
- ◆ Heavy Duty Steel Casing
- ◆ Ratings 4000 V and up are available in 120 & 277 V

www.franceformer.com

P2G Series

7530 P2 & 9030 P4

NORMAL POWER FACTOR

Catalog Number	VAC	Secondary		Primary VA	Input Amp	Wt lbs	Dimensions in Inches					
		Volts	mA				L	W	H	A	B	C
6030 P2G	120	6000	30	180	1.65	10	10.5	3.6875	2.9375	8.4375	1.88	8.875
5030 P2G	120	5000	30	160	1.40	10	10.5	3.6875	2.9375	8.4375	1.88	8.875
4030 P2G	120	4000	30	140	1.15	10	10.5	3.6875	2.9375	8.4375	1.88	8.875
3030 P2G	120	3000	30	105	.85	10	10.5	3.6875	2.9375	8.4375	1.88	8.875
6030 P2G	277	6000	30	180	.75	13	10.5	3.6875	2.9375	8.4375	1.88	8.875
5030 P2G	277	5000	30	160	.60	13	10.5	3.6875	2.9375	8.4375	1.88	8.875
4030 P2G	277	4000	30	140	.50	13	10.5	3.6875	2.9375	8.4375	1.88	8.875
7530 P2	120	7500	30	225	1.88	10	10.5	3.6875	2.9375	8.4375	1.88	8.875
7530 P2	277	7500	30	225	.81	13	10.5	3.6875	2.9375	8.4375	1.88	8.875
9030 P4	120	9000	30	270	2.25	12	10.5	3.6875	3.4375	8.4375	1.88	8.875
9030 P4	277	9000	30	270	.97	15	10.5	3.6875	3.4375	8.4375	1.88	8.875

