

Version	1.0	Date	10/1/2022
Prepared By	J.C		

PRODUCT SPECIFICATION

Category	Flood Light
Item Number	9653
Stock Code	FXFDL30/77/CCT3/BZ-YK
Mounting	Yoke
Housing Color	Bronze

PICTURE



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	30	Replacement Wattage (W)	75-150
Tested Wattage (W)	29.94		
Input Voltage (V)	120 ~277	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.46	AUX (12V) Line	-
Power Factor	≥ 0.9		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	4100	CCT (K)	3000/4000/5000K
Efficacy (lm/w)	137	Beam Angle (°)	NEMA 7Hx7V
CRI	70		

GENERAL CHARACTERISTICS


Operating Temperature (°F)	-40 ~ 113
Storage Temperature (°F)	-40 ~ 158
IP Rating	IP65
Rated Life	50000 hrs.
Warranty	5 years

ACCESSORIES

Item #	Stock Code	Description
P10012	MT-FDL/KNC/BZ	Mount-FDL Knuckle Bronze

PRODUCT DIMENSIONS

Width- in (mm)	6.3	160
Height- in (mm)	5.51	140
Depth- in (mm)	1.65	42
EPA (ft²)	-	
Weight (lbs)	1.46	
Mounting Height (ft)	-	
Cable Length (ft)	-	



CERTIFICATIONS

UL/ETL	cULus	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	V5.1 Premium	RoHs	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

--