

Version	2.0	Date	7/22/2023
Prepared By	J.C		

PRODUCT SPECIFICATION

Category	Troffer
Item Number	9587
Stock Code	FXTF45SW/2X4/8CCT3G1
Mounting	Ceiling
Housing Color	White



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	45 / 40 / 30	Replacement Wattage (W)	90 ~ 130
Tested Wattage (W)	45		
Input Voltage (V)	120 ~ 277	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	max 0.43	AUX (12V) Line	No
Power Factor	>0.9(45W/40W)		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	5850 / 5240 / 4050	CCT (K)	3500
Lumen (lm)	6390 / 5720 / 4350	CCT (K)	4000
Lumen (lm)	5940 / 5360 / 4110	CCT (K)	5000
Efficacy (lm/w)	>130	Beam Angle (°)	115
CRI	80		

GENERAL CHARACTERISTICS

Operating Temperature (°F)	-4 ~ 104
Storage Temperature (°F)	-4 ~ 140
IP Rating	UL Damp Location
Rated Life	50000 hrs.
Warranty	5 Years

ACCESSORIES

Item #	Stock Code	Description
K7334225	FXTF-BAEM-MT	Emergency Driver Kit (7334 + P10225)
K225234	PLT/FXTF/MC605	Motion Sensor Kit (P10225 + P10234)
P10229	MT-2X4FMBOX	Flange Mount Kit
P10147	MT-ACC-4FT	Air Craft Cable - 4ft
P10144	MT-ACC-10FT	Air Craft Cable - 10ft
P10389	SPD-L-10KV-277	10KV Surge protection - 120V ~ 277V
P10390	SPL-L-20KV-277	20KV Surge Protection - 120V ~ 277V

PRODUCT DIMENSIONS

Width- in (mm)	23.74" (603 mm)	
Height- in (mm)	1.97" (50 mm)	
Depth- in (mm)	47.72" (1212 mm)	
EPA (ft²)	N/A	
Weight (lbs)	11.8	
Mounting Height (ft)	10	
Cable Length (ft)	-	

CERTIFICATIONS

UL/ETL	ETL/ cETL	CEC	
NSF / ETL Sanitation		JA8	
Energy Star		FCC	
DLC	V5.1 Standard	RoHs	

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	