Immersion™ Elite

Refrigerated Display Cases

Lights for Horizontal Cases

Project Name _____

Date _____ Type _____

Notes _____

Technical Specifications

Parameter	Specification
Power Supply	GEPS6100NCCON-SY Input: 120-240VAC, 60/50Hz, Output: 24VDC GELP24-100U-GLX Input: 120-277VAC, 60/50Hz, Output: 24VDC GEPS24D-100U-NA Input: 120-277VAC, 60/50Hz, Output: 24VDC GEPS24D-60U-GLX Input: 120-277VAC, 60/50Hz, Output: 24VDC
Warranty Life	5 Years*
Operating Environment	-20 °C to +25°C
Module Dimensions	NA
Warranty	Current Lighting offers a limited system warranty of up to five (5) years
System Certifications	UL Listed (c-us) #E321439, UL Classified (c-us) LED Luminaire Conversion Kit for Commercial Refrigerators and Freezers #E345823, UL Sanitation (ANSI/NSF2 Splash Zone) #SA44273, CE, UKCA, ROHS, IP66, UL Damp Rated

* See terms and conditions.

LED Driver Performance Data

	GEPS6100NCCON-SY; 24V-100W Product Code: 13798	GELP24-100U-GLX; 24V-100W Product Code: 93077673G	GEPS24D-100U-NA; 24V-100W Product Code: 93159243	GEPS24D-60U-GLX; 24V-60W Product Code: 93159242
Dimming	Yes (Step - Contact Input)	No	Yes (0-10V)	Yes (0-10V)
Output Power (Watts)	96	96	96	60
Input Voltage (VAC)	120-240V	120-277V	120-277V	120-277V
Input Line Frequency (Hz)	50/60	50/60	50/60	50/60
Length	10.7 inch (273mm)	9.5 inch (241mm)	9.5 inch (241mm)	5.8 inch (148.2mm)
Width	1.7 inch (43mm)	1.7 inch (43mm)	1.7 inch (43mm)	1.8 inch (45.6mm)
Height	1.1 inch (28mm)	1.0 inch (25.4mm)	1.0 inch (25.4mm)	1.0 inch (25.4mm)

Refer to Power Supply Guide on website for detailed information on Immersion™ Power Supplies
Please only load to within 10% of maximum Watts

Accessories

SKU	Model Number	Description	Package Quantity
69721	GE-MT3000NCM1-SY RH30	Mounting clips	2 pcs per bag
93155838	Sealed Connector Cover	Cover to terminate the connector	50 pcs per bag
93155625	GE-JC241N-66M-66F	Jumper cable to add cable length between bars	5 pcs per bag
93155627	GE-LC241N-66F	24" (609 mm) leader cable with IP66 female connector	5 pcs per bag
93155628	GE-LC241N-66M	24" (609 mm) leader cable with IP66 male connector	5 pcs per bag
93155630	GE-LC169IN-66F	169" (4293 mm) leader cable with IP66 female connector	5 pcs per bag



Electrical products must not be thrown out with domestic waste. They must be taken to a communal collecting point for environmentally friendly disposal in accordance with local regulations. Contact your local authorities or stockist for advice on recycling. The packaging material is recyclable. Dispose of the packaging in an environmentally friendly manner and make it available for the recyclable material collection-service.

© 2026 Current Lighting Solutions, LLC. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.