



GE
Lighting

67345 - GEP320MLTAA4-5/2

GE Pulse Start 1-320W PS M132 or 154 Quad(120/208/240/277V)

- Distributor replacement kit contains the appropriate core & coil with color coded leads, a properly rated capacitor and ignitor (if required) and all other components required for ballast replacement
- Precision-wound coils, ensuring even heat dissipation and the highest electrical integrity.
- Magnetic ballast construction ideal for a wide variety of lighting applications.
- Quad ballast (120, 208, 240, 277)

GENERAL CHARACTERISTICS

Lamp Type	HID -
Bulb	Magnetic
Ballast Type	Pulse Start Metal Halide Core and Coil
Starting Method	Pulse start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-) (NOM)	10.0 %
Ballast Factor	1
Circuit Type	CWA
Insulation Class	UL Class H 180
Enclosure Type	Core and Coil
Type of Capacitor	Oil filled
Capacitance (NOM)	21.0 µF
Capacitor Temperature Rating (NOM)	105.0 °C

ELECTRICAL CHARACTERISTICS

Supply Current Frequency (NOM)	60.0 Hz
Voltage (MIN)	370.0
Voltage (NOM)	120.0

DIMENSIONS

Weight (NOM)	9.5 lb
Exit Type	
Nominal Length (NOM)	3.700 in(94.0 mm)
Frame size (H x L)	NaN in(NaN mm)

PRODUCT INFORMATION

Product Code	67345
Description	GEP320MLTAA4-5/2
ANSI Code	M154/M132
Standard Package	00-Case
Standard Package GTIN	10043168673454
Standard Package Quantity	3
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	3
UPC	043168673457