



DECORATIVE ELECTRONIC FLUORESCENT LAMPS

DURALUX GLOBE




Watts	Bulb	Base	Product Code	Order Code	CRI	Volts	Lumens	Life (HRS)	Kelvin	Pkg	MOL
2700K											
15	EG	Med	03015/E26	EG 15/27K	85	120-130	700	12,000	2700	10	6 15/16"
20	EG	Med	03015/E26	EG 20/27K	85	120-130	1000	12,000	2700	10	7 1/4"
5000K											
15	EG	Med	03018/E26	EG 15/50K	85	120-130	700	12,000	5000	10	6 15/16"
20	EG	Med	03019/E26	EG 20/50K	85	120-130	1000	12,000	5000	10	7 1/4"

DURALUX CANDLE



Watts	Bulb	Base	Product Code	Order Code	CRI	Volts	Lumens	Life (HRS)	Kelvin	Pkg	MOL
2700K											
5	EC	Cand	03322/E12	EC 5/27K	85	120-130	200	12,000	2700	10	5"
7	EC	Cand	03021/E12	EC 7/27K	85	120-130	250	12,000	2700	10	5"
9	EC	Cand	03022/E12	EC 9/27K	85	120-130	300	12,000	2700	10	5"
5000K											
5	EC	Cand	03324/E12	EC 5/50K	85	120-130	200	12,000	5000	10	5"
7	EC	Cand	03023/E12	EC 7/50K	85	120-130	250	12,000	5000	10	5"
9	EC	Cand	03024/E12	EC 9/50K	85	120-130	300	12,000	5000	10	5"

DURALUX GLS



Watts	Bulb	Base	Product Code	Order Code	CRI	Volts	Lumens	Life (HRS)	Kelvin	Pkg	MOL
2700K											
7	GLS	Med	03025/E26	GLS 7/27K	85	120-130	340	12,000	2700	10	5 7/8"
11	GLS	Med	03026/E26	GLS11/27K	85	120-130	540	12,000	2700	10	6 1/8"
15	GLS	Med	03027/E26	GLS 15/27K	85	120-130	800	12,000	2700	10	6 1/2"
5000K											
7	GLS	Med	03028/E26	GLS 7/50K	85	120-130	340	12,000	5000	10	5 7/8"
11	GLS	Med	03029/E26	GLS 11/50K	85	120-130	540	12,000	5000	10	6 1/8"
15	GLS	Med	03030/E26	GLS 15/50K	85	120-130	800	12,000	5000	10	6 1/2"



Life 12.000h.

Up to 80% power saving.

Starter and noise-suppressor capacitor incorporated in the cap.

All the decorated electronic fluorescent lamps can be supplied, on request and in quantities, also with 110-130 V or 240-250 V, and B22 or B15d, E26 or E12 caps.

CERTIFIED COMPANY



ISO 9002