

## Reduced Ballast Factor Options

EcoSystem ballasts, EcoSystem H-Series ballasts and Hi-lume 3D ballasts with Reduced Ballast Factor options provide a low-cost energy savings solution for any space in any application.

The main feature of the Reduced Ballast Factor line is the ability to meet energy savings needs by reducing the ballast factor, or high-end light level capability, to a certain percentage of the maximum rated level.

Reduced Ballast Factor ballasts are being offered as specific ballast model numbers (listed below).

**NOTE:** This document is to be used in conjunction with the EcoSystem Ballast specification submittal (369454), EcoSystem H-Series ballast specification submittal (369266) and the Hi-lume 3D ballast specification submittal (369280).

## EcoSystem Ballasts

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T5	21	1	J	EC5T521JUNV1C85*	120	0.19	0.85	22.59	1785	79	3.76	0.79	>0.95	<10%
					240	0.10	0.85	23.16	1785	77	3.67	0.77		
					277	0.08	0.85	22.66	1785	79	3.75	0.79		
T5	21	2	J	EC5T521JUNV2C85*	120	0.34	0.85	41.24	3570	87	2.06	0.87		
					240	0.17	0.85	40.07	3570	89	2.12	0.89		
					277	0.15	0.85	41.10	3570	87	2.07	0.87		
				EC5T521JUNV2C88*	120	0.35	0.88	42.40	3696	87	2.08	0.87		
					240	0.17	0.88	41.11	3696	90	2.14	0.90		
					277	0.15	0.88	42.16	3696	88	2.09	0.88		
T5	28	1	J	EC5T528JUNV1C85*	120	0.24	0.85	29.05	2465	85	2.93	0.82		
					240	0.12	0.85	28.96	2465	85	2.94	0.82		
					277	0.10	0.85	28.92	2465	85	2.94	0.82		
				EC5T528JUNV1C88*	120	0.25	0.88	29.72	2552	86	2.96	0.83		
					240	0.12	0.88	29.60	2552	86	2.97	0.83		
					277	0.11	0.88	29.53	2552	86	2.98	0.83		
T5	28	2	J	EC5T528JUNV2C70*	120	0.43	0.70	51.50	4060	79	1.36	0.38		
					240	0.21	0.70	51.34	4060	79	1.36	0.38		
					277	0.18	0.70	51.08	4060	79	1.37	0.38		
				EC5T528JUNV2C85*	120	0.48	0.85	57.37	4930	86	1.48	0.41		
					240	0.24	0.85	56.81	4930	87	1.50	0.42		
					277	0.20	0.85	56.15	4930	88	1.51	0.42		
T5	54	2	J	EC5T554JUNV2C80*	120	0.80	0.80	95.58	8000	84	0.84	0.45		
					240	0.39	0.80	94.20	8000	85	0.85	0.46		
					277	0.34	0.80	92.91	8000	86	0.86	0.46		
T8	17	1	J	EC5T817JUNV1C71*	120	0.14	0.71	16.98	994	59	4.18	0.17		
					240	0.07	0.71	17.50	994	57	4.06	0.69		
					277	0.06	0.71	17.59	994	57	4.04	0.69		
T8	17	2	J	EC5T817JUNV2C71*	120	0.23	0.71	28.13	1988	71	2.52	0.86		
					240	0.12	0.71	27.78	1988	72	2.56	0.87		
					277	0.10	0.71	27.89	1988	71	2.55	0.87		
T8	25	1	J	EC5T825JUNV1C71*	120	0.19	0.71	23.09	1527	66	3.07	0.77		
					240	0.10	0.71	23.08	1527	66	3.08	0.77		
					277	0.08	0.71	23.38	1527	65	3.04	0.76		

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

Job Name:	Model Numbers:
Job Number:	

### EcoSystem Ballasts (continued)

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T8	25	2	J	EC5T825JUNV2C71*	120	0.34	0.71	40.41	3061	76	1.76	0.88	>0.95	<10%
					240	0.17	0.71	40.18	3061	76	1.77	0.88		
					277	0.15	0.71	40.52	3061	76	1.75	0.88		
T8	32	1	J	EC5T832JUNV1C71*	120	0.23	0.71	28.19	1811	64	2.52	0.81		
					240	0.12	0.71	28.27	1811	64	2.51	0.80		
					277	0.10	0.71	28.23	1811	64	2.52	0.80		
T8	32	2	J	EC5T832JUNV2C71*	120	0.42	0.71	50.57	3621	72	1.40	0.45		
					240	0.21	0.71	50.49	3621	72	1.41	0.45		
					277	0.18	0.71	50.36	3621	72	1.41	0.45		

### EcoSystem H-Series Ballasts

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD		
T5	14	1	M	EHDT514MU1C50	120	0.10	0.50	11.99	675	56	4.17	0.58	>0.95	<10%		
					240	0.05	0.50	12.46	675	54	4.01	0.56				
					277	0.05	0.50	12.80	675	53	3.91	0.55				
				EHDT514MU1C70	120	0.13	0.70	15.09	945	63	4.64	0.65				
					240	0.06	0.70	15.49	945	61	4.52	0.63				
					277	0.06	0.70	15.78	945	60	4.44	0.62				
				EHDT514MU1C85	120	0.15	0.85	17.42	1148	66	4.88	0.68				
					240	0.07	0.85	17.76	1148	65	4.79	0.67				
					277	0.07	0.85	18.01	1148	64	4.72	0.66				
T5	14	2	M	EHDT514MU2C70	120	0.23	0.70	27.52	1890	69	2.54	0.71				
					240	0.11	0.70	27.53	1890	69	2.54	0.71				
					277	0.10	0.70	27.69	1890	68	2.53	0.71				
T5	21	1	M	EHDT521MU1C50	120	0.14	0.50	16.45	1050	64	3.04	0.64				
					240	0.07	0.50	17.06	1050	62	2.93	0.62				
					277	0.06	0.50	17.45	1050	60	2.87	0.60				
				EHDT521MU1C70	120	0.17	0.70	20.47	1470	72	3.42	0.72				
					240	0.09	0.70	21.45	1470	69	3.26	0.69				
					277	0.08	0.70	22.25	1470	66	3.15	0.66				
				EHDT521MU1C85	120	0.20	0.85	23.49	1785	76	3.62	0.76				
					240	0.10	0.85	24.74	1785	72	3.44	0.72				
					277	0.09	0.85	25.85	1785	69	3.29	0.69				
				EHDT521MU1C90	120	0.20	0.90	24.50	1890	77	3.67	0.77				
					240	0.11	0.90	25.84	1890	73	3.48	0.73				
					277	0.10	0.90	27.05	1890	70	3.33	0.70				
				T5	21	2	M	EHDT521MU2C85	120	0.36	0.85	43.29	3570	82	1.96	0.82
									240	0.18	0.85	43.32	3570	82	1.96	0.82
									277	0.16	0.85	43.38	3570	82	1.96	0.82
EHDT521MU2C90	120	0.38	0.90					45.09	3780	84	2.00	0.84				
	240	0.19	0.90					45.06	3780	84	2.00	0.84				
	277	0.16	0.90					45.08	3780	84	2.00	0.84				

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

<b>Job Name:</b>	<b>Model Numbers:</b>
<b>Job Number:</b>	

EcoSystem H-Series Ballasts (continued)

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T5	28	1	M	EHDT528MU1C50*	120	0.17	0.50	20.88	1450	69	2.39	0.67	>0.95	<10%
					240	0.09	0.50	21.30	1450	68	2.35	0.66		
					277	0.08	0.50	21.05	1450	69	2.38	0.67		
				EHDT528MU1C70*	120	0.22	0.70	25.94	2030	78	2.70	0.76		
					240	0.11	0.70	25.45	2030	80	2.75	0.77		
					277	0.09	0.70	25.98	2030	78	2.69	0.75		
				EHDT528MU1C77*	120	0.23	0.77	27.72	2233	81	2.78	0.78		
					240	0.11	0.77	26.91	2233	83	2.86	0.80		
					277	0.10	0.77	27.71	2233	81	2.78	0.78		
				EHDT528MU1C85*	120	0.25	0.85	29.74	2465	83	2.86	0.80		
					240	0.12	0.85	28.57	2465	86	2.98	0.83		
					277	0.11	0.85	29.68	2465	83	2.86	0.80		
				EHDT528MU1C90*	120	0.26	0.90	31.01	2610	84	2.90	0.81		
					240	0.12	0.90	29.60	2610	88	3.04	0.85		
					277	0.11	0.90	30.91	2610	84	2.91	0.82		
T5	28	2	M	EHDT528MU2C85*	120	0.46	0.85	55.54	4930	89	1.53	0.86		
					240	0.23	0.85	55.42	4930	89	1.53	0.86		
					277	0.20	0.85	55.33	4930	89	1.54	0.86		
				EHDT528MU2C88*	120	0.48	0.88	57.06	5104	89	1.54	0.86		
					240	0.24	0.88	56.96	5104	90	1.54	0.87		
					277	0.21	0.88	56.79	5104	90	1.55	0.87		
				EHDT528MU2C90*	120	0.48	0.90	58.07	5220	90	1.55	0.87		
					240	0.24	0.90	57.98	5220	90	1.55	0.87		
					277	0.21	0.90	57.75	5220	90	1.56	0.87		
T5	39	1	M	EHDT539MU1C90	120	0.34	0.90	40.87	3150	77	2.20	0.86		
					240	0.17	0.90	40.06	3150	79	2.25	0.88		
					277	0.14	0.90	40.14	3150	78	2.24	0.87		
T5	39	2	M	EHDT539MU2C90	120	0.63	0.90	76.05	6300	83	1.18	0.92		
					240	0.31	0.90	74.92	6300	84	1.20	0.94		
					277	0.27	0.90	74.91	6300	84	1.20	0.94		
T5	54	1	M	EHDT554MU1C80*	120	0.43	0.80	51.40	4000	78	1.56	0.84		
					240	0.21	0.80	50.09	4000	80	1.60	0.86		
					277	0.18	0.80	50.47	4000	79	1.59	0.86		
				EHDT554MU1C88*	120	0.47	0.88	56.35	4400	78	1.56	0.84		
					240	0.23	0.88	54.58	4400	81	1.61	0.87		
					277	0.20	0.88	54.90	4400	80	1.60	0.86		
				EHDT554MU1C93*	120	0.50	0.93	59.54	4650	78	1.56	0.84		
					240	0.24	0.93	57.39	4650	81	1.62	0.88		
					277	0.21	0.93	57.82	4650	80	1.61	0.87		
T5	54	2	M	EHDT554MU2C80*	120	0.89	0.80	106.80	8000	87	0.87	0.94		
					240	0.44	0.80	105.60	8000	87	0.87	0.94		
					277	0.38	0.80	105.26	8000	86	0.86	0.93		
				EHDT554MU2C93*	120	1.00	0.93	119.76	9300	88	0.88	0.95		
					240	0.49	0.93	117.60	9300	88	0.88	0.95		
					277	0.43	0.93	119.11	9300	87	0.87	0.94		

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

<b>Job Name:</b>	<b>Model Numbers:</b>
<b>Job Number:</b>	

**EcoSystem H-Series Ballasts (continued)**

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD						
T8	25	1	M	EHDT825MU1C58	120	0.16	0.58	19.31	1102	57	3.00	0.75	>0.95	<10%						
					240	0.08	0.58	19.20	1102	65	3.42	0.85								
					277	0.07	0.58	19.61	1102	56	2.96	0.74								
				EHDT825MU1C72	120	0.19	0.72	22.44	1368	61	3.21	0.80								
					240	0.10	0.72	24.00	1368	68	3.56	0.89								
					277	0.09	0.72	24.93	1368	60	3.18	0.80								
				EHDT825MU1C78	120	0.20	0.78	23.78	1482	62	3.28	0.82								
					240	0.10	0.78	24.00	1482	69	3.61	0.90								
					277	0.09	0.78	23.91	1482	62	3.26	0.82								
				EHDT825MU1C83	120	0.21	0.83	24.9	1577	63	3.33	0.83								
					240	0.11	0.83	26.4	1577	69	3.64	0.91								
					277	0.1	0.83	27.7	1577	63	3.32	0.83								
				EHDT825MU1C88	120	0.22	0.88	26.01	1672	64	3.38	0.85								
					240	0.12	0.88	28.8	1672	70	3.67	0.92								
					277	0.1	0.88	27.7	1672	64	3.38	0.84								
				T8	25	2	M	EHDT825MU2C72	120	0.35	0.72	42.01			2736	65	1.71	0.86	>0.95	<10%
									240	0.17	0.72	41.72			2736	66	1.73	0.86		
									277	0.15	0.72	41.97			2736	65	1.72	0.86		
EHDT825MU2C78	120	0.37	0.78					44.65	2964	66	1.75	0.87								
	240	0.18	0.78					44.21	2964	67	1.76	0.88								
	277	0.16	0.78					44.46	2964	67	1.75	0.88								
EHDT825MU2C88	120	0.41	0.88					49.05	3344	68	1.79	0.90								
	240	0.20	0.88					48.35	3344	69	1.82	0.91								
	277	0.18	0.88					48.60	3344	69	1.81	0.91								
T8	32	1	M	EHDT832MU1C50*	120	0.19	0.50	22.44	1500	67	2.23	0.71	>0.95	<10%						
					240	0.09	0.50	22.44	1500	67	2.23	0.71								
					277	0.08	0.50	22.64	1500	66	2.21	0.71								
				EHDT832MU1C58*	120	0.20	0.58	24.57	1740	71	2.36	0.76								
					240	0.10	0.58	24.48	1740	71	2.37	0.76								
					277	0.09	0.58	24.72	1740	70	2.35	0.75								
				EHDT832MU1C72*	120	0.24	0.72	28.30	2160	76	2.54	0.81								
					240	0.12	0.72	28.04	2160	77	2.57	0.82								
					277	0.10	0.72	28.34	2160	76	2.54	0.81								
				EHDT832MU1C78*	120	0.25	0.78	29.90	2340	78	2.61	0.83								
					240	0.12	0.78	29.56	2340	79	2.64	0.84								
					277	0.11	0.78	29.90	2340	78	2.61	0.83								
				EHDT832MU1C88*	120	0.27	0.88	32.56	2640	81	2.70	0.86								
					240	0.13	0.88	31.20	2340	79	2.64	0.84								
					277	0.12	0.88	32.49	2640	81	2.71	0.87								
				EHDT832MU1C11*	120	0.32	1.11	38.69	3330	86	2.87	0.92								
					240	0.16	1.11	37.96	3330	88	2.92	0.94								
					277	0.14	1.11	38.44	3330	87	2.89	0.92								
				EHDT832MU1C15*	120	0.33	1.15	39.76	3450	87	2.89	0.93								
					240	0.16	1.15	38.98	3450	89	2.95	0.94								
					277	0.14	1.15	39.48	3450	87	2.91	0.93								

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

**EcoSystem H-Series Ballasts (continued)**

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T8	32	2	M	EHDT832MU2C50*	120	0.37	0.50	44.19	3000	68	1.13	0.72	>0.95	<10%
					240	0.19	0.50	44.52	3000	67	1.12	0.72		
					277	0.16	0.50	44.80	3000	67	1.12	0.71		
				EHDT832MU2C71*	120	0.45	0.71	54.31	4260	78	1.31	0.84		
					240	0.23	0.71	54.15	4260	79	1.31	0.84		
					277	0.20	0.71	54.61	4260	78	1.30	0.83		
				EHDT832MU2C72*	120	0.46	0.72	54.79	4320	79	1.13	0.84		
					240	0.23	0.72	54.60	4320	79	1.32	0.84		
					277	0.20	0.72	55.07	4320	78	1.31	0.84		
				EHDT832MU2C78*	120	0.48	0.78	57.68	4680	81	1.35	0.87		
					240	0.24	0.78	57.36	4680	82	1.36	0.87		
					277	0.21	0.78	57.87	4680	81	1.35	0.86		
				EHDT832MU2C80*	120	0.49	0.80	58.64	4800	82	1.36	0.87		
					240	0.24	0.80	58.27	4800	82	1.37	0.88		
					277	0.21	0.80	58.81	4800	82	1.36	0.87		
				EHDT832MU2C83*	120	0.50	0.83	60.09	4980	83	1.38	0.88		
					240	0.25	0.83	59.65	4980	83	1.39	0.89		
					277	0.22	0.83	60.21	4980	83	1.38	0.88		
				EHDT832MU2C85*	120	0.51	0.85	61.05	5100	84	1.39	0.89		
					240	0.25	0.85	60.56	5100	84	1.40	0.90		
					277	0.22	0.85	61.14	5100	83	1.39	0.89		
				EHDT832MU2C86*	120	0.51	0.86	61.53	5160	84	1.40	0.89		
					240	0.25	0.86	61.02	5160	85	1.41	0.90		
					277	0.22	0.86	61.61	5160	84	1.40	0.89		
				EHDT832MU2C88*	120	0.52	0.88	62.50	5280	84	1.41	0.90		
					240	0.26	0.88	61.94	5280	85	1.42	0.91		
					277	0.23	0.88	62.54	5280	84	1.41	0.90		
				EHDT832MU2C11*	120	0.61	1.11	73.58	6660	91	1.51	0.97		
					240	0.30	1.11	72.48	6660	92	1.53	0.98		
					277	0.26	1.11	73.28	6660	91	1.51	0.97		
EHDT832MU2C15*	120	0.63	1.15	75.51	6900	91	1.52	0.97						
	240	0.31	1.15	74.32	6900	93	1.55	0.99						
	277	0.27	1.15	75.14	6900	92	1.53	0.98						

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

Job Name:	Model Numbers:
Job Number:	

### Hi-lume 3D Ballasts

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T5	14	2	C	H3DT514CU2C90	120	0.28	0.90	33.41	2430	73	2.69	0.75	>0.95	<10%
					240	0.14	0.90	33.13	2430	73	2.72	0.76		
					277	0.12	0.90	33.26	2430	73	2.71	0.76		
T5	21	1	C	H3DT521CU1C90	120	0.20	0.90	24.50	1890	77	3.67	0.77		
					240	0.11	0.90	25.84	1890	73	3.48	0.73		
					277	0.10	0.90	27.05	1890	70	3.33	0.70		
T5	21	2	C	H3DT521CU2C50	120	0.26	0.50	30.72	2100	68	1.63	0.68		
					240	0.13	0.50	31.18	2100	67	1.60	0.67		
					277	0.11	0.50	31.41	2100	67	1.59	0.67		
				H3DT521CU2C90	120	0.38	0.90	45.09	3780	84	2.00	0.84		
					240	0.19	0.90	45.06	3780	84	2.00	0.84		
					277	0.16	0.90	45.08	3780	84	2.00	0.84		
T5	28	1	C	H3DT528CU1C90*	120	0.27	0.90	32.40	2610	84	2.90	0.81		
					240	0.13	0.90	31.20	2610	88	3.04	0.85		
					277	0.12	0.90	33.24	2610	84	2.91	0.82		
T5	28	2	C	H3DT528CU2C85*	120	0.46	0.85	55.54	4930	89	1.53	0.86		
					240	0.23	0.85	55.42	4930	89	1.53	0.86		
					277	0.20	0.85	55.33	4930	89	1.54	0.86		
				H3DT528CU2C90*	120	0.48	0.90	58.07	5220	90	1.55	0.87		
					240	0.24	0.90	57.98	5220	90	1.55	0.87		
					277	0.21	0.90	57.75	5220	90	1.56	0.87		
T5	40	2	G	H3DT540GU2C85*	120	0.57	0.85	68.72	5270	77	1.24	0.99		
					240	0.28	0.85	67.92	5270	78	1.25	1.00		
					277	0.25	0.85	68.20	5270	77	1.25	1.00		
T5	54	1	C	H3DT554CU1C50*	120	0.27	0.50	32.82	2500	76	1.52	0.82		
					240	0.14	0.50	33.24	2500	75	1.50	0.81		
					277	0.12	0.50	33.52	2500	75	1.49	0.81		
T5	54	2	C	H3DT554CU2C90*	120	0.97	0.90	102.66	9000	88	0.88	0.95		
					240	0.48	0.90	102.64	9000	88	0.88	0.95		
					277	0.41	0.90	103.68	9000	87	0.87	0.94		
T8	17	1	C	H3DT817CU1C80	120	0.16	0.80	18.71	1040	56	4.28	0.73		
					240	0.08	0.80	18.92	1040	55	4.23	0.72		
					277	0.07	0.80	19.09	1040	54	4.19	0.71		
T8	25	1	C	H3DT825CU1C80	120	0.16	0.80	19.20	1520	63	3.30	0.83		
					240	0.08	0.80	19.20	1520	69	3.62	0.91		
					277	0.07	0.80	19.39	1520	62	3.29	0.82		
T8	25	2	C	H3DT825CU2C86	120	0.40	0.86	48.17	3268	68	1.79	0.89		
					240	0.20	0.86	47.53	3268	69	1.81	0.90		
					277	0.17	0.86	47.77	3268	68	1.80	0.90		

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

<b>Job Name:</b>	<b>Model Numbers:</b>
<b>Job Number:</b>	

**Hi-lume 3D Ballasts (continued)**

Lamp Type	Lamp (W)	# of Lamps	Case	Model	V(in)	A(in)	B.F.	W(in)	Lumens	System Efficacy	Ballast Efficacy Factor	Relative System Efficacy	Power Factor	THD
T8	32	1	C	H3DT832CU1C75*	120	0.24	0.75	29.10	2250	77	2.58	0.82	>0.95	<10%
					240	0.12	0.75	28.80	2250	78	2.60	0.83		
					277	0.11	0.75	29.12	2250	77	2.58	0.82		
				H3DT832CU1C80*	120	0.25	0.80	30.43	2400	79	2.63	0.84		
					240	0.13	0.80	30.07	2400	80	2.66	0.85		
					277	0.11	0.80	30.41	2400	79	2.63	0.84		
				H3DT832CU1C86*	120	0.27	0.86	32.03	2580	81	2.68	0.86		
					240	0.13	0.86	31.60	2580	82	2.72	0.87		
					277	0.12	0.86	31.97	2580	81	2.69	0.86		
T8	32	2	C	H3DT832CU2C50*	120	0.37	0.50	44.19	3000	68	1.13	0.72		
					240	0.19	0.50	44.52	3000	67	1.12	0.72		
					277	0.16	0.50	44.80	3000	67	1.12	0.71		
				H3DT832CU2C71*	120	0.45	0.71	54.31	4260	78	1.31	0.84		
					240	0.23	0.71	54.15	4260	79	1.31	0.84		
					277	0.20	0.71	54.61	4260	78	1.30	0.83		
				H3DT832CU2C86*	120	0.51	0.86	61.53	5160	84	1.40	0.89		
					240	0.25	0.86	61.02	5160	85	1.41	0.90		
					277	0.22	0.86	61.61	5160	84	1.40	0.89		
				H3DT832CU2C88*	120	0.52	0.88	62.50	5280	84	1.41	0.90		
					240	0.26	0.88	61.94	5280	85	1.42	0.91		
					277	0.23	0.88	62.54	5280	84	1.41	0.90		
				H3DT832CU2C90*	120	0.53	0.90	63.46	5400	85	1.42	0.91		
					240	0.26	0.90	62.86	5400	86	1.43	0.92		
					277	0.23	0.90	63.47	5400	85	1.42	0.91		

\* Not for sale in California – See CEC TITLE 20 REGULATION APP NOTE #601 (P/N 048601), for information on alternative models.

Lutron, Lutron, Hi-lume, and EcoSystem are trademarks of Lutron Electronics Co., Inc. registered in the U.S. and other countries.

**LUTRON SPECIFICATION SUBMITTAL**

<b>Job Name:</b>	<b>Model Numbers:</b>
<b>Job Number:</b>	