

LINE NO.	LAMP NUMBER	PRIMARY APPLICATION	DESIGN VOLTS	DESIGN WATTS	DESIGN AMPS	APPROX. INITIAL MAX CANDLE-POWER	BEAM SPREAD HOR. x VER. DEGREES	RATED AVERAGE LAB LIFE HOURS	BASE TYPE	MAXIMUM OVERALL LENGTH		FILAMENT TYPE
										in.	mm.	
PAR-56 Bulb 7" (178mm) Diameter (Continued)												
1	4863A*	Signal, Military, Amber	Hi 28.00 Lo 28.00	80.00 60.00	2.86 2.14	N.A. N.A.	34 x 7 34 x 7	400 400	WP	5.000	127	CC-6 CC-6
2	4863(OR)*	Signal, Military	Hi 28.00 Lo 28.00	80.00 60.00	2.86 2.14	N.A. N.A.	34 x 7 34 x 7	400 400	3 Eyelet	5.000	127	CC-6 CC-6
3	4860A*	Headlamp, Military, Amber	Hi 28.00 Lo 28.00	80.00 60.00	2.86 2.14	18,000 9,000	34 x 7 34 x 7	400 400	WP	5.000	127	CC-6 CC-6
4	4860	Headlamp, Military	Hi 28.00 Lo 28.00	80.00 60.00	2.86 2.14	24,000 12,000	34 x 7 34 x 7	400 400	3 Lug [Ⓣ]	5.000	127	CC-6 CC-6
5	4863*	Headlamp, Military	Hi 28.00 Lo 28.00	80.00 60.00	2.86 2.14	24,000 11,000	34 x 7 34 x 7	400 400	WP	5.000	127	CC-6 CC-6
6	H4815*	Flood, CIM, Halogen	28.00	90.00	3.21	2,500	55 x 30	800	2 Lug [Ⓣ]	4.000	102	2 C-6
7	651*	Headlamp, Train	37.50	110.00	2.93	14,000	30 x 10	1000	2 Lug [Ⓣ]	5.000	127	CC-6
Rectangular Bulb 55mm X 135mm (2.2" X 5.3")												
8	H4360	Tractor, Halogen	12.80	37.50	2.93	2,000	Trapezoidal	320	2 Lug	3.000	76.2	C-6
9	H4351	Headlamp, Automotive, Type L, Low Beam, Halogen	12.80	55.00	4.30	22,000	35 x 7	500	Rt. Angle Plastic	4.000	102	C-8
10	H4352	Headlamp, Automotive, Type U, High Beam, Halogen	12.80	65.00	5.08	45,000	26 x 5	150	Rt. Angle Plastic	4.000	102	C-8
Rectangular Bulb 92mm X 150mm (3.6" X 5.9")												
11	H9415A	Fog, Automotive, Amber, Halogen	12.80	37.50	2.93	—	45 x 5	200 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
12	H9415	Fog, Automotive, Halogen	12.80	37.50	2.93	12,000	45 x 5	200 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
13	H9406	Flood, Tractor, Halogen	12.80	50.00	3.91	1,350	70 x 30	400 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
14	H9414	Flood, Tractor, Halogen	12.80	50.00	3.91	2,700	45 x 20	400 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
15	H9411	Tractor, Halogen	12.80	50.00	3.91	5,400	Trapezoidal	400 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
16	H9421	Fog, Automotive, Halogen	12.80	50.00	3.91	14,000	45 x 8	200 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
17	H9420	Driving, Automotive, Halogen	12.80	50.00	3.91	47,000	15 x 5	200 [Ⓓ]	2 Lug Rt. Angle	3.000	76	C-6
18	H9405	Spot, Halogen	12.80	50.00	3.91	100,000	7 x 4	100	2 Lug Rt. Angle	3.000	76	C-6
19	H4703	Headlamp, Automotive, Type LF, Low Beam, Halogen	12.80	55.00	4.30	35,000	N.A.	320 [Ⓓ]	2 Lug	3.346	85	C-8
20	H4701	Headlamp, Automotive, Type UF, High Beam, Halogen	12.80	65.00	5.08	70,000	N.A.	150 [Ⓓ]	2 Lug	3.346	85	C-8
Rectangular Bulb 100mm X 165mm (4.2" X 6.5")												
21	H4651TV	TruView Sealed Beam	12.80	30.00	3.91	45,000	26 x 5	150	2 Lug [Ⓣ]	4.700		C-6
22	H4656	Headlamp, Automotive, Type 2A1, Low Beam, Halogen	Hi 12.80 Lo 12.80	35.00 35.00	2.73 2.73	15,000 25,000	35 x 7 35 x 7	200 [Ⓓ] 450 [Ⓓ]	3 Lug [Ⓣ]	4.425	111	C-6 C-6
23	HP4656*	Headlamp, Automotive, Type 2A1, Low Beam, Impact Resistant, Halogen	Hi 12.80 Lo 12.80	35.00 35.00	2.73 2.73	15,000 25,000	35 x 7 35 x 7	200 [Ⓓ] 450 [Ⓓ]	3 Lug [Ⓣ]	4.425	111	C-6 C-6

9

Ⓓ At 14 Volts Ⓣ Contact Type
NOTE: CIM = Construction Industrial Machinery D.C. = Double Contact MP = Multipurpose Rt. = Right S.C. = Single Contact
**This part number is included for reference only and inventory may not be available.*