



## H6024 Headlight



The Wagner® halogen sealed beam delivers brighter, whiter light than incandescent lighting.

- DOT/SAE compliant
- Non-reflective bottom shelf helps reduce glare in rain, snow and fog
- High-grade stainless steel terminals
- Coated with lacquer to prevent corrosion
- Shines up to 40% farther than incandescent lighting

### Specifications

#### Lamp Specifications

Part Description

PAR 56 Bulb 7 (178mm) Dia

Primary Application

	Headlamp, High Beam, Automotive, Headlamp, Low & High Beam, Halogen, Type 2D1
Base Type	3 Lug Contact
Bulb Color	Clear
Max. Overall Length (in.)	5.000
Max. Overall Length (mm)	127.0
Filament Quantity	2
Design Volts Primary	12.80
Design Watts Primary	60.00
Design Amps Primary	4.69
Approx. Max Candle Power Primary	35000
Beam Spread Primary (Hor. x Vert.)	35x7
Rated Avg. Life Hours Primary	150
Filament Type Primary	C-6
Design Volts Secondary	12.80
Design Watts Secondary	35.00
Design Amps Secondary	2.73
Approx. Max Candle Power Secondary	27000
Beam Spread Secondary (Hor. x Vert.)	35x7
Rated Avg. Life Hours Secondary	450
Filament Type Secondary	C-6