

HCI-TS 150 W/942 NDL PB

POWERBALL HCI-TS | Metal halide lamps with ceramic technology for enclosed luminaires



Areas of application

- Shopping arcades
- Foyers, reception areas
- Museums, exhibitions
- Exhibition halls and trade fairs
- Factories and workshops
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high efficiency
- Good to excellent color rendering
- Very good color stability
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERBALL ceramic technology
- Light colors: warm white (830 WDL), neutral white (942 NDL)
- Average lifetime: 15,000 h (operation with ECG with 70...400 Hz square-wave current)
- Average lifetime: 12,000 hours (with magnetic control gear)



Product datasheet

Technical data

Electrical data

Nominal wattage	150.00 W
Rated wattage	147.00 W
Lamp current	1.80000 A
PFC capacitor at 50 Hz	20 μ F ¹⁾
Ignition voltage	3.6 / 5.0 kVp ²⁾

¹⁾ At rated voltage and $\cos \varphi \geq 0.9$

²⁾ Minimum; for superimposed ignition with square wave electronic ballast 3.0 kVp are sufficient / Maximum; this limit is for safety reasons


Photometrical data

Luminous flux	14800 lm ¹⁾
Luminous efficacy	101 lm/W ²⁾
Color rendering index Ra	96
Color temperature	4200 K
Light color	942
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.75
Rated LLMF at 6,000 h	0.70
Rated LLMF at 8,000 h	0.67
Rated LLMF at 12,000 h	0.65
UV protection	Yes

¹⁾ In operation with low frequency square wave electronic ballast, 70...400 Hz. Operation with electromagnetic ballast may be less efficient.

²⁾ In operation with low frequency square wave electronic ballast, 70...400 Hz. Operation with electromagnetic ballast may be less efficient.

Dimensions & weight



Diameter	23.0 mm
Length	138.0 mm
Light center length (LCL)	69.0 mm

Product datasheet

Product weight	27.00 g
----------------	---------

Temperatures

Maximum permitted outer bulb temperature	650 °C
Maximum permitted pinch temperature	330 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.98
Rated lamp survival factor at 6,000 h	0.97
Rated lamp survival factor at 8,000 h	0.96
Rated lamp survival factor at 12,000 h	0.80
Lifespan B50	15000 h ¹⁾
Operation mode LLMF/LSF	ECG

¹⁾ At ECG

Additional product data

Base (standard designation)	RX7s-24
System guarantee level	3 (2/5)
Lamp mercury content	17.9 mg ¹⁾

¹⁾ Maximum

Capabilities

Dimmable	Yes ¹⁾
Burning position	p45
Enclosed luminaire required	Yes

¹⁾ In combination with POWERTRONIC PTo

Certificates & standards


Energy efficiency class	A+
Energy consumption	162 kWh/1000h

Country specific categorizations

ILCOS	MD/UB-150/942-H/SL-RX7s=24-25/132/H
-------	-------------------------------------

Product datasheet

Light Distribution



Spectral power distribution


System guarantee

For the vast majority of our lamps we are offering an extended system guarantee in conjunction with OSRAM POWERTRONIC control gear.




Guarantee


Product datasheet



Circuit diagram



Circuit diagram



Circuit diagram



Circuit diagram

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321679871	HCI-TS 150 W/942 NDL PB	Shipping carton box 12	180 mm x 178 mm x 142 mm	4.55 dm ³	603.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit

▶ www.osram.com/system-guarantee

Disclaimer