



LED LAMPS

ProLED[®] HID Omnidirectional Lamp Series



UL Rated



5 Year Warranty



DLC Qualified
For Mogul Based Lamps

The ProLED[®] HID Retrofit lamps are an easy to install LED solution for post tops, bollards and low bay fixtures. These lamps offer an energy-efficient alternative to traditional Metal Halide, Incandescent and CFL lamps. A 50,000 hour useful life, combined with the ability to eliminate the ballast ensures that luminaire maintenance is a thing of the past. The ProLED[®] HID Retrofit lamps are enclosed fixture and damp location rated. They are 84 CRI and come with the option of 3000K and 5000K color temperatures.



Halco[®]
LIGHTING TECHNOLOGIES

**A-Shape Design
Emits Omnidirectional,
Uniform Light**

**Frosted Lens
Reduces Glare**

**For Use in Base Up or
Base Down Positions**

**Acceptable for Use in
Enclosed Luminaires**

**120-277 Input Range -
Ballast Bypass**

Backed by a 5-Year Warranty

Applications:

Post Top Luminaires
Bollard Luminaires
Low Bay Luminaires

Markets:

Indoor commercial
Outdoor Commercial

Contact Your Customer Care Specialist
For Pricing, Orders And Technical Support.
800.677.3334 **www.halcolighting.com**

HID Omnidirectional Lamp Series

Product #: _____ Type: _____

Project: _____ Date: _____

Comments: _____ Initials: _____

Performance

CRI	_____	84
Rated Life	_____	50,000 hour life
Watt	_____	20W, 25W and 35W
Efficacy (LPW)	_____	<144
Min. Start Temp.	_____	-13°F(-25°C)
Max. Operating Temp.	_____	122°F(50°C)
Warranty	_____	5-Year Limited
Control	_____	Non-Dimmable
Weight	_____	0.59lb, 1.08lb and 1.56lb

Construction

- Omnidirectional design ideal for base up, base down, or horizontal operation
- UL Listed for Damp Locations
- E26 and EX39 Bases
- Mercury Free

Installation

- Ballast Bypass
- Acceptable for Enclosed Luminaires
- Rated for use in ambient temperatures up to 122°F(50°C)

Electrical

- Non - Dimmable
- 120 - 277 VAC input range
- 50/60Hz operating frequency
- Integral 4kV surge protection

Ordering Information

Product Code	Product Number	Wattage	Base	Volts	Lumens	Color Temp	CRI	Equivalent Wattage
HID20/OMNI/830/LED	84318	20W	E26	120-277V	2780	3000	84	80W
HID20/OMNI/850/LED	84319	20W	E26	120-277V	2865	5000	84	80W
HID25/OMNI/830/LED	84320	25W	E26	120-277V	3500	3000	84	100W
HID25/OMNI/850/LED	84321	25W	E26	120-277V	3612	5000	84	100W
HID25/OMNI/830/EX39/LED	84322	25W	EX39	120-277V	3500	3000	84	100W
HID25/OMNI/850/EX39/LED	84323	25W	EX39	120-277V	3612	5000	84	100W
HID35/OMNI/830/EX39/LED	84324	35W	EX39	120-277V	4620	3000	84	150W
HID35/OMNI/850/EX39/LED	84325	35W	EX39	120-277V	4760	5000	84	150W

