



**HID25/OMNI/850/LED  
84321 LED HID RETROFIT  
OMNIDIRECTIONAL  
BYPASS 25W 5000K NON  
DIMMABLE 120 277V E26**

| Specifications           | Resources | Technical  |
|--------------------------|-----------|--|
| Applications             |           | Post Top, Wall Pack, Low Bay                                       |
| Average Life (Hrs)       |           | 50,000   |
| Base                     |           | E26  |
| Beam Angle               |           | Omnidirectional  |
| Brand                    |           | ProLED   |
| CRI                      |           | 84   |
| CSA                      |           | No   |
| Color Temperature        |           | 5000K  |
| DesignLights Consortium  |           | No   |
| Dimmable                 |           | No   |
| ENERGY STAR              |           | No   |
| Equivalent Wattage       |           | 100W   |
| HTS code                 |           | 8539500090   |
| Initial Lumens           |           | 3612   |
| Inner Carton Quantity    |           | 1  |
| Input Current (Amps)     |           | 0.21   |
| Input Frequency (Hz)     |           | 50/60  |
| Markets                  |           | Commercial/Industrial  |
| Master Carton Quantity   |           | 24   |
| Maximum Overall Diameter |           | 3.23   |
| Maximum Overall Length   |           | 6.28   |
| Nominal Length           |           | 6.28   |
| Operating Position       |           | Universal  |
| Prod Code                |           | HID25/OMNI/850/LED   |
| Product Category         |           | LED  |
| Product Description      |           | LED HID RETROFIT OMNIDIRECTIONAL BYPASS 25W A21 5000K 120-277V E26 |
| Product Number           |           | 84321  |
| TITLE20 Y/N              |           | Y  |
| Voltage (V)              |           | 120-277V   |
| Warranty (Yrs)           |           | 5  |
| Wattage (W)              |           | 25   |