



Product Number: 54653

Order Abbreviation: HPL 750/120/X (UCF)

General Description: 750 watt, tungsten halogen, HPL series, long life

Product Information

| | |
|-----------------------------------|-----------------------------------|
| Abbrev. With Packaging Info. | HPL750120X (UCF) 120V 12/CS 1/SKU |
| Application | Stage & Studio |
| Average Rated Life (hr) | 2000 |
| Base | Medium Bipin with Heat Sink |
| Bulb | T6 |
| Class | C (gas) |
| Color Rendering Index (CRI) | 100 |
| Color Temperature (K) | 3065 |
| Diameter d (in) | 0.748 |
| Diameter d (mm) | 19.00 |
| Distance a (in) | 2.352 |
| Distance a (mm) | 60.3 |
| Family Brand Name | HPL |
| Filament | 4-C8 |
| Lamp Finish | Clear |
| Length l (in) | 4.1 |
| Length l (mm) | 104 |
| Length l max. (in) | 4.1 |
| Length l max. (mm) | 104 |
| Light Center Length - LCL (in) | 2.352 |
| Light Center Length - LCL (mm) | 60.3 |
| Luminous Flux (lm) | 16400 |
| Maximum Overall Length - MOL (in) | 4.1 |
| Maximum Overall Length - MOL (mm) | 104 |
| Nominal Voltage (V) | 120.00 |
| Nominal Wattage (W) | 750.00 |
| Operating Position | Any |
| Reflector Coating | 19.00 |
| Type of Current | AC |

Footnotes

- High-performance HPL halogen lamps are manufactured under license from ETC, Inc.