




HALOGEN



CONTENTS	90	How to Read a Table
	91	PAR Lamps
	93	Reflector Lamps
	93	AR111 Lamps
	93	Double Envelope Lamps
	94	MR8, MR11, MR16 Lamps
	98	JC and JCD Type Lamps
	99	Double Ended J Type Lamps
	100	Single Ended JD Type Lamps
	102	Bulb, Base and Filament Identification
	103	Symbols, Footnotes and Abbreviations





Bulb	Base	Product Number	Footnotes	Product Code	Description	Pkg. Qty.	Volts	Lumens	Color Temp	Avg. Life	Design Filament	MOL	Beam Spread	
PRISM® & HaloXen® JC Type (cont'd)														
25 WATT														
T4	G9	71001	3	JCD25/G9	Clear	10/500	130	280	2650	2000	CC-2V	1.65"	-	
		107902	3	JCD25FR/G9	Frost	10/500	130	280	2650	2000	CC-2V	1.65"	-	
35 WATT														
T4	BA15d	147012	3	JC35/BA15D	Clear	10/1000	12	600	2850	3000	C-8	1.50"	-	
		107720	2,3	JC35/BA15D/HX	Clear HaloXen®	10/1000	12	600	2900	10000	C-8	1.50"	-	
	G4	107000	3	JC35/G4	Clear	10/1000	12	600	2850	3000	C-8	1.58"	-	
		G6.35	107012	3	JC35	Clear	10/1000	12	600	2850	3000	C-8	1.58"	-
			107714	2,3	JC35/HX	Clear HaloXen®	10/1000	12	600	2900	10000	C-8	1.60"	-
		GY6.35	107011	3	JCD35	Clear	10/500	130	350	2800	2000	CC-2V	1.81"	-
	G8	107072	3	JCD35/G8	Clear	10/500	130	350	2800	2000	CC-2V	1.65"	-	
40 WATT														
T4	G9	107906	3	JCD40/G9	Clear	10/500	130	480	2750	2000	CC-2V	1.65"	-	
		107908	3	JCD40/FR/G9	Frost	10/500	130	450	2750	2000	CC-2V	1.65"	-	
		107310	3	JCD40/FR/G9/120	Frost	10/1000	120	450	2800	2000	CC-2V	1.65"	-	
50 WATT														
T4	BA15d	147014	x,3	JC50/BA15D	Clear	10/1000	12	900	2950	3000	C-8	1.50"	-	
		G6.35	107014	3	JC50	Clear	10/1000	12	900	2950	3000	C-8	1.58"	-
			107716	2,3	JC50/HX	Clear HaloXen®	10/1000	12	900	3000	10000	C-8	1.60"	-
			GY6.35	107015	3	JCD50	Clear	10/500	130	600	2900	2000	CC-2	1.81"
		G8	107074	3	JCD50/G8	Clear	10/500	130	600	2900	2000	CC-2	1.65"	-
60 WATT														
T4	G9	71002	3	JCD60/G9	Clear	10/500	130	780	2950	2000	CC-2V	1.65"	-	
		107904	3	JCD60FR/G9	Frost	10/500	130	750	2950	2000	CC-2V	1.65"	-	
75 WATT														
T4	GY6.35	107002	3	JC75	Clear	10/1000	12	1350	3000	3000	C-8	1.81"	-	
		107001	3	JCD75	Clear	10/500	130	980	2950	2000	CC-2V	1.81"	-	
100 WATT														
T4	GY6.35	107004	3	JC100	Clear	10/1000	12	2100	3100	3000	C-8	1.81"	-	
		107003	3	JCD100	Clear	10/500	130	1400	3050	2000	CC-2V	2.09"	-	
		G8	107070	3	JCD100/G8	Clear	10/500	130	1400	3050	2000	CC-2V	2.09"	-
PRISM® J Type Double Ended														
75 WATT														
T3	R7s	107212	3,8,9	Q75T3C	Clear 118mm	10/500	130	1200	2850	2000	C-8	4.65"	-	
		107210	3,8,9	Q75T3C/S	Clear 78mm	10/500	130	1250	2850	2000	C-8	3.07"	-	
100 WATT														
T3	R7s	107182	3,8,9	Q100T3C	Clear 118mm	10/500	130	1400	2950	2000	C-8	4.65"	-	
		107184	3,8,9	Q100T3C/S	Clear 78mm	10/500	130	1400	2950	2000	C-8	3.07"	-	