



Allusion LED Lamps with Smooth Warm Dimming

Introducing TCP® latest offering of Allusion LED lamps—the “incandescent-like” LEDs that offer a unique dimming profile, replicating true incandescent/halogen dimming.

Reasons to choose the Allusion LED Lamps from TCP

- Instant energy savings - up to 85% more efficient than incandescent/halogen replacements
- Long life of 25,000/30,000 hours (SL16) minimizes replacement and maintenance costs
- Smooth warm dimming creates the perfect atmosphere
- UL approved for damp locations* - can be used outdoors when protected from elements. Can withstand humidity indoors/outdoors
- Shatter resistance lowers the risk of injury and breakage

Ideal Applications

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Decorative
- Track lights
- Recessed Downlights

Specifications:

Voltage 120VAC/ 12 VAC (MR16)
Input Line Frequency..... 50/60HZ
Lamp Life (Rated) 25,000/30,000 (SL16) hours
Minimum Starting Temp -22°F/-30°C
Maximum Operating Temp..... 45°C

CRI..... 80
Color Temperatures 3000K to 2000K/
..... 3000K to 1800K (MR16)

Specifications:



PAR38
40°/25°
Beam Angles



PAR30
40°/25°
Beam Angles



PAR20
40°/25°
Beam Angles



MR16 GU5.3
20°
Beam Angles



SL16 Starlight
110° Beam Angle

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CCT	COLOR TEMPERATURE	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED PAR38 90W Equivalent												
L15P38DNFLA	LED 15W PAR38 30K Allusion NFL	120V	12.5	90	975	78.00	>80	3000K to 2000K	25°	5.4	4.75	E26
L15P38DFLA	LED 15W PAR38 30K Allusion FL	120V	12.5	90	975	78.00	>80	3000K to 2000K	40°	5.4	4.75	E26
LED PAR30 90W Equivalent												
L15P30DNFLA	LED 15W PAR30 30K Allusion NFL	120V	12.5	90	950	76.00	>80	3000K to 2000K	25°	4.7	3.8	E26
L15P30DFLA	LED 15W PAR30 30K Allusion FL	120V	12.5	90	950	76.00	>80	3000K to 2000K	40°	4.7	3.8	E26
LED PAR20 50W Equivalent												
L7P20DNFLA	LED 7W PAR20 30K Allusion NFL	120V	6.5	50	525	80.77	>80	3000K to 2000K	25°	3.4	2.5	E26
L7P20DFLA	LED 7W PAR20 30K Allusion FL	120V	6.5	50	525	80.77	>80	3000K to 2000K	40°	3.4	2.5	E26
LED MR16 50W Equivalent												
L712VMR16DNFLA	LED 7W MR16 30K Allusion NFL	12V	6	50	350	58.33	>80	3000K to 1800K	20°	1.9	2.0	5.3
LED SL16 Starlight												
L15SL16D30A	LED 13W SL16 30K Allusion	120V	13	—	1200	92.30	>80	3000K to 2000K	110°	3.8	6.3	E26

For the most up-to-date specs, please visit www.tcpi.com