



T8/T5 Type C LED Lamps and Drivers

HIGHLIGHTS

- Type C lamps offer superior efficacy compared to other types of LED tubes
- Type C drivers feature adjustable current outputs, making them compatible with a wide range of Type C tubes and providing flexibility to meet various lighting requirements and configurations
- Instantaneous full light output upon power-up
- Glass material for better light transmission
- Dimmable with 0-10V dimmer

CERTIFICATIONS

- ETL
- FCC Compliant
- RoHS Compliant
- ICES-005 Compliant
- Damp Location
- DesignLights Consortium® Qualified - meets DLC requirements for efficacy and lumen maintenance

PERFORMANCE

- High efficacy, up to 162 lm/W
- Available in single CCT models: 3500, 4000, or 5000K
- Adjustable current output drivers
- CRI: 83
- Rated Life: >50,000 hours

ELECTRICAL

- Drivers: 120-277VAC (input), 48VDC (output)
- Lamps: 48VDC
- Driver Surge protection: 2.5kV
- Power Factor: >0.9
- THD: <20%

THERMAL

- -4°F to 113°F (-20°C to 45°C) operating temperature
- Not recommended for air-tight fixtures

CONSTRUCTION

- Available in 2', 3', 4' and U-bend
- Frosted glass lens reduces glare and provides optimal light distribution
- G13 bi-pin

WARRANTY

- 5-Year limited warranty available [online](#). Contact your EiKO sales rep for additional details.

project name	type
catalog number	voltage
approved by	date

T8 Type C Lamps
Available in 2', 3' and 4' lengths



T8 U-BENDS



T5 Type C Lamps
Available in 4'



Type C Driver



APPLICATIONS

- Office
- Hospital
- Classroom
- Hotel
- Retail
- Warehouse
- Stairwell
- Hallway
- Production
- Gym
- Campus

MODEL CONFIGURATOR

MODEL	WATTAGE	TUBE SIZE	TUBE LENGTH	TYPE	WIRING	MATERIAL	CCT
L : LED	9W - 9W 11.5W - 11.5W 13.5W - 13.5W 15W - 15W 24W - 24W	T8 - T8 T5 - T5	24 - 2ft 36 - 3ft 46/48 - 4ft U1 - 1-5/8" U6 - 6"	C - Type C	D - Double-ended	G - Glass	35K - 3500K 40K - 4000K 50K - 5000K

AVAILABLE MODELS

ORDER	ORDER CODE	ITEM #	WATTS	LUMENS	EFFICACY (lm/W)	CCT (K)	CRI	BEAM ANGLE (°)	SYSTEM WATTAGE				TRADITIONAL WATTAGE EQUIVALENT	DLC FAMILY CODE
									DTC60WDIMCSU48		DTC30WDIMCSU48			
									4	3	2	1		
T8 TUBES														
2' LENGTH														
	15347	L9WT8/24/CDG/35K	7.92	1100	122	3500	83	200	36	27	18	9	17W Fluorescent	XXXFSY
	15348	L9WT8/24/CDG/40K	7.92	1100	122	4000	83	200	36	27	18	9	17W Fluorescent	XXXFSY
	15349	L9WT8/24/CDG/50K	7.92	1100	122	5000	83	200	36	27	18	9	17W Fluorescent	XXXFSY
3' LENGTH														
	15323	L11.5WT8/36/CDG/35K	10.12	1500	130	3500	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
	15325	L11.5WT8/36/CDG/40K	10.12	1500	130	4000	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
	15326	L11.5WT8/36/CDG/50K	10.12	1500	130	5000	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
4' LENGTH														
	15327	L11.5WT8/48/CDG/35K	10.12	1850	161	3500	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
	15328	L11.5WT8/48/CDG/40K	10.12	1850	161	4000	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
	15329	L11.5WT8/48/CDG/50K	10.12	1850	161	5000	83	200	46	34.5	23	11.5	25W Fluorescent	XXXFSY
	15331	L13.5WT8/48/CDG/35K	11.88	2200	163	3500	83	200	54	40.5	27	13.5	32W Fluorescent	XXXFVU
	15332	L13.5WT8/48/CDG/40K	11.88	2200	163	4000	83	200	54	40.5	27	13.5	32W Fluorescent	XXXFVU
	15333	L13.5WT8/48/CDG/50K	11.88	2200	163	5000	83	200	54	40.5	27	13.5	32W Fluorescent	XXXFVU
T8 U-BENDS														
1-5/8" INCH														
	15337	L15WT8/U1/CDG/35K	13.2	2200	147	3500	83	170	60	45	30	15	25W Fluorescent	QQQWCV
	15338	L15WT8/U1/CDG/40K	13.2	2200	147	4000	83	170	60	45	30	15	25W Fluorescent	QQQWCV
	15339	L15WT8/U1/CDG/50K	13.2	2200	147	5000	83	170	60	45	30	15	25W Fluorescent	QQQWCV
6" INCH														
	15340	L15WT8/U6/CDG/35K	13.2	2200	147	3500	83	170	60	45	30	15	25W Fluorescent	XXXFVU
	15341	L15WT8/U6/CDG/40K	13.2	2200	147	4000	83	170	60	45	30	15	25W Fluorescent	XXXFVU
	15342	L15WT8/U6/CDG/50K	13.2	2200	147	5000	83	170	60	45	30	15	25W Fluorescent	XXXFVU
T5 TUBES														
4" T5HE														
	15334	L15WT5/46/CDG/35K	13.2	1800	120	3500	83	180	60	45	30	15	28W Fluorescent	QQQWCV
	15335	L15WT5/46/CDG/40K	13.2	1800	120	4000	83	180	60	45	30	15	28W Fluorescent	QQQWCV
	15336	L15WT5/46/CDG/50K	13.2	1800	120	5000	83	180	60	45	30	15	28W Fluorescent	QQQWCV

ORDER	ORDER CODE	ITEM #	WATTS	LUMENS	EFFICACY (lm/W)	CCT (K)	CRI	BEAM ANGLE (°)	SYSTEM WATTAGE		TRADITIONAL WATTAGE EQUIVALENT	DLC FAMILY CODE	
									DTC60WDIMCSU48				DTC30WDIMCSU48
									2 LAMPS	1 LAMP			
T5 TUBES													
4FT T5HO													
	15344	L24WT5/46/CDG/35K	21.12	3200	133	3500	83	170	48	24	54W Fluorescent	QQQWCV	
	15345	L24WT5/46/CDG/40K	21.12	3200	133	4000	83	170	48	24	54W Fluorescent	QQQWCV	
	15346	L24WT5/46/CDG/50K	21.12	3200	133	5000	83	170	48	24	54W Fluorescent	QQQWCV	

COMPATIBLE EMERGENCY BATTERIES

ORDER CODE	ITEM #	DESCRIPTION	INPUT VOLTAGE	EMERGENCY TIME	OUTPUT POWER	BACKUP LUMENS	RECHARGE TIME	TITLE 20
11675	EEBE18WHA170S	External Emergency Battery, 18W	120-347V	>90 mins	18W	Refer to lamp*	24 hrs	Yes

* Refer to the lamp's lumen output for the Backup Lumens

DRIVERS

ORDER	ORDER CODE	ITEM #	INPUT VOLTAGE (VAC)	MAX CURRENT (A) @ 120VAC	MAX OUTPUT POWER (W)	OUTPUT VOLTAGE (VDC)	MAX TUBES
	15313	DTC30WDIMCSU48	120-277	0.250	30	48	2
	15321	DTC60WDIMCSU48	120-277	0.500	60	48	4

TYPE C DRIVER DIP SWITCH SETTINGS

DTC30WDIMCSU48 - 30W 120-277V DRIVER


SINGLE LAMP WATTAGE	MAX TUBES	MIN TUBES	S1	S2	S3
9W	2	1	ON	ON	ON
11.5W	2	1	ON	OFF	ON
13.5W	2	1	OFF	OFF	ON
15W	2	1	ON	ON	OFF
24W	1	1	OFF	ON	OFF

DTC60WDIMCSU48 - 60W 120-277V DRIVER


SINGLE LAMP WATTAGE	MAX TUBES	MIN TUBES	S1	S2	S3
9W	4	1	ON	ON	ON
11.5W	4	1	ON	OFF	ON
13.5W	4	1	OFF	OFF	ON
15W	4	1	ON	ON	OFF
24W	2	1	OFF	ON	OFF

PRODUCT DIMENSIONS


T8 - 2 FT.




T8 - 3 FT.




T8 - 4 FT.




T5 - 4 FT.




U1



U6







PRODUCT DIMENSIONS CONT'D



WIRING DIAGRAMS G13

Linear T8/T5 Type C LED Driver Wiring for 1-4 Lamps



U-Bend T8 Type C LED Driver Wiring for 1-3 Lamps

