



Commercial Grade **LED T8 Lamp**

Flex™
Internal Driver **LED Lamp**

Features & Benefits

- Assembled in USA
- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long Life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes shunted or unshunted G13 sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty
- High performance plastic series

Specification Data

Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD	DLC
L24T8/830/9P-ID DE BAA/TAA	24	G13	9	120-277	3000	1150	80	325	127	0.9	<20%	Yes
L24T8/835/9P-ID DE BAA/TAA	24	G13	9	120-277	3500	1150	80	325	127	0.9	<20%	Yes
L24T8/840/9P-ID DE BAA/TAA	24	G13	9	120-277	4000	1150	80	325	127	0.9	<20%	Yes
L24T8/850/9P-ID DE BAA/TAA	24	G13	9	120-277	5000	1150	80	325	127	0.9	<20%	Yes

Ordering Information

EXAMPLE: **L48T8/840/14G-ID DE**

L Manufacturer's Code	48 Normal Length 48=48"	T8 Lamp Shape T8=T8	8 CRI 8=>80	40 CCT 50=5000K 40=4000K 35=3500K	12 P Wattage 12P-12W	- ID Internal Driver	DE Double End Input
---------------------------------	--------------------------------------	----------------------------------	--------------------------	--	-----------------------------------	--------------------------------	-------------------------------

Wiring diagram



