



California Quality LED Lamp Specifications

ENERGY EFFICIENT • 15,000 / 25,000 / 35,000 HOURS • DIMMABLE

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	BEAM ANGLE	COLOR	HOURS	CRI	MOL (inches)	DIA (inches)	TITLE 20	JA8	ENERGY STAR	BASE	CASE QTY
--------	-------------	-------	-------------------	--------	------------	-------	-------	-----	--------------	--------------	----------	-----	-------------	------	----------

A Lamps

Dimmable • 25,000 Hour

L40A19D2527KCQ	A19 40W 27K DIM CQ	6	40	475	OMNI	2700K	25,000	90	4.0	2.2	Y	Y	Y	E26	48
L40A19D2530KCQ	A19 40W 30K DIM CQ	6	40	475	OMNI	3000K	25,000	90	4.0	2.2	Y	Y	Y	E26	48
L40A19D2541KCQ	A19 40W 41K DIM CQ	6	N/A	525	OMNI	4100K	25,000	90	4.0	2.2	Y	N/A	Y	E26	48
L40A19D2550KCQ	A19 40W 50K DIM CQ	6	N/A	525	OMNI	5000K	25,000	90	4.0	2.2	Y	N/A	Y	E26	48
L11A19GUD2527KCQ	LED 10W A19 GU24 DIM 27K CQ	10	60	800	OMNI	2700K	25,000	90	4.8	2.4	Y	Y	Y	GU24	48
L11A19GUD2530KCQ	LED 10W A19 GU24 DIM 30K CQ	10	60	850	OMNI	3000K	25,000	90	4.8	2.4	Y	Y	Y	GU24	48
L60A19D2527KCQ	A19 60W 27K DIM CQ	10	60	800	OMNI	2700K	25,000	90	4.3	2.4	Y	Y	Y	E26	48
L60A19D2530KCQ	A19 60W 30K DIM CQ	10	60	800	OMNI	3000K	25,000	90	4.3	2.4	Y	Y	Y	E26	48
L60A19D2541KCQ	A19 60W 41K DIM CQ	10	N/A	800	OMNI	4100K	25,000	90	4.3	2.4	Y	N/A	Y	E26	48
L60A19D2550KCQ	A19 60W 50K DIM CQ	10	N/A	800	OMNI	5000K	25,000	90	4.3	2.4	Y	N/A	Y	E26	48
L75A19D2527KCQ	A19 75W 27K DIM CQ	13	75	1100	OMNI	2700K	25,000	90	4.4	2.5	Y	Y	Y	E26	48
L75A19D2530KCQ	A19 75W 30K DIM ECQ	13	75	1100	OMNI	3000K	25,000	90	4.4	2.5	Y	Y	Y	E26	48
L75A19D2541KCQ	A19 75W 41K DIM CQ	13	N/A	1100	OMNI	4100K	25,000	90	4.4	2.5	Y	N/A	Y	E26	48
L75A19D2550KCQ	A19 75W 50K DIM CQ	13	N/A	1100	OMNI	5000K	25,000	90	4.4	2.5	Y	N/A	Y	E26	48
L100A21GUD2527KCQ	A21 100W 27K GU24 DIM CQ	16.5	100	1600	OMNI	2700K	25,000	90	5.2	2.5	Y	Y	Y	GU24	48
L100A21GUD2530KCQ	A21 100W 30K GU24 DIM CQ	16.5	100	1600	OMNI	3000K	25,000	90	5.2	2.5	Y	Y	Y	GU24	48
L100A21D2527KCQ	A21 100W 27K DIM CQ	17	100	1600	OMNI	2700K	25,000	90	5.2	2.8	Y	Y	Y	E26	48
L100A21D2530KCQ	A21 100W 30K DIM CQ	17	100	1625	OMNI	3000K	25,000	90	5.2	2.8	Y	Y	Y	E26	48
L100A21D2541KCQ	A21 100W 41K DIM CQ	17	N/A	1675	OMNI	4100K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48
L100A21D2550KCQ	A21 100W 50K DIM CQ	17	N/A	1675	OMNI	5000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48
L100A213W2527KCQ	A21 3 WAY 100/60/40W 27K CQ	17/10/6	100/60/40	1650/800/450	OMNI	2700K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48
L100A213W2530KCQ	A21 3 WAY 100/60/40W 30K CQ	17/10/6	100/60/40	1650/800/450	OMNI	3000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48
L100A213W2541KCQ	A21 3 WAY 100/60/40W 41K CQ	17/10/6	N/A	1700/800/450	OMNI	4100K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48
L100A213W2550KCQ	A21 3 WAY 100/60/40W 50K CQ	17/10/6	N/A	1700/800/450	OMNI	5000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	48

BR Lamps

Dimmable • 25,000 Hour

L65BR30D2527KCQ	BR30 65W 27K DIM CQ	8	65	650	110°	2700K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L65BR30D2530KCQ	BR30 65W 30K DIM CQ	8	65	650	110°	3000K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L65BR30D2541KCQ	BR30 65W 41K DIM CQ	8	N/A	650	110°	4100K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L65BR30D2550KCQ	BR30 65W 50K DIM CQ	8	N/A	700	110°	5000K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L100BR30D2527KCQ	BR30 100W 27K DIM CQ	16	100	1500	110°	2700K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L100BR30D2530KCQ	BR30 100W 30K DIM CQ	16	100	1550	110°	3000K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L100BR30D2541KCQ	BR30 100W 41K DIM CQ	16	N/A	1600	110°	4100K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L100BR30D2550KCQ	BR30 100W 50K DIM CQ	16	N/A	1600	110°	5000K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L85BR40D2527KCQ	BR40 85W 27K DIM CQ	13.5	85	1065	110°	2700K	25,000	90	6.1	5.0	Y	Y	Y	E26	12
L85BR40D2530KCQ	BR40 85W 30K DIM CQ	13.5	85	1065	110°	3000K	25,000	90	6.1	5.0	Y	Y	Y	E26	12
L85BR40D2541KCQ	BR40 85W 41K DIM CQ	13.5	N/A	1065	110°	4100K	25,000	90	6.1	5.0	Y	N/A	Y	E26	12
L85BR40D2550KCQ	BR40 85W 50K DIM CQ	13.5	N/A	1065	110°	5000K	25,000	90	6.1	5.0	Y	N/A	Y	E26	12

R20 Lamps

Dimmable • 25,000 Hour

L50R20D2527KCQ	R20 50W 27K DIM CQ	7	50	525	110°	2700K	25,000	90	3.8	2.5	Y	Y	Y	E26	48
L50R20D2530KCQ	R20 50W 30K DIM CQ	7	50	525	110°	3000K	25,000	90	3.8	2.5	Y	Y	Y	E26	48