LED A-Lamps

Omni-directional

All-purpose

3-way



TCP's LED A-Lamps provide the lighting you need at a cost you will love. Advanced factory techniques and rigorous testing ensure each lamp is perfect from day one. Install an LED A-lamp wherever you would a traditional lamp and see the improvement.

Reasons to choose the LED A-Lamps from TCP

- Use up to 85% less energy than halogen alternatives for instant energy savings
- Long-life minimizes replacement and maintenance costs
- Very low heat generation -- perfect for sensitive display lighting such as galleries, window displays and general lighting applications
- UL approved for damp locations, can be used in covered indoor and outdoor fixtures
- Excellent color consistency and CRI enhance colors of focal point while maintaining uniformity throughout lighting installation
- Durable polycarbonate material for shatterproof composition lowers the risk of injury and breakage
- ANSI construction compliant; will fit all A-lamp installations
- Dims to ≤10% of full light level when applicable

Ideal Applications

- General lighting
- Table lamps
- Floor lamps
- Sconces
- Ceiling fixtures
- Post lights

Specifications

Voltage ..... 120 VAC
Input Line Frequency..... 50/60Hz
Lamp Life (Rated) ..... 10,000/15,000/25,000 hours
Minimum Starting Temp .....-30°C (-22°F)
Maximum Operating Temp.....40°C (104°F)

CRI.....80

Suitable for use in totally enclosed fixtures (Vapor tight or jelly jar applications may reduce life).

Do not use more than 2 bulbs in an enclosed fixture. If fixture is manufactured for incandescent bulbs, use no higher than the LED equivalent wattage, as shown on this spec sheet.

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

c UL us LISTED

5 YEAR WARRANTY
25,000 HOUR LAMPS
Based on 12 hours use per day

LED A-Lamps

Specifications

ITEM #	DESCRIPTION	VOLTAGE	WATTS	INCANDESENT WATTS	LPW	LUMENS	COLOR	HOURS	CRI	MOL (IN.)	DIA (IN.)	BASE	WARRANTY YEARS	CASE QTY
6W A19 A-Lamp – Dimmable • 25,000 Hours														
L40A19D2524K	LED 6W A19 DIM 2400K	120	6	40	62.5	375	2400K	25,000	80	4.1	2.4	E26	5	12
L40A19D2527K	LED 6W A19 DIM 2700K	120	6	40	80	480	2700K	25,000	80	4.1	2.4	E26	5	12
L40A19D2530K	LED 6W A19 DIM 3000K	120	6	40	80	480	3000K	25,000	80	4.1	2.4	E26	5	12
L40A19D2541K	LED 6W A19 DIM 4100K	120	6	40	83.3	500	4100K	25,000	80	4.1	2.4	E26	5	12
L40A19D2550K	LED 6W A19 DIM 5000K	120	6	40	87.5	525	5000K	25,000	80	4.1	2.4	E26	5	12
9W A19 A-Lamp – Dimmable • 25,000 Hours														
L9A19D2524K	LED 9W A19 DIM 2400K	120	9	60	77.7	700	2400K	25,000	80	4.3	2.4	E26	5	12
L9A19D2527K	LED 9W A19 DIM 2700K	120	9	60	88.9	800	2700K	25,000	80	4.3	2.4	E26	5	12
L9A19D2530K	LED 9W A19 DIM 3000K	120	9	60	88.9	800	3000K	25,000	80	4.3	2.4	E26	5	12
L9A19D2535K	LED 9W A19 DIM 3500K	120	9	60	88.9	800	3500K	25,000	80	4.3	2.4	E26	5	12
L9A19D2541K	LED 9W A19 DIM 4100K	120	9	60	91.7	825	4100K	25,000	80	4.3	2.4	E26	5	12
L9A19D2550K	LED 9W A19 DIM 5000K	120	9	60	91.7	825	5000K	25,000	80	4.3	2.4	E26	5	12
9W A19 A-Lamp – Allusion Dimmable • 25,000 Hours														
LED9A19DA	LED 9W A19 2000K - 2700K ALLUSION	120	9	60	72.2	650	2000K-2700K	25,000	80	4.6	2.4	E26	5	12
9.5W A19 A-Lamp GU24 – Dimmable • 25,000 Hours														
L10A19GUD27K	LED 9.5W A19 GU24 DIM 27K	120	9.5	60	84.2	800	2700K	25,000	80	4.2	2.4	GU24	5	12
L10A19GUD30K	LED 9.5W A19 GU24 DIM 30K	120	9.5	60	89.5	850	3000K	25,000	80	4.2	2.4	GU24	5	12
L10A19GUD41K	LED 9.5W A19 GU24 DIM 41K	120	9.5	60	89.5	850	4100K	25,000	80	4.2	2.4	GU24	5	12
L10A19GUD50K	LED 9.5W A19 GU24 DIM 50K	120	9.5	60	89.5	850	5000K	25,000	80	4.2	2.4	GU24	5	12
11.5W A19 A-Lamp – Dimmable • 25,000 Hours														
L75A19D2527K	LED 11.5W A19 DIM 2700K	120	11.5	75	81.5	1100	2700K	25,000	80	4.4	2.4	E26	5	12
L75A19D2530K	LED 11.5W A19 DIM 3000K	120	11.5	75	81.5	1100	3000K	25,000	80	4.4	2.4	E26	5	12
L75A19D2541K	LED 11.5W A19 DIM 4100K	120	11.5	75	81.5	1100	4100K	25,000	80	4.4	2.4	E26	5	12
L75A19D2550K	LED 11.5W A19 DIM 5000K	120	11.5	75	81.5	1100	5000K	25,000	80	4.4	2.4	E26	5	12
15W A19 A-Lamp – Dimmable • 25,000 Hours														
L15A19D2527K	LED 15W A19 DIM 2700K	120	15	100	106.7	1600	2700K	25,000	80	4.7	2.6	E26	5	12
L15A19D2530K	LED 15W A19 DIM 3000K	120	15	100	106.7	1600	3000K	25,000	80	4.7	2.6	E26	5	12
L15A19D2541K	LED 15W A19 DIM 4100K	120	15	100	106.7	1600	4100K	25,000	80	4.7	2.6	E26	5	12
L15A19D2550K	LED 15W A19 DIM 5000K	120	15	100	106.7	1600	5000K	25,000	80	4.7	2.6	E26	5	12
9.5W A19 Omni-Directional Wet Location A-Lamp – Dimmable • 25,000 Hours														
LED10A19DOD27KW	LED 9.5W A19 DIM OMNI 27K WET	120	9.5	60	84.2	800	2700K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD30KW	LED 9.5W A19 DIM OMNI 30K WET	120	9.5	60	86.8	825	3000K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD41KW	LED 9.5W A19 DIM OMNI 41K WET	120	9.5	60	89.5	850	4100K	25,000	80	4.6	2.5	E26	5	12
LED10A19DOD50KW	LED 9.5W A19 DIM OMNI 50K WET	120	9.5	60	89.5	850	5000K	25,000	80	4.6	2.5	E26	5	12
4/8/16W A21 3-Way A-Lamp • 25,000 Hour														
LED16A21D3WAY27K	LED 16W A21 2700K 3WAY	120	4/8/16	40/60/100	120/100/100	480/800/1600	2700K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY30K	LED 16W A21 3000K 3WAY	120	4/8/16	40/60/100	120/100/100	480/800/1600	3000K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY41K	LED 16W A21 4100K 3WAY	120	4/8/16	40/60/100	120/100/100	480/800/1600	4100K	25,000	80	4.9	2.6	E26	5	12
LED16A21D3WAY50K	LED 16W A21 5000K 3WAY	120	4/8/16	40/60/100	120/100/100	480/800/1600	5000K	25,000	80	4.9	2.6	E26	5	12

SUGGESTED DIMMER COMPATIBILITY			
MANUFACTURER	MODEL NUMBER	MANUFACTURER	MODEL NUMBER
Lutron	CTCL-153PDH-WH	Leviton	R50-IPL06-10M
	TGCL-153PH-WH		R61-06674-P0I
	DVWCL-153PH-WH		

Note: E26 compatible dimmer

For the most up-to-date specs, please visit www.tcpi.com

TCP®
325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcpi.com

©TCP AUG 2025/WF195102

c UL us LISTED

5 YEAR WARRANTY
25,000 HOUR LAMPS
Based on 12 hours use per day