

Pulse Rated Sockets, Thermal Detectors

Thermal Detector

- A. L9454 B. L9454-277
(277 volts)

8.2k resistor, 120 Volts, opening temperature
is 135°C, 18 ga. 105°C 6" lds.



Metal Halide Lamps (G12 Base)


L557

12" lds, 200 C°, 5KV pulse rated,
660W-600V, max lamp rating
150W



Intermediate Base Hickey
or Bracket

- A. L2624-F B. L2623
(side bracket)

porcelain, 75W-250V 9" 150 dg, lds


Standard Type Base
660W-250V

- A. L380 B. L396
(terminals) (leads)



Mogul Base Par Connector

- A. L357F V+
B. L357-4KV (pulse rated)

6" lds, 200 C°, 660W-125V,
porcelain, for par 56 & 64



Brass Knob

S50

1-1/4" long, push-on



Die-Cast Mogul Cap

- A. LX6590 - 1/4 IPS
B. LX6591 - 3/8 IPS
C. LX6592 - 1/2 IPS

furnished with insulators,
mounting holes, tapped 8-32



Mogul (Position-Oriented)

- A. L8750 (2) 8/32 screws
B. L8750-2 (2) 8/32 nuts
1500W-600V, #14 AWG
200° 12" lds


Standard Type Starts
660W-250V

- A. FS2 - 14, 15, 20W
B. FS4 - 13, 30, 40W
C. FS5 - 4, 6, 8W
D. FS12 - 32W circline
E. FS25 - 22, 25W circline

plastic housing



Mogul Lampholder (Keyless)

L8678

1500W-600V, cap 1/4 IPS



Mogul Two-Circuit

L8601F

low-med-high-off, removable brass
knob, 750W-250V, 1/4 IP hickey



Mogul 4 KV Pulse Rated

1500W - 600V 14AWG 200 dg.

- L8756 - domestic
L8756F - Value Plus
L8756-2 - domestic
2 Screws



PULSE RATED SOCKETS

Medium (4KV Pulse Rated)

- A. L70046F (2) screws
B. L70045 (2) 6-32 bushings
C. L70045F V+
D. L70045-36F V+ 36" leads
660W -600V, 14 AWG 200°,
18ga. 9" leads



Mogul (5KV Pulse Rated)

- A. L8746 VALUE
PLUS
B. L8746F

1500W -600V, 14 AWG 200°,
(2) 8-32 Screws 12" lds.



Medium Base (4KV Pulse Rated)

Snap-In Socket, 660W -600V

- L18876 -9" 200° lds



Mogul (4KV Pulse Rated)

L8751

(2) 8-32 screws #14 AWG
200°. 12" lds., 1500W -600V

Specially designed for use with metal
halide lamps. Mogul-base metal ha-
lide lamps without the inner protective
shield will not make contact with the
lamp holders center contact.

