



Project / Job Name:

Location:

Fixture Type:

Notes:

**65-1330** - 40W/35W/30W/25W/20W Wattage Selectable LED Light Bar Retrofit Kit; 3000K/3500K/4000K/5000K/6500K CCT Selectable; 2-Bars; 2 Feet; 120-277 Volt; Silver Finish



| GENERAL                   |                                                               |
|---------------------------|---------------------------------------------------------------|
| Company                   | NUVO                                                          |
| EA Height                 | 1.18                                                          |
| EA Width                  | 3.23                                                          |
| EA Length                 | 22.44                                                         |
| Bulb Included             | Integrated                                                    |
| Material                  | Aluminum                                                      |
| Fixture Type              | Backlit Flat Panel                                            |
| Includes                  | Magnetic Feet, Screws, Wire nuts                              |
| Product Notes             | Default CCT setting is 4000K; Default Wattage setting is 40W. |
| Status                    | Active                                                        |
| Style                     | Utility                                                       |
| Surge Protection          | Built-in surge protection - 1KV                               |
| Total Harmonic Distortion | <20%                                                          |
| Up Down Installation      | Down                                                          |
| CCT Selectable            | Yes                                                           |
| Wattage Selectable        | Yes                                                           |
| Finish Family             | Silver                                                        |
| Additional Info           | Default CCT setting is 4000K; Default Wattage setting is 40W. |
| Amps                      | 0.333-0.144/0.292-0.126/0.25-0.108/0.208-0.09/0.167-0.072A    |
| Lens Finish               | Frosted                                                       |
| Lens Material             | Polycarbonate (PC)                                            |
| Nominal Length            | 21.0                                                          |
| Power Factor              | >0.9                                                          |
| SDS Class                 | LED_Fixture                                                   |
| Indoor Outdoor            | Indoor                                                        |
| Product Technology        | LED                                                           |
| Fluor Equiv               | 2 x 17W T8                                                    |

| ELECTRICAL          |                               |
|---------------------|-------------------------------|
| CCT (Kelvin Temp)   | 3000K/3500K/4000K/5000K/6500K |
| Dimmable            | Yes-Dimmable                  |
| Hours Rated         | 50000                         |
| Beam Angle (degree) | 120                           |
| Color Temp          | Soft White to Daylight        |
| CRI                 | 80+                           |
| Dimming Type        | 0-10V Dimming                 |
| Operating Frequency | 50/60Hz                       |
| Operating Temp      | -4F to +113F (-20C to +45C)   |
| Lumens              | 5000L/4375L/3750L/3125L/2500L |
| Volts               | 120V-277V                     |
| Watts               | 40W/35W/30W/25W/20W           |

| PHYSICAL      |                |
|---------------|----------------|
| Lamp Base     | Integrated     |
| Finish        | SILVER         |
| Housing Color | Silver         |
| ANSI Base     | Integrated     |
| Lamp Type     | Integrated LED |
| Fixture Shape | Rectangle      |

| ADDITIONAL INFO            |         |
|----------------------------|---------|
| Warranty                   | 5-Years |
| Rated For Enclosed Fixture | Yes     |

| FEATURES     |     |
|--------------|-----|
| Flicker Free | Yes |

| PACKAGING     |                |
|---------------|----------------|
| UPC           | 045923409844   |
| Case Cube     | 0.6567         |
| Case Height   | 6.89           |
| Case Length   | 23.23          |
| Case Quantity | 10             |
| Case UPC      | 10045923409841 |
| Case Weight   | 18.0           |
| Case Width    | 7.09           |
| EA Cube       | 0.0495         |
| EA Height     | 1.18           |
| EA Length     | 22.44          |
| EA Quantity   | 1              |
| EA Weight     | 1.6            |
| EA Width      | 3.23           |
| Pack Type     | Kraft Box      |
| Web Height    | 1.19           |
| Web Length    | 20.87          |
| Web Width     | 0.93           |

| COMPLIANCE            |                   |
|-----------------------|-------------------|
| CA Prop 65            | Lead              |
| Dark Sky Rated        | No                |
| DLC ID                | S-570F3T          |
| FCC Compliant         | Yes               |
| Location Rating       | Damp              |
| NSF Approved          | No                |
| ROHS Compliant        | Yes               |
| Safety Listing        | cULus - Certified |
| California Ban        | Lawful for sale   |
| DLC Approved          | Yes               |
| Energy Star Certified | No                |
| Title 20              | Exempt            |
| T24/JA8 Compliant     | No                |