




## RETROFIT FLUORESCENT T5s W/ LONG-LASTING, ENERGY-SAVING LED T5s.


High-quality Type A+B tubes provide excellent light output. Install our retrofit to get worry-free operation for years to come.

- 3-in-one operation — Ballast or ballast bypass w/ either single or double ended connection
- Available in 2 FT, 3 FT and 4 FT lengths
- Shatter-resistant glass construction and frosted lens
- Suitable for dry and damp locations
- UL classified retrofit listed


----- **SHATTER-RESISTANT  
GLASS LENS**



LED-12T5HO-8XXAB24-G5



LED-18T5HO-8XXAB36-G5



LED-25T5HO-8XXAB48-G5



PART #	REPLACES	WATTAGE	LUMENS	CCT	BASE	DLC CODE		
LED-12T5HO-835AB24-G5	24W	12W	1600	3500K	G5 MINI BI-PIN	N/A		
LED-12T5HO-840AB24-G5				4000K				
LED-12T5HO-850AB24-G5				5000K				
LED-18T5HO-835AB36-G5	39W	18W	2500	3500K				
LED-18T5HO-840AB36-G5				4000K				
LED-18T5HO-850AB36-G5				5000K				
LED-25T5HO-835AB48-G5	54W	25W	3500	3500K			G5 MINI BI-PIN	PENDING
LED-25T5HO-840AB48-G5				4000K				
LED-25T5HO-850AB48-G5				5000K				

\* NOTE MAXIMUM NUMBER OF LAMPS PER CIRCUIT IS 40 UNITS. PRODUCT IS DESIGNED TO OPERATE ON STANDARD ELECTRICAL SYSTEMS, AND MAY BE INCOMPATIBLE WITH UNCONVENTIONAL ELECTRICAL SYSTEMS. PLEASE SEE INSTALLATION INSTRUCTIONS FOR MORE DETAILS.

