# LED-8055 PAR38 / Recessed / Flood


SKU No. (USA) SKU No. Canada


LED-8055E27 LED-8055E27C 30W, 2700K LED-8055E42 LED-8055E42C 30W, 4200K LED-8055E57 LED-8055E57C 30W, 5700K 30w = 100W
HH/HPS

#### **Description:**

30W LED retrofit design replaces MH and HPS lamps up to 100w. Design features 24 high power LEDs delivering a uniform 120° light distribution. Suitable for fully enclosed and/or recessed fixtures..

- 30W power consumption
- Replaces up to a 100W HID
- 120° Beam
- 120-277VAC, Non-Dimmable (USA) 120-347VAC, Non-Dimmable (Canada)
- Available in 2700K, 4200K & 5700K CCT
- >80 CRI
- 50,000 hr. rated L70 LED life
- Operating temp: -40°F 122°F
- · Double insulated
- UL Listed (US & CA) Damp Locations and rated for enclosed fixtures (pending)
- 5 Year warranty





#### **Applications:**

LED PAR38 / Recessed / Flood LED for HID retrofit lamps lower energy costs, bulb and ballast replacement costs and also can greatly reduce costly equipment rental when re-lamping HID lamps on and off cycle. LED for HID retrofits will also eliminate lamp disposal issues due to the mercury content of many HID lamps.

- Recessed
- Flood
- Spot

### Packaging: 4/Master Carton

Unit : 6.6" x 6.6" x 9.65" Master: 13.82" x 13.82 x 10.24"

## **Installation Notes:**

- When installing LED-8000 series retrofit lamps within HID fixtures, ballast must be bypassed when present.
- 8000 series retrofits are UL damp rated, sealing the fixtures after installation will deliver best results.
- Installing surge/lightning protectors is highly recommended and helps to eliminate premature driver failure caused by surges and other power fluctuations.

| Technical Specifications |  |                          |                         |
|--------------------------|--|--------------------------|-------------------------|
| Bulb Type                | HID Retrofit                                       | Mounting                 | E26                     |
| Bulb Material            | Aluminum/<br>Polycarbonate                         | LEDs:                    | 24 SMD LED's            |
| Power<br>Consumption     | 30 watts   | Beam Angle               | 120°                    |
| Lumens                   | 2700K: 2100 Lm<br>4200K: 2300 Lm<br>5700K: 2400 Lm | Dimmable                 | No                      |
| Efficacy                 | 70-80 LPW  | Replaces                 | Up to 100W HID          |
| Rated LED<br>Life        | Up to 50,000 Hrs.                                  | сст                      | 2700K<br>4200K<br>5700K |
| Power<br>Factor:         | >99  | CRI:                     | > 80                    |
| IR / UV                  | None   | Mercury/<br>Lead Content | None                    |
| Warranty                 | 5 year Limited                                     | Dimensions               | 5.75"<br>X 4.75"        |

Note: All specification information falls within a  $\pm$  2% range and is subject to change without notice.

NOTE: Light Efficient Design is providing this information to the general public. Please note that all products contained herein are trademarked, copyrighted, and/or have patents pending. Any use of these designs is strictly prohibited without prior written consent. Light Efficient Design protects its proprietary information vigorously in the courts of the United States of America.

