

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS														
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY		
HID RETROFITS: LED SITE / WAREHOUSE / UTILITY SERIES																	
WALL PACK / SHOE BOX / POLE TOP HID RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL														
	LED-8088E 50W SHOEBOX/ WALL PACK TYPE V OPTICS	LED-8088E40	6079	50W	116	175W	E26 Edison	4000K	>80	TYPE V	7.87" X 3.75"	1.26		Type V Optics Only	9		
		LED-8088E57	5984	50W	115	175W	E26 Edison	5700K	>80	TYPE V	7.87" X 3.75"	1.26			9		
	LED-8088M 50W SHOEBOX/ WALL PACK TYPE V OPTICS	LED-8088M40	6079	50W	116	175W	E39 Mogul	4000K	>80	TYPE V	8.47" X 3.75"	1.30		Type V Optics Only	9		
		LED-8088M57	5984	50W	115	175W	E39 Mogul	5700K	>80	TYPE V	8.47" X 3.75"	1.30			9		
	LED-8089M 80W SHOEBOX/ WALL PACK TYPE V OPTICS	LED-8089M40	6910	80W	86	250W	E39 Mogul	4000K	73	TYPE V	11.4" X 4.3"	2.35		Only Type V optics are available on LED- 8089M	9		
		LED-8089M50	7403	80W	92	250W	E39 Mogul	5000K	70	TYPE V	11.4" X 4.3"	2.35			9		
	LED-8090M 120W SHOEBOX/ WALL PACK TYPE V OPTICS	LED-8090M40	9561	120W	81.5	400W	E39 Mogul	4000K	84	TYPE V	11.4" X 4.3"	2.35			9		
		LED-8090M50	10434	120W	92	400W	E39 Mogul	5000K	77	TYPE V	11.4" X 4.3"	2.35			9		
	LED-8090M 120W SHOEBOX/ WALL PACK TYPE IV OPTICS	LED-8090M4T4	9561	120W	81.5	400W	E39 Mogul	4000K	84	TYPE IV	11.4" X 4.3"	2.35			9		
		LED-8090M5T4	10416	120W	92	400W	E39 Mogul	5000K	77	TYPE IV	11.4" X 4.3"	2.35			9		
	LED-8090M 120W SHOEBOX/ WALL PACK TYPE III OPTICS	LED-8090M4T3	9561	120W	81.5	400W	E39 Mogul	4000K	84	TYPE III	11.4" X 4.3"	2.35			9		
		LED-8090M5T3	10416	120W	92	400W	E39 Mogul	5000K	77	TYPE III	11.4" X 4.3"	2.35			9		

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY
 HID RETROFITS: High Bay / Low Bay / Parking Garage / Fuel Canopy															
LOW BAY / GARAGE HID RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/C												
	LED-8025E 52W PARKING GARAGE/ LOW BAY	LED-8025E42	5413	52W	103.5	175W	E26 Edison	4200K	84.4	360°	5.91" X 7.8"	2.64			4
		LED-8025E57	5193	52W	98.9	175W	E26 Edison	5700K	86	360°	5.91" X 7.8"	2.64			4
	LED-8025M 52W PARKING GARAGE/ LOW BAY E39	LED-8025M42	5413	52W	103.5	175W	E39 Mogul	4200K	84.4	360°	6.6" X 7.8"	2.64			4
		LED-8025M57	5193	52W	98.9	175W	E39 Mogul	5700K	86	360°	6.6" X 7.8"	2.64			4
	LED-8035E 60W PARKING GARAGE/ LOW BAY w/ UP-LIGHT	LED-8035E42	5993	60W	98.3	175W	E26 Edison	4200K	84.6	360°	5.91" X 7.8"	2.64			4
		LED-8035E57	5979	60W	98.35	175W	E26 Edison	5700K	85.5	360°	5.91" X 7.8"	2.64			4
HIGH BAY HID RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/C												
	LED-8036M 100W LOW BAY/ HIGH BAY (REPLACES 8026M)	LED-8036M42	10698	100W	108.6	250W	E39 Mogul	4200K	84	360°	7.6" X 7.9"	2.76			4
		LED-8036M57	10465	100W	103.5	250W	E39 Mogul	5700K	86.2	360°	7.6" X 7.9"	2.76			4
	LED-8030M 150W HIGH BAY w/UP-LIGHT	LED-8030M42	15515	150W	102.7	400W	E39 Mogul	4200K	84.1	360°	9.2" X 9.1"	3.85			2
		LED-8030M57	15515	150W	102.1	400W	E39 Mogul	5700K	84.1	360°	9.2" X 9.1"	3.85			2
	LED-8032M 150W HIGH BAY	LED-8032M42	15020	150W	101.4	400W	EX39	4200K	84.3	360°	9.4" X 9.1"	3.96			2
		LED-8032M57	14149	150W	95.1	400W	EX39	5700K	86.3	360°	9.4" X 9.1"	3.96			2

Product List

MODEL	DESCRIPTION	USA MODEL NUMBER	PRODUCT SPECIFICATIONS												CTN QTY
			INITIAL LUMENS	POWER USED	LPW	REPLACES	BASE	CCT	CRI	LED/LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	
	HIGH BAY LUMINAIRE 16" PC Globe	LED-9101M	N/A	N/A	N/A	N/A	E39 Mogul	N/A	N/A	N/A	16.2" X 16.8"				1



HID RETROFITS: PAR38 / BR40 RECESSED FIXTURES

PAR38 / RECESSED HID RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	LED-8055E 30W PAR38 HIGH POWER	LED-8055E27	1868	30W	62.9	100W	E26 Edison	2700K	82.3	120°	5.8" x 4.7"	1.32			4 / -
		LED-8055E42	2194	30W	73.9	100W	E26 Edison	4200K	83.7	120°	5.75" x 4.7"	1.32			4 / -
		LED-8055E57	2187	30W	72.9	100W	E26 Edison	5700K	83.1	120°	5.75" x 4.7"	1.32			4 / -
	LED-8055M 30W PAR38 HIGH POWER E39	LED-8055M27	1868	30W	62.9	100W	E39 Mogul	2700K	82.3	120°	5.8" x 4.7"	1.32			4 / -
		LED-8055M42	2194	30W	73.9	100W	E39 Mogul	4200K	83.7	120°	5.75" x 4.7"	1.32			4 / -
		LED-8055M57	2187	30W	72.9	100W	E39 Mogul	5700K	83.1	120°	5.75" x 4.7"	1.32			4 / -
	LED-8045M 50W PAR38 HIGH POWER	LED-8045M27	3478	50W	66.7	175W	E39 Mogul	2700K	81.2	45°	7" x 4.7"	1.78		Note: Transitioning from 5700K to 5000K	4 / -
		LED-8045M42	4613	50W	90.3	175W	E39 Mogul	4200K	81.9	45°	7" x 4.7"	1.78			4 / -
		LED-8045M57/LED-8045M50	4480	50W	88.9	175W	E39 Mogul	5000K/5700K	72.5	45°	7" x 4.7"	1.78			4 / -



HID RETROFITS: LED SITE / POST TOP / BOLLARD SERIES

EXTERNAL DRIVER POST TOP / AREA RETROFIT			SPECIFICATIONS: 0-10V DIMMING • IP65 • VOLTAGE: USA 120-277VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	LED-8084M 45W POST TOP / SITE LIGHTING EXTERNAL DRIVER DIMMABLE	LED-8084M42	4273	45W	93.4	175W	E39 Mogul	4200K	84.4	360°	10.5" X 3.93"	2.24		3 Way Dimmable Driver: 0-10V,	4
		LED-8084M57	4509	45W	96.9	175W	E39 Mogul	5700K	85.8	360°	10.5" X 3.93"	2.34			4

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS													
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY	
	LED-8085M 60W POST TOP / SITE LIGHTING	LED-8085M42	5807	60W	101.5	250W	E39 Mogul	4200K	96.2	360°	10.5" X 3.93"	2.34		PWM, and Resistive Dimming	4	
	EXTERNAL DRIVER DIMMABLE	LED-8085M57	6130	60W	107.4	250W	E39 Mogul	5700K	84.7	360°	10.5" X 3.93"	2.34			4	
POST TOP / SHOE BOX RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/C													
	LED-8033E 38W POST TOP / SITE LIGHTING	LED-8033E30	3889	38W	99.9	175W	E26 Edison	3000K	81	360°	9.53" X 3.15"	1.21			9	
		LED-8033E42	4367	38W	116	175W	E26 Edison	4200K	84.5	360°	9.53" X 3.15"	1.21			9	
		LED-8033E57	4275	38W	116	175W	E26 Edison	5700K	86.4	360°	9.53" X 3.15"	1.21			9	
	LED-8024E 45W POST TOP / SITE LIGHTING w/STD BASE	LED-8024E30	4969	45W	111.9	175W	E26 Edison	3000K	84.4	360°	9.22" X 3.15"	1.23			9	
		LED-8024E42	5361	45W	118.9	175W	E26 Edison	4200K	84.4	360°	9.22" X 3.15"	1.23			9	
		LED-8024E57	5037	45W	111.7	175W	E26 Edison	5700K	86	360°	9.22" X 3.15"	1.23			9	
	LED-8024M 45W POST TOP / SITE LIGHTING w/MOGUL BASE	LED-8024M30	5107	45W	112	175W	E39 Mogul	3000K	84.4	360°	9.75" X 3.25"	1.23			9	
		LED-8024M42	5146	45W	116	175W	E39 Mogul	4200K	84.2	360°	9.75" X 3.25"	1.23			9	
		LED-8024M57	5297	45W	116	175W	E39 Mogul	5700K	85.8	360°	9.75" X 3.25"	1.23			9	
	LED-8046M 65W POST TOP / SITE LIGHTING w/MOGUL BASE	LED-8046M30	5850	65W	90	250W	E39 Mogul	3000K	81	360°	11.22" X 3.98"	1.80		SPECIAL ORDER*	6	
		LED-8046M42	6350	65W	96.6	250W	E39 Mogul	4200K	82.2	360°	11.22" X 3.98"	1.80			6	
		LED-8046M57	6497	65W	100	250W	E39 Mogul	5700K	80.9	360°	11.22" X 3.98"	1.80			6	
	LED-8027M 100W POST TOP / SITE LIGHTING	LED-8027M30	10603	100W	105.92	250W	E39 Mogul	3000K	84.6	360°	11.9" X 4.9"	2.86		SPECIAL ORDER*	4	
		LED-8027M42	10669	100W	110.8	250W	E39 Mogul	4200K	84.6	360°	11.9" X 4.9"	2.86			4	
		LED-8027M57	10083	100W	105.36	250W	E39 Mogul	5700K	86.8	360°	11.9" X 4.9"	2.86			4	

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS													
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY	
MINI POST TOP / BOLLARD / JELLY JAR HID RETROFITS			GENERAL SPECIFICATIONS: VOLTAGE: USA/CANADA 120-277VAC • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL													
	LED-8039E 20W BOLLARD / JELLY JAR / SITE LIGHTING	LED-8039E30	1845	20W	9601	70W	E26 Edison	3000K	84	360°	5.7" X 2.75"	0.55		120-277V Only	9	
		LED-8039E42	1961	20W	102.7	70W	E26 Edison	4200K	84.9	360°	5.7" X 2.75"	0.55			9	
		LED-8039E57	2014	20W	104.4	70W	E26 Edison	5700K	86.7	360°	5.7" X 2.75"	0.55			9	
MINI POST TOP / BOLLARD / JELLY JAR HID RETROFITS																
	LED-8028E 21W BOLLARD / POST TOP / SITE LIGHTING	LED-8028E30	2059	21W	95.7	70W	E26 Edison	3000K	84.5	360°	6.61" X 3.15"	0.81		Obsolete, inventory remaining	9	
		LED-8028E42	2073	21W	99.2	70W	E26 Edison	4200K	84.4	360°	6.61" X 3.15"	0.81			9	
		LED-8028E57	1991	21W	94.4	70W	E26 Edison	5700K	85.5	360°	6.61" X 3.15"	0.81			9	
	LED-8029E 24W BOLLARD / POST TOP / SITE LIGHTING	LED-8029E30	2320	24W	96.3	100W	E26 Edison	3000K	84.5	360°	7.1" X 3.15"	0.88			9	
		LED-8029E42	2319	24W	100	100W	E26 Edison	4200K	84.4	360°	7.1" X 3.15"	0.88			9	
		LED-8029E57	2366	24W	94.3	100W	E26 Edison	5700K	85.6	360°	7.1" X 3.15"	0.88			9	
	LED-8029M 24W BOLLARD / POST TOP / SITE LIGHTING	LED-8029M30	2317	24W	97	100W	E39 Mogul	3000K	84.8	360°	7.6" X 3.15"	0.88			9	
		LED-8029M42	2225	24W	97.2	100W	E39 Mogul	4200K	85.6	360°	7.6" X 3.15"	0.88			9	
		LED-8029M57	2387	24W	101	100W	E39 Mogul	5700K	85	360°	7.6" X 3.15"	0.88			9	
LED FLUORESCENT RETROFIT SERIES- UL LISTED																
LED Retrofit for PL Lamps			SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CAN 120-347V • NON-DIM • 36,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/C													
	PL LED 9W G24q 4 PIN Omni-Directional	LED- 7310-40A	750	9W	95	26W	G24q	4000K	83	360°	6.8"X 1.4"	0.40		25000 Hr. LED Life 120-277v	12 / -	
	PL LED 10W G24d 2 PIN Horizontal Mounting	LED-7302-35A	932	10W	93.08	26W	G24d	3500K	85.4	180°	5.5"X 2.2"	0.40			12	
		LED- 7302-42A	1013	10W	100.8	26W	G24d	4200K	84.9	180°	5.5"X 2.2"	0.40			12	

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS													
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY	
	PL LED 10W G24q 4 PIN Horizontal Mounting	LED-7304-35A	920	10W	93	26W	G24q	3500K	85	180°	5.5"X 2.2"	0.40				12
		LED- 7304-42A	1032	10W	101	26W	G24q	4200K	85	180°	5.5"X 2.2"	0.40				12
	PL LED 10W G24d 2 PIN Vertical Mounting	LED-7306-35A	1043	10W	90.7	26W	G24d	3500K	82.5	120°	6.11"X 3.78"	0.73				6
		LED- 7306-42A	1071	10W	90.8	26W	G24d	4200K	84.6	120°	6.11"X 3.78"	0.73				6
	PL LED 10W G24q 4 PIN Vertical Mounting	LED-7308-35A	1085	10W	85.5	26W	G24q	3500K	82.4	120°	6.11"X 3.78"	0.73				6
		LED- 7308-42A	1037	10W	90.2	26W	G24q	4200K	85	120°	6.11"X 3.78"	0.73				6
T8 LINEAR - DOUBLE END POWER INTERNAL DRIVER BALLAST COMPATIBLE			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC • NON-DIM • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL • FULL CARTONS ONLY													
4' T8 LED Ballast Compatable	4' T8 LED 17W FROSTED LENS works with Instant Start Ballasts	LED-6204 -UL-4-40K-BFR	1880	18W	104	32W	G13	4000K	>80	120°	47.2 X 1.125"	1.30	DLC Listed	Full Carton Only or 15% Broken Package Charge will apply		35
T8 LINEAR -SINGLE END POWER - 2015 MODEL INTERNAL DRIVER			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC • NON-DIM • 50,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL • FULL CARTONS ONLY													
4' T8 LED	4' T8 LED18W FROSTED LENS	LED-6115 -UL-4-40K-BFR	1880	18W	104	32W	G13	4000K	>80	120°	47.2 X 1.125"	1.30	DLC Listed	Full Carton Only or 15% Broken Package Charge will apply		35
		LED-6115 -UL-4-57K-BFR	1880	18W	104	32W	G13	5700K	>80	120°	47.2 X 1.125"	1.30				35
2' T8 LED	2' T8 LED 10W FROSTED LENS	LED-6111 -UL-2-40K-BFR	1000	10W	100	17W	G13	4000K	>80	120°	23.1 X 1.125"	1.27	DLC Listed	SPECIAL ORDER 90 MOQ		35
3' T8 LED	3' T8 LED 12.7W FROSTED LENS	LED-6123 -UL-3-40K-BFR	1346	12.7W	105	25W	G13	4000K	>80	120°	35.1 X 1.125"	1.30				35

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												CTN QTY
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	
T8 LINEAR - INTERNAL DRIVER - 2014 MODEL			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC • NON-DIM • 50,000 HR RATED LIFE • 5 YR LIMITED WARRANTY •												
4' T8 LED	4' T8 LED17W CLEAR LENS	LED-6114-00- UL-4-NW-N	1650	17.2W	95	32W	G13	3000K	>80	120°	47.2 X 1.125"	1.30	2014 MODEL OBSOLETE WHEN INVENTORY IS DEPLETED		24/12
		LED-6116-00- UL-4-DL-N	1947	17.2W	116	32W	G13	5700K	>80	120°	47.2 X 1.125"	1.30			24/12
2' T8 LED	2' T8 LED 10W CLEAR LENS	LED-6111-00- UL-2-CW-N	1000	10W	100	17W	G13	4000K	>80	120°	23.1 X 1.125"	1.27			24/12
		LED-6112-00- UL-2-DL-N	1050	10W	105	17W	G13	5700K	>80	120°	23.1 X 1.125"	1.27			24/12
3' T8 LED	3' T8 LED 12.7W CLEAR LENS	LED-6118-00 UL-3-DL-N	1611	12.7W	126	25W	G13	5700K	>80	120°	35.1 X 1.125"	1.30			24/12
INCANDESCENT / HALOGEN LED RETROFIT LAMPS															
PAR20'S			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	PAR20 8W 50W REPLACEMENT	LED-1735-30K-B	619	8W	79	50W	E26 Edison	3000K	81	40°	3.54" X 2.48"	0.38		Discontinued 1/1/16	100
		LED-1735-50K-B	636	8W	75.5	50W	E26 Edison	5000K	84	40°	3.54" X 2.48"	0.38			100
PAR30'S			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	PAR30 13W 75W REPLACEMENT	LED-1736-30K-B	830	13W	65	75W	E26 Edison	3000K	80	40°	4.5" X 3.5"	0.63		Discontinued 1/1/16	25
		LED-1736-50K-B	1006	13W	79	75W	E26 Edison	5000K	81	40°	4.5" X 3.5"	0.63			25
		LED-1736-50K-277	1000	13W	79	75W	E26 Edison	5000K	81	40°	4.5" X 3.5"	0.63			25
PAR38'S			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	PAR38 17W 100W REPLACEMENT	LED-1737-30K-B	1298	17W	80	100W	E26 Edison	3000K	81	40°	5.2" X 4.6"	1.08		Discontinued 1/1/16	16
		LED-1737-50K-B	1530	17W	92	100W	E26 Edison	5000K	83	40°	5.2" X 4.6"	1.08			16
		LED-1737-50K-277	1530	17W	92	100W	E26 Edison	5000K	83	40°	5.2" X 4.6"	1.08			16
BR SERIES			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	BR30 12W 75W REPLACEMENT	LED-1739-30K-B	912	12W	76	75W	E26 Edison	3000K	83	120°	5.3" X 3.75"	0.68		Discontinued 1/1/16	25
		LED-1739-50K-B	944	12W	79	75W	E26 Edison	5000K	87	120°	5.3" X 3.75"	0.68			25
		LED-1739-50K-277	944	12W	79	75W	E26 Edison	5000K	87	120°	5.3" X 3.75"	0.68			25

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY
	BR40 17W 120W REPLACEMENT	LED-1740-27K	1111	17W	68	120W	E26 Edison	2700K	80	120°	6.4" X 5.0"	1.03		Discontinued 1/1/16	16
		LED-1740-50K	1160	17W	71	120W	E26 Edison	5000K	82	120°	6.4" X 5.0"	1.03			16
		LED-1740-50K-277	1100	17W	71	120W	E26 Edison	5000K	80	120°	6.4" X 5.0"	1.03			16
OUTDOOR PAR			GENERAL SPECIFICATIONS: IP65 • VOLTAGE: USA 120VAC • NON-DIM • 35,000 HR RATED LIFE • 2 YR LTD WARRANTY • UL/CUL												
	PAR20 3W OUTDOOR	LED-1680-B	240	3W	57	20W	E26 Edison	2700K	70	120°	3.5"X 2.5"	0.14		Discontinued 1/1/16	16
	PAR30 4W OUTDOOR	LED-1671-B	320	4W	62	35W	E26 Edison	2700K	70	120°	3.9" x 3.82"	0.23			16
	PAR38 7W OUTDOOR	LED-1676-B	650	7W	72	50W	E26 Edison	2700K	70	120°	5.5" X 4.9"	0.32			16
MR16			GENERAL SPECIFICATIONS: VOLTAGE: USA 12VAC/DC • NON-DIMMABLE 5 YEAR LIMITED WARRANTY • UL/CUL												
	MR16 3W 20W REPLACEMENT	LED-4200	160	3W	53	20W	GU5.3	3000K	70	38°	1.75" x 1.87"	0.13		Discontinued 1/1/16	100
		LED-4201	200	3W	66	20W	GU5.3	4500K	70	38°	1.75" x 1.87"	0.13			100
MR16 HIGH POWER			GENERAL SPECIFICATIONS: VOLTAGE: USA 12VAC/DC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	MR16 7W 50W REPLACEMENT	LED-4250-27K-B	401	7W	62	45W	GU5.3	2700K	80	40°	1.87" x 1.87"	0.13		Discontinued 1/1/16	200
		LED-4250-50K-B	468	7W	69	50W	GU5.3	5000K	86	40°	1.87" x 1.87"	0.13			200
GU10 HIGH POWER			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIM • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL												
	GU10 7W 50W REPLACEMENT	LED-5250-27K -B	401	7W	62	40W	GU10	2700K	80	40°	1.9" x 1.9"	0.15		Discontinued 1/1/16	200
		LED-5250-50K-B	439	7W	69	40W	GU10	5000K	86	40°	1.9" x 1.9"	0.15			200
AMBER / TURTLE SAFE			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC (EXCEPT LED-8039, LED-4270) • 25,000 HR RATED LIFE • 5 YR LTD WARRANT												
	LED-8039 AMBER	LED-8039EAMB	576	15W	32	70W	E26 Edison	590nm	>80	360°	5.7" X 2.75"	0.55		120-277V 50,000 HOURS NON DIMMABLE	9
	MR16 AMBER	LED-4270	150	5W	30	15W	GU5.3	590nm	30	30°	1.75" X 2"	0.10			200
	PAR20 AMBER	LED-1730	200	6W	33	20W	E26 Edison	590nm	30	30°	3.4" X 2.4"	0.38			100

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS														
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY		
	PAR30 AMBER	LED-1731-B	350	12W	35	40W	E26 Edison	590nm	30	40°	4.25" X 3.75"	0.63		Discontinued 1/1/16		25	
	PAR38 AMBER	LED-1732-B	500	17W	33	50W	E26 Edison	590nm	30	40°	5.4" X 4.75"	1.03				16	
	A19 AMBER	LED-1733	225	7W	32	25W	E26 Edison	590nm	30	120°	5.75" x 2.3"	1.03				40	
A-19 SERIES			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 25,000 HR RATED LIFE • 5 YR LTD WARRANTY • UL/CUL														
	A19 9.5W 60W REPLACEMENT	LED-1029-27K-B	800	9.5W	84	60W	E26 Edison	2700K	>80	220°	4.5" X 2.5"	1.03		Discontinued, limited inventory available		24	
	A19 7W 40W REPLACEMENT	LED-1028-27K-B	480	7W	68	40W	E26 Edison	2700K	>80	220°	4.5" X 2.5"	1.03				24	
CANDELABRA WITH E-12 BASE			GENERAL SPECIFICATIONS: VOLTAGE: USA 120VAC • DIMMABLE • 35,000 HR RATED LIFE • 5 YR LIMITED WARRANTY • UL/CUL														
	CANDLE 3W FLAME 25W REPLACEMENT	LED-3025	155	3W	52	25W	E12	2700K	83	240°	4.4" X 1.25"	0.10		Discontinued 1/1/16		50	
		LED-3025-2200	155	3W	52	25W	E12	2200K	83	240°	4.4" X 1.25"	0.10				50	
	CANDLE 3W TORPEDO 25W REPLACEMENT	LED-3026	160	3W	53	25W	E12	2700K	83	240°	4.2 X 1"	0.09				50	
		LED-3026-2200	160	3W	53	25W	E12	2200K	83	240°	4.2 X 1"	0.09				50	

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY
 HIGH POWER LIGHTING FOR HORTICULTURE															
			PRODUCT SPECIFICATIONS												
	DESCRIPTION	USA / CANADA MODEL NUMBER	INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	SPECTRUM	LED/ LAMP BEAM ANGLE	PRODUCT DIMENSION L x W x H	PRODUCT WEIGHT (LBS)	OTHER CERT	COMMENTS	MST/ SUB- PACK QTY	
OVERHEAD / PRIMARY GROW LAMPS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC/CANADA 120-347VAC • 50,000 HR LIFE • 5 YR LTD WARRANTY • UL												
	LED-8025 52W OVERHEAD	LED-8025EGE	N/A	52W	N/A	175W	E26 Edison	R/G/B RB - 20% Red - 60% 3000K - 20%	120°	5.91" X 7.8"	2.64			4	
	LED-8026 100W OVERHEAD	LED-8026MGE	N/A	100W	N/A	250W	E39 Mogul	R/G/B RB - 20% Red - 60% 3000K - 20%	120°	7.6" X 7.9"	2.77			4	
	LED-8032 150W OVERHEAD	LED-8032MGB / LED- 8032MGBC	N/A	150W	N/A	400W	E39 Mogul	R/G/B + UV	120°	9.0" DIA X 9.25" H	3.40			2	
SUPPLEMENTAL GROW LAMPS															
SUPPLEMENTAL GROW LAMPS			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC • 50,000 HR RATED LIFE • 5 YR LIMITED WARRANTY • UL APPROVED												
	LED-8055 PAR38 30W (Royal Blue/Red/White)	LED-8055EGE	N/A	30W	N/A	100W	E26 Edison	R/G/B RB - 20% Red - 60% 3000K - 20%	120°	5.75" x 4.7"	1.98 LBS			4	
			GENERAL SPECIFICATIONS: VOLTAGE: USA 120-277VAC • 50,000 HR RATED LIFE • 5 YR LIMITED WARRANTY • UL APPROVED												
	48" T8 LED 17W GROW LAMP CLEAR LENS (Royal Blue/Red/White)	LED-6114-00- UL-4-GE-N	N/A	17.2W	N/A	32W	G13	R/W/B BLUE - 20% RED - 60% 3000K - 20%	120°	47.2 X 1.125"	1.30			12	

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS													
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	CTN QTY	
COMMERCIAL GROW LIGHT FIXTURE			GENERAL SPECIFICATIONS: VOLTAGE: 120-277VAC OR 200-480 VAC • 50,000 HR LIFE • 5 YR LTD WARRANTY • UL												1	
	150 Watt Grow Light. High-Bay style. UL. IP65 120-277 VAC	LED-9630G	N/A	150W	N/A	up to 400W	N/A	FULL SPECTRUM R/W/B BLUE - 20% 3000K - 40% RED - 40%	120°	16.5" dia x 7.5" height (including bracket)	15.00	WET LOCATION IP65			1	
	150 Watt Grow Light. High-Bay style. UL. IP65 200-480 VAC	LED-9630G-HV	N/A	150W	N/A	up to 400W	N/A	FULL SPECTRUM R/W/B BLUE - 20% 3000K - 40% RED - 40%	120°	16.5" dia x 7.5" height (including bracket)	15.00	WET LOCATION IP65			1	
GROW LIGHT FIXTURE			GENERAL SPECIFICATIONS: VOLTAGE: USA 100-277 VAC • 2 YR LIMITED WARRANTY • CE													
	90 WATT PROGRAMMABLE GROW LIGHT	LED-9610G	N/A	90 W	N/A	UP TO 150 W	N/A	3 CH VEG /BLOOM/GROW/ ALL-ON. FULL SPECTRUM WITH UV, IR.	78° TO 105°	9 x 9 x 3	3.80	CE	SPECIAL ORDER		4	
	180 WATT PROGRAMMABLE GROW LIGHT	LED-9611G	N/A	180 W	N/A	UP TO 300W	N/A	3 CH VEG /BLOOM/GROW/ ALL-ON. FULL SPECTRUM WITH UV, IR.	78° TO 105°	9 x 15 x 3	6.60	CE			4	
	270 WATT PROGRAMMABLE GROW LIGHT	LED-9612G	N/A	270 W	N/A	UP TO 450W	N/A	3 CH VEG /BLOOM/GROW/ ALL-ON. FULL SPECTRUM WITH UV, IR.	78° TO 105°	21 x 9 x 3	9.50	CE	SPECIAL ORDER		4	
	360 WATT PROGRAMMABLE GROW LIGHT	LED-9613G	N/A	360 W	N/A	UP TO 600 W	N/A	3 CH VEG /BLOOM/GROW/ ALL-ON. FULL SPECTRUM WITH UV, IR.	78° TO 105°	15 x 15 x 3	11.60	CE			2	
	540 WATT PROGRAMMABLE GROW LIGHT	LED-9614G	N/A	540 W	N/A	UP TO 1000W	N/A	3 CH VEG /BLOOM/GROW/ ALL-ON. FULL SPECTRUM WITH UV, IR.	78° TO 105°	21 x 15 x 3	15.90	CE			2	

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												CTN QTY
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS	
	REMOTE CONTROL	LED-9620GA	N/A		N/A		N/A								1
	Power Cable (Plug-in)	LED-9623GA													1
DAISY POWER CABLE	18"	LED-9621GA													1
	36"	LED-9624GA													1
	72"	LED-9626GA													1
DAISY CHAIN CONTROL CABLE	18"	LED-9622GA													1
	36"	LED-9625GA													1
	72"	LED-9627GA													1

POOL AND SPA LAMPS

MODEL	DESCRIPTION	USA MODEL NUMBER	INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	PRODUCT DIMENSION L x W x H	PRODUCT WEIGHT (LBS)	OTHER CERT	COMMENTS	MST/ SUB- PACK QTY
	LED-8055 30W PAR38 POOL AND SPA COLOR CHANGING	LED-8055EC	N/A	30W	70	>300w Halogen	E26 Edison	N/A	>80	120°	5.8" x 4.7"	1.45 LBS			4
	LED-8055 30W PAR38 POOL AND SPA WHITE LED	LED-8055EW	N/A	30W	70	>300w Halogen	E26 Edison	N/A	>80	120°	5.8" x 4.7"	1.45 LBS			4

Accessories

	INTERMATIC ARREST- GUARD FOR LIGHTNING / SURGE PRONE INSTALLATIONS	MODEL NUMBER	TYPE	ENCLOSURE	POLES	NOM DISCH CUR	PRODUCT DIMENSION LxW	PRODUCT WEIGHT	WAR		MST/ SUB- PACK QTY
		AG2401C3	SINGLE PHASE, 120/240V, 3 WIRE, 18" LEAD, OUTDOOR ENCLOSURE	TYPE 4 RAINPROOF	1 OR 2	20,000A	4" X 3.75"		1 YR.	✓	1
		AG48013	SINGLE PHASE, 277/480V, 3 WIRE, 18" LEAD, OUTDOOR ENCLOSURE	TYPE 4 RAINPROOF	1 OR 2	20,000A	4.4 X 1"		1 YR.	✓	1
		AG6503C3	THREE PHASE, 347/600V, 4 WIRE, 36" LEAD, OUTDOOR ENCLOSURE	TYPE 4 RAINPROOF	3	20,000A	4.4 X 1"		1 YR.	✓	1

Product List

		USA MODEL NUMBER	PRODUCT SPECIFICATIONS												CTN	QTY
MODEL	DESCRIPTION		INITIAL LUMENS	POWER USED	LPW	REPL ACES	BASE	CCT	CRI	LED/ LAMP BEAM ANGLE	DIMENSION L x W x H	WEIGHT (LBS)	OTHER CERT	COMMENTS		

General Policies and Procedures:

Send orders to: orders@led-llc.com

Freight Policy: Prepaid at \$2000 order level

Freight: FOB Warehouse at \$2000 on approved programs. Special order FOB Warehouse/ FOB Factory. Net 30 on approved credit (COD orders are not applicable). 50% upfront required for all special orders (100 pcs MOQ).

Shipments: All shortages and or incorrect shipments must be reported within 10 days of delivery

Terms: Net 30, A rate of 1.5% per month may be added to any past due balances.

Return Policy/Process

1. All return requests (including warranty) should be sent to returns@led-llc.com.
2. All non-warranty return requests must be made with 10 days of delivery, a 15% re-stocking charge will apply.
3. RGA form will be generated with instructions on how to proceed. All returns of product must include an RGA form.
4. Replacement orders are required for all warranty replacements
5. Replacement orders will be invoiced upon shipment and a possible credit may be given after receipt and evaluation of returned items.

Warranty: 5 year, 3 year or 2 year warranty based on maximum bulb usage of 12 hrs per day. See www.led-llc.com for full warranty statement.

Contact information: Phone: 847-380-3540 Fax: 847-380-3542

LIGHT EFFICIENT DESIGN, LLC • 188 S. Northwest Highway • Cary, IL 60013 • (847) 380-3540 • www.led-llc.com