

BFS BULLET FLOODLIGHT (1/2" Knuckle Mount)

PROJECT: _____

SCHEDULE: _____ DATE: _____

PREPARE BY: _____

NOTES: _____

DESCRIPTION

naturaLED® Bullet Flood light (BFS) delivers exceptional illumination performance to landscape and security lighting. Our Bullet Flood light provides beam angle distribution of 40°, rated IP65, and comes with 1/2" NPT knuckle mount. Creating bright, security and spot lighting for a variety of applications such as perimeter, entryway, facades, landscapes, retail and residential complexes and architectural lighting.



Rated Life 50,000 Hours
Warranty 5 Years

APPLICATIONS

Security, Architectural, Perimeter, Entryway, Pathway, Landscape

FEATURES

- Energy Star
- IP65 Rated
- ETL Listed
- Long life LED chips
- ColorTemp: 3000K, 5000K
- Beam Angle: 40°
- Input line voltage: 120-277V
- CRI: 80
- Surge Protection: 2KV
- Powerfactor >0.9
- 1/2" NPT threaded knuckle mount
- Material: Aluminum die-cast housing
- Voltage Frequency (Hz): 50/60
- Operating temperature: -22°F - 122°F
- 5 Year Warranty
- Finish Color: Bronze

SAMPLE NUMBER LED-FXBFS10/40/830/BZ-KNC

STYLE	SERIES	FAMILY	WATTAGE	BEAM ANGLE	COLOR TEMP	COLOR	ACCESSORY
LED	FX	BFS	10	40	830	BZ	KNC
LED Lighting	Fixture	Bullet Floodlight	10 Watt	40°	CRI 80 3000K	Bronze	1/2" Knuckle




ORDERING

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Knuckle	IP65 Rated	Energy Star
10	9291	LED-FXBFS10/40/830/BZ-KNC	3000K	900	100	1/2"	•	•
10	9292	LED-FXBFS10/40/850/BZ-KNC	5000K	900	100	1/2"	•	•
21	9293	LED-FXBFS20/40/830/BZ-KNC	3000K	1,800	150	1/2"	•	•
21	9294	LED-FXBFS20/40/850/BZ-KNC	5000K	1,800	150	1/2"	•	•

DIMENSIONS



10W / 21W
1.50-lbs



PHOTOMETRICS CHART

10 Watt
Energy Star

21 Watt
Energy Star



Center Beam fc	Beam Width
2.5R	2.15 fc 2.2 ft 2.2 ft
5.0R	53.7 fc 4.4 ft 4.5 ft
7.5R	23.9 fc 6.6 ft 6.7 ft
10.0R	13.4 fc 8.7 ft 9.0 ft
12.5R	8.60 fc 10.9 ft 11.2 ft
15.0R	5.97 fc 13.1 ft 13.4 ft

■ Vert. Spread: 47.2°
■ Horiz. Spread: 46.3°

Center Beam fc	Beam Width
2.5R	420 fc 2.2 ft 2.2 ft
5.0R	105 fc 4.3 ft 4.4 ft
7.5R	46.7 fc 6.5 ft 6.5 ft
10.0R	26.3 fc 8.6 ft 8.7 ft
12.5R	15.8 fc 10.8 ft 10.9 ft
15.0R	11.7 fc 12.9 ft 13.1 ft

■ Vert. Spread: 46.6°
■ Horiz. Spread: 47.1°

PACKAGE

Case Qty 10 pcs

