

Version	2.0	Date	10/11/2021
Prepared By	C.L.		

PRODUCT SPECIFICATION

Category	Utility Strip Light
Item Number	7594
Stock Code	LED-FXUSL40/48FR/850/MV
Mounting	Surface / Ceiling / Chain
Housing Color	White + Frosted Lens



ELECTRICAL CHARACTERISTICS

Rated Wattage (W)	40	Replacement Wattage (W)	2 x 32W T8
Tested Wattage (W)	37.86		
Input Voltage (V)	120 ~277	Surge Protect Level	2KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.34 (@120V)	AUX (12V) Line	No
Power Factor	>0.9		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS

Lumen (lm)	5395	CCT (K)	5000
Efficacy (lm/w)	142	Beam Angle (°)	120
CRI	>80		

GENERAL CHARACTERISTICS


Operating Temperature (°F)	-4 ~ 131
Storage Temperature (°F)	-4 ~ 131
IP Rating	IP20
Rated Life	50000 hrs.
Warranty	5 years

ACCESSORIES

Item #	Stock Code	Description
7336	BAEM4-60BC/MV-A	120V ~ 277V 4W EM Driver
7334	BAEM15-48BC/MV-A	120V ~ 277V 15W EM Driver
P10234	SEN-MC605V-D	120V ~ 277V Microwave Motion Sensor
P10303	WG-USL/48/WH	Wireguard
P10429	BA-MTM00706227C	347V/480V to 277V Transformer (Max. 70W)

PRODUCT DIMENSIONS

Width- in (mm)	2.5" (63.5mm)
Height- in (mm)	2.9" (73mm)
Depth- in (mm)	48" (1219mm)
EPA (ft²)	N/A
Weight (lbs.)	3.85
Mounting Height (ft.)	>7.8
Cable Length (ft.)	2



CERTIFICATIONS

UL/ETL	cETLus	CEC	
NSF/ETL Sanitation		JAB	
Energy Star		FCC	✓
DLC	V5.1 Standard	RoHS	✓

DOCUMENTS

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS

--