

# ENERGY STAR® 2.0



## LED A-Line general purpose lamps

GE ENERGY STAR® rated LED A-Line lamps are the perfect low energy, long life replacements for standard incandescent, halogen and CFL lamps. New ENERGY STAR® 2.0 standards require lamps to be more efficient (higher LPW), and lower the minimum life rating to 15,000 hours. Take advantage of the ENERGY STAR® rating and check for utility rebates in your area.

### LOW COST OPERATION

- For example, a 60-watt incandescent replacement lamp using 10 watts of energy and producing 800 lumens can save over \$82 in energy costs over the rated life of the lamp vs. a standard 840 lumen, 60-watt incandescent A19 based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements vs. standard incandescent or halogen light sources

### EXCELLENT COLOR RENDERING

- Available with a CRI of 80

### COLOR TEMPERATURE

- Available in 2700K, 3000K, 4000K and 5000K

### LONG LIFE

- Up to 15,000 hours rated life (L70)

### DIMMABLE

- Dims from 100% to as low as 10%

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS



### GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)

**When you Think LED lighting, Think GE.**

## Product Specifications

Type	Base Type	Watts	Order Code	Description	Volts	Case Qty*	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information
<b>LED A-Line A-19</b>																
	MED		69115	LED6DA19/827	120	6	4.4	480	2700K	80	40W	15,000	Yes	★	Damp	White, Omni
			69118	LED6DA19/830	120	6	4.4	480	3000K	80	40W	15,000	Yes	★	Damp	White, Omni
			69132	LED6DA19/840	120	6	4.4	480	4000K	80	40W	15,000	Yes	★	Damp	White, Omni
			69144	LED6DA19/850	120	6	4.4	480	5000K	80	40W	15,000	Yes	★	Damp	White, Omni
			69117	LED10DA19/827	120	6	4.4	800	2700K	80	60W	15,000	Yes	★	Damp	White, Omni
			69119	LED10DA19/830	120	6	4.4	800	3000K	80	60W	15,000	Yes	★	Damp	White, Omni
			69133	LED10DA19/840	120	6	4.4	800	4000K	80	60W	15,000	Yes	★	Damp	White, Omni
			69146	LED10DA19/850	120	6	4.4	800	5000K	80	60W	15,000	Yes	★	Damp	White, Omni
<b>LED Bright Stik®</b>																
	MED		66256	LED5.5LS3/827	120	48	4.45	450	2700K	80	40W	15,000	-	★	Damp	Case = 16 3-packs
			75177	LED5.5LS3/850	120	48	4.45	450	5000K	80	40W	15,000	-	★	Damp	Case = 16 3-packs
			75184	LED9LS3/827	120	48	4.45	760	2700K	80	60W	15,000	-	★	Damp	Case = 16 3-packs
			75588	LED9LS3/850	120	48	4.45	760	5000K	80	60W	15,000	-	★	Damp	Case = 16 3-packs
			75590	LED12LS2/827	120	32	4.45	1060	2700K	80	75W	15,000	-	★	Damp	Case = 16 2-packs
			75591	LED12LS2/850	120	32	4.45	1060	5000K	80	75W	15,000	-	★	Damp	Case = 16 2-packs

Get more information at  
[GELighting.com/ThinkLED](http://GELighting.com/ThinkLED)

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.  
2) LED A19 Locking device works on PC, 85791, 85792, 89898, 62182, 89899 and 89900



Product is compliant with material restriction requirements of RoHS  
ENERGY STAR® is a registered U.S. Mark

**current**  
powered by GE

[www.currentbyge.com](http://www.currentbyge.com), [www.gelighting.com](http://www.gelighting.com)

Current, powered by GE, Current by GE, GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. Current, powered by GE, Current by GE, GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

LEDL038 (Rev. 02/01/16)